



# T8

## 10.5T8/MAS/48-840/MF16/P 10/1

Our TLEDs are available in InstantFit (Type A / Type C) or MainsFit (Ballast bypass / Type B) versions. The InstantFit lamps work on a broad variety of ballasts and LED drivers. Only InstantFit has over 15,000 lamp & ballast combinations delivering even light output, energy savings and a long lifetime. Our MainsFit products feature a double-ended design, simplifying installation while a proprietary safety circuit minimizes a shock risk. Lamp sizes range from 2-foot to 8-foot and U-bend with a variety of lumen outputs.

### Product data

General Information	
Base	G13 [ Medium Bi-Pin Fluorescent]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	70000 h
Switching Cycle	50000X
Light Technical	
Color Code	841 [ CCT of 4100K (841)]
Beam Angle (Nom)	180 °
Initial lumen (Nom)	1650 lm
Luminous Flux (Rated) (Nom)	1650 lm
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	157.00 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	0.7%
Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	10.5 W

Lamp Current (Max)	105 mA
Lamp Current (Min)	48 mA
Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.6 s
Power Factor (Nom)	0.9
Voltage (Nom)	120-277 V

Temperature	
T-Ambient (Max)	45 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	65 °C
T-Storage (Min)	-40 °C
T-Case Maximum (Nom)	70 °C

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Product Length	1200 mm

# T8

## Approval and Application


Energy Saving Product	Yes
Approbation Marks	RoHS compliance UL certificate DLC compliance

## Product Data

Order product name	10.5T8/MAS/48-840/MF16/P 10/1
EAN/UPC - Product	046677557362

Order code	557363
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929002325204
Net Weight (Piece)	0.120 kg
Model Number	9290023252



## Dimensional drawing



TLED T8 120-277V 10.5-32W 1650lm 4000K


Product	D1	D2	A1	A2	A3
10.5T8/MAS/48-840/MF16/P 10/1	25.7 mm	28 mm	1198 mm	1205 mm	1212 mm

## Photometric data





LEDtube\_10.5W\_G13\_840-GUL

LEDtube\_G13\_840-POC





LEDtube\_G13\_1-LDD

Lifetime




LEDtube\_70K-LED

LEDtube\_70K\_LifetimeVsTc-LED



LEDtube\_70K\_LumenVsTc-LMP

LEDtube\_70K\_FailureRate-LED



LEDtube\_70K-LMP

