# **PHILIPS** Lighting



# LED PAR38

# 10PAR38/LED/930/F40/DIM/GULW/T20 6/1FB

Philips LED spots with a single optic beam, provide a clean beam that's free from shadows with beam angles from 15 and 40 degrees to suit every general lighting application.

### **Product data**

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Nominal lifetime	25,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes
Light Technical	
Color Code	930 [CCT of 3000K]
Beam Angle (Nom)	40 degree(s)
Luminous Flux	900 lumen
Luminous Intensity (Nom)	1,900 cd
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	90.00 lm/W
Color Consistency	<4
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom) 70 %	

# Operating and Electrical

Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	10 W
Lamp Current (Nom)	97 mA


Wattage Equivalent	90 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	120 V
Temperature	
T-Case Maximum (Nom)	158 °F
Controls and Dimming	
Dimmable	Only with specific dimmers
Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Glass
Bulb Shape	PAR38 [PAR 4.75 inch/121mm]
Approval and Application	
Suitable For Accent Lighting	Yes
Energy Certifications	Energy Star
Product Data	
Order product name	10PAR38/LED/930/F40/DIM/GULW/T20
	6/1FB

# LED PAR38

Order code	567909
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929003029104
Full product name	10PAR38/LED/930/F40/DIM/GULW/T20
	6/1FB


EAN/UPC - Case	50046677567908	
EAN/UPC - Product/Case	046677567903	

#### **Dimensional drawing**




Product	D	с
10PAR38/LED/930/F40/DIM/GULW/T20 6/1FB	4-13/16 inch	5-1/8 inch

#### Photometric data



Spectral Power Distribution Colour - 10PAR38/LED/930/F40/DIM/ GULW/T20 6/1FB




Light Distribution Diagram - 10PAR38/LED/930/F40/DIM/GULW/T20 6/1FB

	1 x 929043429164 19W 2080K
	1 x 900 in
×	
Er if	


Accent Lighting Spots - 10PAR38/LED/930/F40/DIM/GULW/T20 6/1FB

## LED PAR38

#### Lifetime



Life Expectancy Diagram - 10PAR38/LED/930/F40/DIM/GULW/T20 6/1FB



Lumen Maintenance Diagram - 10PAR38/LED/930/F40/DIM/GULW/T20 6/1FB



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.