



PAR38 LED

33PAR38/PER/830/F25/DIM/120V B 6/1FB

Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Nominal Lifetime (Nom)	25000 h
Switching Cycle	50000X
Technical Type	33-250W
Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	25 °
Luminous Flux (Nom)	3000 lm
Luminous Flux (Rated) (Nom)	3000 lm
Luminous Intensity (Nom)	10000 cd
Color Designation	White (WH)
Rated Beam Angle	25 °
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	90.00 lm/W
Color Consistency	<4
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	33 W
Lamp Current (Nom)	300 mA
Wattage Equivalent	250 W


Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.95
Voltage (Nom)	120 V
Temperature	
T-Case Maximum (Nom)	90 °C
Controls and Dimming	
Dimmable	Yes
Approval and Application	
Suitable For Accent Lighting	Yes
Product Data	
Order product name	33PAR38/PER/830/F25/DIM/120V B 6/1FB
EAN/UPC - Product	046677534639
Order code	929001919704
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929001919704
Net Weight (Piece)	0.430 kg

PAR38 LED

Warnings and Safety

- Suitable for use in damp locations.
- Not for use in totally enclosed luminaires.
- CAUTION: Risk of electric shock - do not use where directly exposed to water.
- NOTES: This device complies with Part 18 of the FCC rule. This product may cause interference with other devices. If interference occurs, change the location of the products involved. This RFLD device complies with Canadian ICES-005


Dimensional drawing




PAR38 120V 32-W 2800lm 25D 3000K E26 D

Product	D	C
33PAR38/PER/830/F25/DIM/120V B 6/1FB	123 mm	133 mm


Photometric data



LEDSpot 33W E26 PAR38 F25 B





LEDSpot 33W E26 PAR38 F25



LEDSpot 33W E26 PAR38

PAR38 LED

Lifetime



LEDSpot 33W E26 PAR38

LEDSpot 33W E26 PAR38

