Presented By: **Candela Corporation** Contact Phone:

Contact E-mail:

(800) 922-9226 sales@candelacorp.com





GE Lighting

20330 - 45R/FL/MI-1 6PK

GE Soft White BR30

- Use original GE's Soft White when you need a light without glare and harsh shadows.
- Replace ordinary light bulbs with GE Flood and Spotlight in all your track and recessed lighting fixtures.





CAUTIONS & WARNINGS

Warning

- Risk of Fire
- Keep combustible materials away from lamp.
- Unexpected lamp rupture may cause injury, fire, or property damage - Avoid direct water, liquid or metal contact.

Customer Name: Project Name: Fixture Type:

GENERAL CHARACTERISTICS

Lamp Type Bulb Base Filament Wattage Voltage Rated Life **Primary Application**

Incandescent - Reflector **BR30** Medium Screw (E26) CC-6 45 120 2000 hrs Indoor Floodlight

PHOTOMETRIC CHARACTERISTICS

Initial Lumens 485 Center Beam Candlepower 300 (CBCP) Nominal Initial Lumens per Watt 10

DIMENSIONS

Maximum Overall Length (MOL) Bulb Diameter (DIA) Bulb Diameter (DIA) (MAX) 5.3700 in(136.4 mm) 3.750 in(95.2 mm) 3.750 in(95.2 mm)

PRODUCT INFORMATION

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

20330 45R/FL/MI-1 6PK BUNDLE 00043168203302 30 Unit 1 30

043168906791