

---

## 6.6 A Current Controlled Halogen - Reflector Lamps for Series Operation | 6.6 A reflector lamps for airfield lighting that provide accurate filament alignment for precision optics

---

### Areas of application

- Airfield Lighting



---

### Product family benefits

- Reduced operation and maintenance costs due to long lifetime

---

### Product family features

- Dimmable
- Available with connector combinations A, B, C/Z on request
- Infrared radiation output that provides light in the worst of conditions

# Product datasheet

## Technical data

### General Product Information

Global order reference	64331 FL-A 30W-
Product number (Americas)	58964
Product name (Americas)	6.6A 30MR16 64331A FL 20/CS 1/SKU

### Electrical Data

Nominal wattage	30 W
Nominal current	6.60 A
Type of current	AC

### Physical Attributes & Dimensions

Lamp base	Leads w/female A
Diameter (in)	1.984 in
Diameter	50.4 mm
Length	48.0 mm
Connector: presence	Yes
Connection with cable	Yes
Product weight	25.00 g

### Lifetime Data

Nominal lifetime	1000 hr
------------------	---------

### Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4008321229564
Date of declaration	05-08-2024
Declaration no. in SCIP database	In work
Candidate list substance 1	No declarable substances contained

## Product datasheet

---

### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.