

LIGHTING HARDWARE

For every repair or replacement need, Westinghouse has you covered. From sockets to switches, canopies to crossbars, we have the hard-to-find parts required to make your fixtures perform like new. Available in bulk and packaged.



4" Glass Shade Holder Kit
70238 - White Finish
 Use (1) Medium Base Lamp, 60 Watt Maximum
 Includes:
 • 1 Crossbar
 • 2 Mounting Screws
 • 1 Green Grounding Screw
 • 3 Knurled Fitter Screws
 • 1 Fiberglass Insulator



4" Glass Shade Holder Kit
70243 - Antique Brass Finish
 Use (1) Medium Base Lamp, 60 Watt Maximum
 Includes:
 • 1 Crossbar
 • 2 Mounting Screws
 • 1 Green Grounding Screw
 • 3 Knurled Fitter Screws
 • 1 Fiberglass Insulator



3-1/4" Glass Shade Holder Kit
70230 - Brass Finish
 Use (1) Medium Base Lamp, 60 Watt Maximum
 Includes:
 • 1 Crossbar
 • 2 Mounting Screws
 • 1 Green Grounding Screw
 • 3 Knurled Fitter Screws
 • 1 Fiberglass Insulator



3-1/4" Glass Shade Holder Kit
70236 - Antique Brass Finish
 Use (1) Medium Base Lamp, 60 Watt Maximum
 Includes:
 • 1 Crossbar
 • 2 Mounting Screws
 • 1 Green Grounding Screw
 • 3 Knurled Fitter Screws
 • 1 Fiberglass Insulator



Twin Cluster Ceiling Kit
70234
 Medium Base
 Includes:
 • 1 Canopy • 1 Wired Socket
 • 1 Crossbar, • 2 Mounting Screws
 • 1 Lock-Up Cap • 2 Rubber Washers
Ideal for Glass Diffusers



Twin Cluster Socket with Male Threads on Each End
***22259**
 Medium Base
 6" Wire Leads, 18 Gauge, 105° Leads
 660 Watts Max., 250 Volts
 1/2-IP Nipple
 Height - 4 3/4"



1-Piece Phenolic Shell
***22205**
 Bottom Turn-Knob Socket
 Medium Base
 1/2-IP Nipple
 660 Watts Max.
 250 Volts
 Height - 3 1/4"



Turn-Knob Phenolic Socket
70430
 On/Off
 Threaded 1/2-IP
 Medium Base
 660 Watts Max.
 250 Volts



High Heat Phenolic Socket
***22234**
 Medium Base
 Keyless
 1/2-IP Bushing with Set Screw
 660 Watts Max.
 250 Volts, Height - 2 3/4"



Vertical Phenolic Snap-In Socket
70146
 Fits into 3/8" x 1/4" Hole
 Medium Base
 660 Watts Max.
 250 Volts



Horizontal Phenolic Snap-In Socket
70145
 Fits into 7/8" x 1/4" Hole
 Medium Base
 660 Watts Max.
 250 Volts



Keyless Phenolic Socket
70407
 1/2-IP Hickey
 Medium Base
 660 Watts Max.
 250 Volts



Push-Through Phenolic Socket
***22237**
 Medium Base
 1/2-IP Cap with Side Screw
 Aluminum Screw Shell
 660 Watts Max.
 250 Volts
 Height - 2 5/8"



Pull Chain Phenolic Socket
70433
 On/Off
 Tapped 1/2-IP
 Medium Base
 250 Watts Max.
 250 Volts



Turn-Knob Socket
***22502**
 On/Off
 Medium Base
 250 Watts Max.
 250 Volts
 Height - 1 1/8"



3-Way Turn-Knob Socket
***22504**
 Medium Base
 250 Watts Max.
 250 Volts
 Height - 1 1/8"



Black Harness Set
***22381 - 3 Light**
***22382 - 4 Light**
 Candelabra Base
 Fits 3/4" Hole
 Includes Lock Nuts,
 SPT-2, 18 Gauge, 105° Leads
 75 Watts Max. Per Socket, 125 Volts
 6 1/4" Between Sockets
 12" on End Height - 1 1/4"



1 Light Black Harness Set
***22380**
 Candelabra Base
 Fits 3/4" Hole
 Includes Lock Nut
 12" Wire Leads
 SPT-2, 18 Gauge,
 105° Leads
 75 Watts Max., 125 Volts
 Height - 1 1/4"



1-3/4" Socket
***22377**
 18" Wire Leads
 Candelabra Base
 1/2-IP Hickey
 18 Gauge,
 105° Leads
 75 Watts Max.,
 125 Volts
 Height - 1 3/4"



Pigtail Socket
***22220**
 24" Wire Leads
 Candelabra Base
 18-2, SPT-1
 105° Leads
 75 Watts Max.
 125 Volts
 Height - 1 5/8"