

# ProLine® ARC Series

LED IP65 Round High Bay

Mounting/Accessory Options

## CUSTOMER NAME

Project Name \_\_\_\_\_

Date \_\_\_\_\_ Type \_\_\_\_\_

Catalog Number \_\_\_\_\_

## FIELD-INSTALLABLE MOUNTING AND ACCESSORY OPTIONS

MOUNTING/ACCESSORY OPTIONS	IMAGE	ORDER SKU#	DIMENSIONS/NOTES
Safety Tether (optional)		100W - 93142318 150W - 93142319 200-240W - 93142320  Min Order Quantity = 100	Cable length: 0.53m (21 in.)
Wire Guard (optional)		100W - 93142300 150W - 93142301 200-240W - 93142302  Min Order Quantity = 10	100W: H 3cm (1.2 in.); Dia 26cm (10.2 in.) 150W: H 3cm (1.2 in.); Dia 28.9 cm (11.4 in.) 200-240W: H 3cm (1.2 in.); Dia 33.3cm (13.1 in.)
Polycarbonate Refractor (optional)		100W - 93142303 150W - 93142304 200-240W - 93142305  Min Order Quantity = 1	100W: H 16.4cm (6.5 in.); Dia 41cm (16 in.) 150W: H 14.9cm (5.9 in.); Dia 41cm (16 in.) 200-240W: H 18.1cm (7.1 in.); Dia 48cm (18.9 in.)
Polycarbonate Drop Lens (optional)		100-150W - 93142306 200-240W - 93142307  Min Order Quantity = 1	Drop lens adds: 100W: H 3.6cm (1.4 in.) 150W: H 3.6cm (1.4 in.) 200-240W: H 4.1cm (1.6 in.)
Aluminum Reflector (optional)		100W - 93142308 150W - 93142309 200-240W - 93142310  Min Order Quantity = 5	100W: H 13.7cm (5.4 in.); Dia 35cm (14 in.) 150W: H 15.3cm (6 in.); Dia 36.5cm (14.4 in.) 200-240W: H 17.3cm (6.8 in.); Dia 41.4cm (16.3 in.)
Wall Mount Bracket (optional)		100W - 93142313 150W - 93142314 200-240W - 93142315  Min Order Quantity = 10	Total Height of assembly from top of bracket to bottom of fixture: 100W: 20.7cm (8.2 in.) 150W: 23.5cm (9.3 in.) 200-240W: 22.8cm (9 in.)
12V Tri-level occupancy and/or light sensor (optional)		Sensor - 93142316 Remote - 93142317  Min Order Quantity = 1	Notes: 1. Easy plug-and-play install to center face of fixture; maintains IP65 rating 2. Sensor requires remote if programming is desired