

SYLVANIA Luminaires

ValueLED™ Area Light 3A

Application

The SYLVANIA ValueLED Area Light 3A luminaires are the perfect alternative to traditional lighting technologies, offering a variety of solutions to illuminate parking lots, parking garage roofs and general area lighting.

Benefits and Features

- IP65 rated body offered in a modern and sleek design
- Each luminaire ships with a universal mounting accessory for round/square pole mounting and tenon mounting
- DLC Premium listed to maximize rebate opportunities
- Integrated 3 pin photocontrol receptacle compatible with Standard NEMA photo cell. Shorting cap included
- Up to 135 LPW
- 4000K and 5000K color temperatures
- CRI >70
- Offered in 150 and 300 watts
- Type III and V distribution
- Energy savings up to 73%

Electrical

- 120-277V_{AC}
- Power Factor >90%
- THD <20%
- 0-10V dimmable

Optical

- Lens is polycarbonate

Rated Life

- 100,000 hours (L₇₀) @25°C

Warranty

- 5-year

Ambient Operating Range

- -40°F to +102°F (-40°C to +40°C)

Item #

Type

Project

Notes

Date



Wattage Comparison

Traditional Source	Traditional System Wattage	LED System Wattage	Energy Savings
250W MH	290W	150W	48%
250W HPS	295W	150W	49%
320W MH	370W	150W	59%
750W HPS	820W	300W	63%
750W MH	840W	300W	64%
1000W MH	1080W	300W	72%
1000W HPS	1100W	300W	73%

Certifications and Listings

- cULus
- RoHS
- FCC
- IP65
- DLC Premium

Installation

- Each luminaire ships with a universal mounting accessory for round/square pole mounting



Ordering Guide

AREAFLD	3A	/	XXX	XXX	D	7	XX	/	TX	/	BZ
Product Name	Generation		Wattage	Voltage	Dimming	CRI	Color Temp		Distribution		Color / Finish
AREAFLD =	3A = Generation 3A		150 = 150 Watts	UNV = 120-277V	D = 0-10V	CRI = >70	40 = 4000K		T3 = Type III		BZ = Bronze
Area Floodlight			300 = 300 Watts				50 = 5000K		T5 = Type V		
Luminaire											

Ordering Information


Item Number	Ordering Abbreviation	Wattage (W)	Input Voltage (V)	Dimming	CRI	Color Temperature (CCT)	Distribution	Total Fixture Lumens	LPW*	DLC	BUG Rating
61316	AREAFLD3A/150UNVD740/T3/BZ	150	120-277V	0-10V	> 70	4000K	III	20,000	135	Prm	B3-U0-G3
61317	AREAFLD3A/150UNVD740/T5/BZ	150	120-277V	0-10V	> 70	4000K	V	20,000	135	Prm	B3-U0-G3
61318	AREAFLD3A/150UNVD750/T3/BZ	150	120-277V	0-10V	> 70	5000K	III	20,000	135	Prm	B3-U0-G3
61319	AREAFLD3A/150UNVD750/T5/BZ	150	120-277V	0-10V	> 70	5000K	V	20,000	135	Prm	B3-U0-G3
61320	AREAFLD3A/300UNVD740/T3/BZ	300	120-277V	0-10V	> 70	4000K	III	40,000	135	Prm	B4-U0-G5
61321	AREAFLD3A/300UNVD740/T5/BZ	300	120-277V	0-10V	> 70	4000K	V	40,000	135	Prm	B4-U0-G5
61322	AREAFLD3A/300UNVD750/T3/BZ	300	120-277V	0-10V	> 70	5000K	III	40,000	135	Prm	B4-U0-G5
61323	AREAFLD3A/300UNVD750/T5/BZ	300	120-277V	0-10V	> 70	5000K	V	40,000	135	Prm	B4-U0-G5

*Lumens and LPW are based on 5000K CCT.


Photometric Information

Mounted at 15' at a 15° angle

150W Type III Distribution




300W Type III Distribution




Physical Information

150W



300W



Dimensions in inches (mm)


Accessories

NEMA Photocontrols


61393 AREAFDXA/NEMAPHOTOCELL/UNV NEMA locking photocell, 120-277V

Mounting

Drill Pattern for Pole Mounting



Universal Bracket



Legend	
1	Universal bracket
2	Bracket conversion
3	Bracket junction box cover
4	Bracket fixed iron bar
5	Bracket silicone pad 1
6	Bracket silicone pad 2
7	Bracket silicone pad 3
8	Hexagon socket machine screw M8*50
9	Hexagon socket machine screw M8*25
10	Screw flat washer
11	Open spring pad
12	Screw KM3*6MM
13	Screw M4*18MM
14	M8 rubber stopper

Poles





Product Features

- Poles available in six heights: 12', 15', 17', 20', 25', and 30'
- 12'-25' poles are 4" square; 30' pole is 5" square
- 12'-25' poles are 11 gauge, while 30' poles are offered in 7 and 11 gauge
- Fabricated from the highest grade structural steel

Specifications

- Square steel pole with powder coat paint. The standard color is bronze
- Polycarbonate spring loaded top cover
- Pre-drilled mounting holes on all 4 sides with Polycarbonate grommets
- Reinforced 2.5" x 4.5" cast iron hand-hole with ground screw included
- Easily secured base cover included
- Bolt circle template included



Ordering Guide (Poles)

POLESQS	2A	/	XX	/	XXG	/	XXIN	/	BZ
Product Name	Generation		Height		Gauge		Size		Finish
POLESQS =	2A		12 = 12 feet		11G = 11		4IN = 4 inches		Bronze
Square Straight Pole			15 = 15 feet		07G = 7		5IN = 5 inches		
			17 = 17 feet						
			20 = 20 feet						
			25 = 25 feet						
			30 = 30 feet						

Ordering Information (Poles)

Item Number	Ordering Abbreviation	Shape	Height (ft)	Gauge (in)	Size (in)	Finish
62306	POLESQS2A/12/11G/4IN/BZ	SquareStraight	12	11	4	Bronze
62307	POLESQS2A/15/11G/4IN/BZ	SquareStraight	15	11	4	Bronze
62308	POLESQS2A/17/11G/4IN/BZ	SquareStraight	17	11	4	Bronze
62309	POLESQS2A/20/11G/4IN/BZ	SquareStraight	20	11	4	Bronze
62310	POLESQS2A/25/11G/4IN/BZ	SquareStraight	25	11	4	Bronze
62311	POLESQS2A/30/11G/5IN/BZ	SquareStraight	30	11	5	Bronze
62312	POLESQS2A/30/07G/5IN/BZ	SquareStraight	30	7	5	Bronze




Ordering Information (Accessories)

Item Number	Ordering Abbreviation	Description	Compatibility
60665	POLESQS1A/ANJBOLTKIT/304	3/4" x 30" Anchor Bolt Kit (set of 4 bolts)	Compatible with 62306, 62307, 62308, 62309 and 62310
60666	POLESQS1A/ANJBOLTKIT/364	1" x 36" Anchor Bolt Kit (set of 4 bolts)	Compatible with 62311 and 62312
60667	POLESQS1A/TENON/4IN/BZ	4" Tenon Mount, Bronze Finish	For use with 62306, 62307, 62308, 62309 and 62310
60668	POLESQS1A/TENON/5IN/BZ	5" Tenon Mount, Bronze Finish	For use with 62311 and 62312
65013	POLESQS1A/DBLTENON/4IN/BZ	4" Double Tenon Bracket, Bronze Finish	For use with 62306, 62307, 62308, 62309 and 62310
65014	POLESQS1A/DBLTENON/5IN/BZ	5" Double Tenon Bracket, Bronze Finish	For use with 62311 and 62312
65015	POLESQS1A/DBLBULLHORN/4IN/BZ	4" Double Bullhorn Bracket, Bronze Finish	For use with 62306, 62307, 62308, 62309 and 62310
65016	POLESQS1A/DBLBULLHORN/5IN/BZ	5" Double Bullhorn Bracket, Bronze Finish	For use with 62311 and 62312
60845	POLESQS1A/TPLBULLHORN/4IN/BZ	4" Triple Bullhorn Bracket, Bronze Finish	For use with 62306, 62307, 62308, 62309 and 62310
60846	POLESQS1A/TPLBULLHORN/5IN/BZ	5" Triple Bullhorn Bracket, Bronze Finish	For use with 62311 and 62312
65112	POLESQS1A/QUADTENON/4IN/BZ	4" Quad Tenon Bracket, Bronze Finish	For use with 62306, 62307, 62308, 62309 and 62310
65113	POLESQS1A/QUADTENON/5IN/BZ	5" Quad Tenon Bracket, Bronze Finish	For use with 62311 and 62312

For further information and to learn more about utility rebates, contact your local SYLVANIA sales representative.


NAED 60665 – 3/4" x 30"

NAED 60666 – 1" x 36"




Tenon

NAED 60667 – 4 inch
NAED 60668 – 5 inch




Double Bullhorn

NAED 65015 – 4 inch
NAED 65016 – 5 inch




Double Tenon

NAED 65013 – 4 inch
NAED 65014 – 5 inch



Triple Bullhorn

NAED 60845 – 4 inch
NAED 60846 – 5 inch



Quad Tenon

NAED 65112 – 4 inch
NAED 65113 – 5 inch

Allowable Wind Loading

Ordering Abbreviation	Mounting Height (ft)	90 MPH	100 MPH	110 MPH	120 MPH	130 MPH	150 MPH	Anchor Bolt	
		EPA (ft²)	EPA (ft²)	EPA (ft²)	EPA (ft²)	EPA (ft²)	EPA (ft²)	Diameter (in)	Length (in)
62306	12	12	12	12	12	9.2	6.8	0.75	30
62307	15	12	12	12	9.8	7.8	4.9	0.75	30
62308	17	12	12	9.9	7.6	5.9	3.3	0.75	30
62309	20	12	9.1	6.7	4.8	3.4	1.3	0.75	30
62310	25	7	4.6	2.7	1.3	0.3	–	0.75	30
62311	30	5.6	2.7	0.6	–	–	–	1	36
62312	30	11.7	7.8	4.8	2.5	0.8	–	1	36

Pole Loading

Model	EPA (ft²)
150W	0.47
300W	0.62


Fixture Pole Loading

Pole Description	90 MPH		100 MPH		110 MPH		120 MPH		130 MPH		150 MPH	
	Area 150W	Area 300W	Area 150W	Area 300W	Area 150W	Area 300W	Area 150W	Area 300W	Area 150W	Area 300W	Area 150W	Area 300W
POLESQS2A/12/11G/4IN/BZ	8+	8+	8+	8+	8+	8+	8+	8+	8+	8+	8+	8+
POLESQS2A/15/11G/4IN/BZ	8+	8+	8+	8+	8+	8+	8+	8+	8+	8+	8+	7
POLESQS2A/17/11G/4IN/BZ	8+	8+	8+	8+	8+	8+	8+	8+	8+	8+	7	5
POLESQS2A/20/11G/4IN/BZ	8+	8+	8+	8+	8+	8+	8+	7	7	5	2	2
POLESQS2A/25/11G/4IN/BZ	8+	8+	9	7	5	4	2	2	–	–	–	–
POLESQS2A/30/11G/5IN/BZ	8+	8+	5	4	1	–	–	–	–	–	–	–
POLESQS2A/30/7G/5IN/BZ	8+	8+	8+	8+	8+	7	5	4	1	1	–	–

Pole Loading

Pole Description	90 MPH		100 MPH		110 MPH		120 MPH		130 MPH		150 MPH	
	Area 150W	Area 300W	Area 150W	Area 300W	Area 150W	Area 300W	Area 150W	Area 300W	Area 150W	Area 300W	Area 150W	Area 300W
With Double Tenon, Knuckle, 2 Area Lights												
POLESQS2A/12/11G/4IN/BZ	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
POLESQS2A/15/11G/4IN/BZ	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
POLESQS2A/17/11G/4IN/BZ	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N
POLESQS2A/20/11G/4IN/BZ	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N
POLESQS2A/25/11G/4IN/BZ	Y	Y	Y	Y	N	N	N	N	N	N		
POLESQS2A/30/11G/5IN/BZ	Y	Y	N	N	N	N						
POLESQS2A/30/7G/5IN/BZ	Y	Y	Y	Y	Y	Y	N	N	N	N		
With Double Bullhorn, Knuckle, 2 Area Lights												
POLESQS2A/12/11G/4IN/BZ	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
POLESQS2A/15/11G/4IN/BZ	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
POLESQS2A/17/11G/4IN/BZ	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N
POLESQS2A/20/11G/4IN/BZ	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N
POLESQS2A/25/11G/4IN/BZ	Y	Y	Y	Y	N	N	N	N	N	N		
POLESQS2A/30/11G/5IN/BZ	Y	Y	N	N	N	N						
POLESQS2A/30/7G/5IN/BZ	Y	Y	Y	Y	Y	Y	N	N	N	N		
With Triple Bullhorn, Knuckle, 3 Area Lights												
POLESQS2A/12/11G/4IN/BZ	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
POLESQS2A/15/11G/4IN/BZ	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N
POLESQS2A/17/11G/4IN/BZ	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N
POLESQS2A/20/11G/4IN/BZ	Y	Y	Y	Y	Y	Y	Y	N	N	N	N	N
POLESQS2A/25/11G/4IN/BZ	Y	Y	N	N	N	N	N	N	N	N		
POLESQS2A/30/11G/5IN/BZ	Y	N	N	N	N	N						
POLESQS2A/30/7G/5IN/BZ	Y	Y	Y	Y	Y	N	N	N	N	N		

Wind Map



Notes: Dark shading indicates a special wind region.

1. Values are nominal design 3-s gust wind speeds in miles per hour (m/s) at 33 ft. (10 m) above ground for Exposure Category C.
2. Linear interpolation is permitted between contours. Point values are provided to aid with interpolation.
3. Islands, coastal areas, and land boundaries outside the last contour shall use the last wind speed contour.
4. Mountainous terrain, gorges, ocean promontories, and special wind regions shall be examined for unusual wind conditions.
5. Wind speeds correspond to approximately a 15% probability of exceedance in 50 years. (Annual Exceedance Probability = 0.00333, MRI = 300 years).
6. Location-specific basic wind speeds shall be permitted to be determined using www.atcouncil.org/windspeed.

LEDVANCE LLC
200 Ballardvale Street
Wilmington, MA 01887 USA
Phone 1-800-LIGHTBULB (1-800-544-4828)
www.ledvanceUS.com

SYLVANIA and LEDVANCE are registered trademarks.
All other trademarks are those of their respective owners.
Licensee of product trademark SYLVANIA in general lighting.
Specifications subject to change without notice.

[/sylvania](https://twitter.com/sylvania) [/sylvania](https://facebook.com/sylvania)

Name:

Email:

Phone:

