LIGHT BAR

DESCRIPTION:

Made in the USA, the Light Bar is easy to install and comes in assorted sizes. Rugged construction with anodized aluminum rail.

FEATURES:

- 6' lead of 18 gauge direct burial wire
- Custom lengths up to 90"
- Custom colors available
- Dimmable w/ most magnetic transformers
- Mounting Brackets available
- Shield available in copper and stainless steel for 3 & 6 only

Kelvin Temperature	2700
Operating Range	8-18VAC
Input Voltage	12VAC
Chipset	CREE
CRI	85
IP	68
Warranty (years)	5

Length	LEDs	Lumens	Watts	
5 1/4"	3	135	2.6	
9 1/8″	6	270	5.2	
13″	9	405	7.8	

NOT for installation within 10 ft of swimming pool per NEC Article 411-2

ATTENTION: Operating voltage range is 8-18 Volts AC/DC





17 (1) 1	I TOMDER.	DIG	/\/\	////		/\/	
	Light B			# 0	of LEC)'s	

Mounting Bracket = MB LB & MB Kit = LBMB

```
Optional - Light Bar Shield (3 & 6 LED only)
```

PART NUMBER: LBS X XXXXXX

of LED's 3 6



6

9



Optional: Light Bar Shield in 3 and 6 LEDs





