
BVV 1000W 120V 6/CS 1/SKU



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54691
Product Name	BVV 1000W 120V 6/CS 1/SKU
Ordering Abbreviation	BVV 1000W 120V 6/CS 1/SKU
Brand Name	OSRAM
General Description	1,000 watt, tungsten halogen, medium to high voltage, single-ended
Application	Stage & Studio

Electrical data

Nominal Wattage	1000 W
Nominal Voltage	120 V
Type of Current	AC

Light technical data

Luminous Flux	27500 lm
Light Center Length - LCL (in)	3.9 in
Light Center Length - LCL (mm)	100 mm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	200 h

Physical attributes

Base	P40S MOGUL PREFOCUS
Bulb Shape	T6
Maximum Overall Length (in)	6.934 in
Maximum Overall Length (mm)	177.8 mm
Length l (in)	6.934 in
Length l (mm)	177.8 mm
Length l max. (in)	6.934 in
Length l max. (mm)	177.8 mm
Diameter d (in)	0.945 in
Diameter d (mm)	24.00 mm
Distance a (in)	3.900 in
Distance a (mm)	100 mm
Filament	C-13D

Product datasheet

Additional product data

Operating Position	Any
Total surface inside 1: appearance (cold)	CLEAR
Class	C (gas)
Lamp Type	SINGLE END

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
54691	4062172147217	Unpacked (SKU)	1	8.9 in x 3.7 in x 3.7 in	0.9 lb
54691	4062172147224	Shipping box (Case)	6	11.4 in x 10.5 in x 8.4 in	5.9 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.