

A

B

C

D

E

A

B

C

D


E

20-5012 A

SAFETY STANDARDS COMPLIANCE: UL8750 UL1310 LVD EN61347-2-13 EMI STANDARDS: FCC 47 CFR PART 15 CLASS B CE EN55015, EN61547 EN61000-4-2,3,4,5,6,8,11			SAFETY CERTIFICATIONS UL, cUL E345001 LVD pending FCC 14KWE061620F EMC pending			SAFETY
INPUT RANGE: 100 - 277 VAC, 1.3 A @ FULL LOAD. FREQUENCY: 50 / 60 Hz. POWER FACTOR: > 0.9 EFFICIENCY: 85 % Typ. LEAKAGE CURRENT: PEAK INRUSH: <1 mA 60A AMPS @ 230V AC						
LOAD CAPACITY: 100 WATTS OUTPUT MIN MAX LOAD REG MAX. RIP 1700mA 36V 48V ±6% 15% p-p						OUTPUT
COOLING: CONVECTION PROTECTION: NOISE LEVEL: 0 dB OCP,SCP,OVP AUTO-RECOVERY RELIABILITY (MTBF): (MIL-HDBK-217E) 100,000 HRS. @ 25 °C @ FULL LOAD ENVIRONMENTAL CONDITIONS: OPERATING TEMPERATURE: -20 ~ 40°C RELATIVE HUMIDITY: 5 ~ 95% LOCATION: DRY AND DAMP USE ONLY CONNECTOR:						
MISCELLANEOUS						

205012A0M1.DWG

REVISIONS		
REV	DESCRIPTION	DATE
A0	RELEASE TO PRODUCTION	06/23/2014



CON	PIN	COLOR	OUTPUT	AWG	LENGTH
AC IN	—	BROWN	LINE	18	6.5 [165] ±0.5 [±13]
	—	BLUE	NEUTRAL	18	
	—	GREEN	FG	18	
DC OUT	—	RED	+V	18	
	—	BLACK	GND	18	
DIM CNTL	—	YELLOW	+10V OUT	20	
	—	PURPLE	DIM+	20	
	—	GRAY	DIM-	20	

FG

L: Brown

N: Blue

MAGTECH

MODEL: ESL1100-48-C1700

INPUT: 100~277VAC, 1.3A, 50/60Hz

Suitable for Dry and Damp Locations

0~10V Dimmable, Isolated Class 2 Constant Current LED Driver

OUTPUT: 1700mA / 36~48V •tc

100W max

P/N: 20-5012 Rev: A

Made in China

UL E345001

SELV equivalent

S/N: 0910293004

LED+ (Red)

LED- (Black)

Dim- (Gray)

Dim+ (Prpl)

+10V (Yllw)


Notes:

1.- 5 yrs warr provided Tc point remains below 75°C

2.- Bar code defined by drawing 77-0120.

3.- Transformer – Rated Class 130 (B) insulation system

MANUFACTURED BY: Juno

THIS ITEM IS THE PROPERTY OF MAGTECH INDUSTRIES AND CONTAINS PROPRIETARY CONFIDENTIAL AND TRADE SECRET INFORMATION. THE INFORMATION CONTAINED HEREIN MUST NOT BE USED, DISCLOSED OR REPRODUCED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN CONSENT FROM MAGTECH IND.					
UNLESS OTHERWISE SPECIFIED		QC:			
DIMENSIONS IN INCHES (MM)					
TOLERANCES:				TITLE: ESL1100-48-C1700, CN-0197, 100~277VAC, 1700mA, 36~48V, 5YRS	
.X DECIMALS±		.05 [1.3]			
.XX DECIMALS±		.02 [0.5]			
.XXX DECIMALS±		.005 [0.13]			
ANGLES±		1°			
FRACTIONS±		1/16			
DO NOT SCALE THIS DRAWING		APPROVAL DATE: 06/27/2014		MODEL NO.	
INTERPRET DRAWING PER ANSI Y14.5M		EFFECTIVE DATE: 07/02/2014		ESL1100-48-C1700	
				DWG NO. REV. A0 SH OF 1 1	
				M20-5012	

FORM PF-0004