

4

3

1

DWG NO. 1000382SH 1

REV

DESCRIPTION

DATE

APPROVED

55

33.0

Ø13.0

⌀

NOTES:

1. ALL DIMENSIONS ARE IN MM.

2. SEAL TEMP: SHOULD BE MAINTAINED BELOW 350°C

3. THE DIMENSIONS AND SPECIFICATIONS OF PRODUCT LISTED IN THIS SHEET ARE SUBJECT TO CHANGE WITHOUT NOTICE FOR IMPROVEMENT.

CHARACTERISTICS

VOLTAGE

24 V

WATTAGE

250 W

TOTAL LUMEN

8100 Lm

COLOR TEMP.

3400 K

BASE TYPE

G6.35

AVERAGE LIFE

300 HRS

FILAMENT TYPE

CBar6

BURN POSITION

Any

APPLICATION

ITEM

QTY

DESCRIPTION

CODE IDENT

PART NUMBER

REMARKS

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

DECIMALS .X ± -

.XX ± -

.XXX ± -

ANGLES ± -

DRILLED HOLES PER AND 10387 REMOVE BURRS AND SHARP EDGES ALL DIMENSIONS AFTER PLATING

MATERIAL

COMPOSITE

FINISH

CONTRACT NO.

APPROVALS

DATE

DRAWN

R.AMPARO

09/02/99

CHKD

D.GILCZYNSKI

09/02/99

ENGR

MFG

QUAL

DSGN ACTVY

GOVT ACTVY

TITLE

EVC/FGX

JC24V-250W

SIZE

B

CODE IDENT NO.

EVC

DWG NO.

1000382

SCALE

NONE

WEIGHT

SHEET

1 OF 1

USHIO AMERICA, INC.

5440 Cerritos Avenue Cypress, CA 90630