

4


3

DWG NO. 1000383 SH 1

1

REVISIONS

REV	DESCRIPTION	DATE	APPROVED
-----	-------------	------	----------



NOTES:

1. ALL DIMENSIONS ARE IN MM UNLESS OTHERWISE SPECIFIED.
2. SEAL TEMP SHOULD BE MAINTAINED BELOW 350°C.
3. THE DIMENSIONS AND SPECIFICATIONS OF PRODUCT LISTED IN THIS SHEET ARE SUBJECT TO CHANGE WITHOUT NOTICE FOR IMPROVEMENT.

CHARACTERISTICS

VOLTAGE	36 V
WATTAGE	400 W
TOTAL LUMEN	14500 Lm
COLOR TEMP.	3450 K
BASE TYPE	G8.35
AVERAGE LIFE	50 HRS
FILAMENT TYPE	C80r8
BURN POSITION	BD/Her

NEXT ASSY	USED ON
APPLICATION	

ITEM	QTY	DESCRIPTION	CODE IDENT	PART NUMBER	REMARKS
LIST OF MATERIALS					
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES DECIMALS .X ± - .XX ± - .XXX ± - ANGLES ± - DRILLED HOLES PER AND 10387 REMOVE BURRS AND SHARP EDGES ALL DIMENSIONS AFTER PLATING			CONTRACT NO.		
			APPROVALS DATE		
			DRAWN	R.AMPARO	08/20/99
			CHKD	D.GILCZYNSKI	09/20/99
			ENGR		
			APPD		
			QUAL		
			DRON ACTVY		
			DDVT ACTVY		
MATERIAL			TITLE		
COMPOSITE			USHIO AMERICA, INC.		
FINISH			5440 Carritas Ave. Cypress, CA90630		
			EVD, JC36V-400WS1 HALOGEN LAMP		
			SIZE	CODE IDENT NOS	DWG NO.
			B	EVD	1000383
			SCALE	NONE	WEIGHT
			SHEET 1 OF 1		

4

3

2

1

CAD