

**Presented By:** Candela Corporation  
**Contact Phone:** (800) 922-9226  
**Contact E-mail:** sales@candelacorp.com


**Customer Name:**  
**Project Name:**  
**Fixture Type:**



GE  
Lighting

### 97571 - F13BX/841/ECO

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse



### GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Plug-In
Bulb	T4
Base	GX23
Wattage	13
Voltage	120/59
Rated Life	10000 hrs
Starting Temperature	0 °C (32 °F)
LEED-EB MR Credit	563 picograms Hg per mean lumen hour
Additional Info	TCLP compliant
Primary Application	Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse

### PHOTOMETRIC CHARACTERISTICS

Initial Lumens	825
Mean Lumens	710
Nominal Initial Lumens per Watt	63
Color Temperature	4100 K
Color Rendering Index (CRI)	82

### ELECTRICAL CHARACTERISTICS


Lamp Current	0.285 A
Current Crest Factor	1.7
Supply Current Frequency	60 Hz

### DIMENSIONS

Maximum Overall Length (MOL)	7.3000 in(185.4 mm)
Nominal Length	7.000 in(177.8 mm)
Base Face to Top of Lamp	6.690 in(169.9 mm)

### PRODUCT INFORMATION

Product Code	97571
Description	F13BX/841/ECO
ANSI Code	60901-IEC-0013-1
Standard Package	BUNDLE
Standard Package GTIN	
Standard Package Quantity	100
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	100
UPC	043168975711



### CAUTIONS & WARNINGS

#### Caution

- Lamp may shatter and cause injury if broken
  - Remove and install by grasping only plastic portion of the lamp.

### NOTES

- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life