



**F13T5CW 9231 F13 T5
COOL WHT PROLUME**

| Specifications | Resources | Technical |
|---------------------------------|-----------|-------------------------|
| Applications | | overhead fixtures |
| Average Life (Hrs) | | 6000 |
| Base | | Miniature Bi-Pin |
| Brand | | ProLume |
| Bulb | | T5 |
| CRI | | 65 |
| Color Temperature | | 4100 |
| Design Lumens | | 666 |
| Dimmable | | No |
| Efficacy (lm/W) | | 56.9 |
| HTS code | | 8539310070 |
| Initial Lumens | | 740 |
| Inner Carton Quantity | | 10 |
| Input Current (Amps) | | 0.165 |
| Input Frequency (Hz) | | 60 |
| Markets | | Residential, Commercial |
| Master Carton Quantity | | 200 |
| Maximum Overall Diameter | | 0.63 |
| Maximum Overall Length | | 21 |
| Nominal Length | | 21 |
| Open/Enclosed Rated | | Open or Enclosed |
| Operating Position | | Universal |
| Product Category | | Linear Fluorescent |
| Product Description | | F13 T5 COOL WHT PROLUME |
| Product Number | | 9231 |
| Start Type | | Preheat |
| UV/IR Emissions | | Yes |
| Wattage (W) | | 13 |