Presented By: Candela Corporation
Contact Phone: (800) 922-9226
Contact E-mail: sales@candelacorp.com

Customer Name: Project Name: Fixture Type:



GE Lighting

# 45741 - F17T8/SP30/ECO

GE Ecolux® Starcoat® T8

• Passes TCLP, which can lower disposal costs.









#### **CAUTIONS & WARNINGS**

## Caution


- Lamp may shatter and cause injury if broken
- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.

#### Warning

- Risk of Electric Shock
- Turn power off before inspection, installation or removal.

#### **GRAPHS & CHARTS**

**Spectral Power Distribution** 



**Lumen Maintenance** 

## **GENERAL CHARACTERISTICS**

Lamp Type Linear Fluorescent - Straight

Linear

Bulb T8

 Base
 Medium Bi-Pin (G13)

 Wattage
 17

 Voltage
 70

 Rated Life
 20000 hrs

Rated Life (instant start) @ 15000 h @ 3 h Time 20000 h @ 12 h

Rated Life (rapid start) @ Time 20000.0 @ 3.0/24000.0 @

Bulb Material Soda lime
Starting Temperature 10 K (50 °F)

LEED-EB MR Credit 157 picograms Hg per mean

lumen hour

Additional Info TCLP compliant

#### PHOTOMETRIC CHARACTERISTICS

Initial Lumens 1325
Mean Lumens 1260
Nominal Initial Lumens per Watt 77
Color Temperature 3000 K
Color Rendering Index (CRI) 78
S/P Ratio (Scotopic/Photopic 1.3
Ratio)

#### **ELECTRICAL CHARACTERISTICS**

Open Circuit Voltage (rapid 285 V

start)

Open Circuit Voltage (rapid 210 V @ 10 °C

start) Min @ Temperature

Cathode Resistance Ratio - Rh/ 4.25

Rc (MIN)

Cathode Resistance Ratio - Rh/ 6.5

Rc (MAX)

Current Crest Factor 1.7

# **DIMENSIONS**

Maximum Overall Length 23.78 cm

(MOL)

Minimum Overall Length 23.67 cm
Nominal Length 24 cm
Bulb Diameter (DIA) 1 cm
Bulb Diameter (DIA) (MIN) 0.94 cm
Bulb Diameter (DIA) (MAX) 1 cm
Max Base Face to Base Face 23.22 cm

(A)

Face to End of Opposing Pin 23.4 cm

(B) (MIN)

Face to End of Opposing Pin 23.5 cm

(B) (MAX)

End of Base Pin to End of 23.67 cm

Opposite Pin End (C)

#### **PRODUCT INFORMATION**

Product Code 45741

Description F17T8/SP30/ECO


ANSI Code 1001-1 Standard Package Case

Standard Package GTIN 10043168457412

Standard Package Quantity 24
Sales Unit Unit
No Of Items Per Sales Unit 1
No Of Items Per Standard 24

Package

UPC 043168457415



# **Lamp Mortality**

