Presented By: **Candela Corporation** Contact Phone: (800) 922-9226 Contact E-mail: sales@candelacorp.com

**Customer Name:** Project Name: Fixture Type:




# 45743 - F17T8/SP35/ECO

GE Ecolux® Starcoat® T8

• Passes TCLP, which can lower disposal costs.







#### **CAUTIONS & WARNINGS**


#### Caution

- Lamp may shatter and cause injury if broken
- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.

- · Risk of Electric Shock
- Turn power off before inspection, installation or removal.

# **GRAPHS & CHARTS**

**Spectral Power Distribution** 



**Lumen Maintenance** 

## **GENERAL CHARACTERISTICS**

Lamp Type Linear Fluorescent - Straight

Linear

Bulb T8

Medium Bi-Pin (G13) Base Wattage 17 Voltage 70 Rated Life 20000 hrs Rated Life (instant start) @ 15000 h @ 3 h

20000 h @ 12 h Time Rated Life (rapid start) @ Time 20000.0 @ 3.0/24000.0 @

12.0 h **Bulb Material** Soda lime

Starting Temperature 10 K (50 °F)

LEED-EB MR Credit 157 picograms Hg per mean

lumen hour

Additional Info TCLP compliant

### PHOTOMETRIC CHARACTERISTICS

**Initial Lumens** 1325 Mean Lumens 1260 Nominal Initial Lumens per Watt 77 Color Temperature 3500 K Color Rendering Index (CRI) 78 S/P Ratio (Scotopic/Photopic 1.4 Ratio)

### **ELECTRICAL CHARACTERISTICS**

Open Circuit Voltage (rapid 285 V

start)

Open Circuit Voltage (rapid 210 V @ 10 °C

start) Min @ Temperature

Cathode Resistance Ratio - Rh/ 4.25 Rc (MIN)

Cathode Resistance Ratio - Rh/ 6.5

Rc (MAX)

**Current Crest Factor** 1.7

# **DIMENSIONS**

Maximum Overall Length 23.78 cm

(MOL)

Minimum Overall Length 23.67 cm Nominal Length 24 cm Bulb Diameter (DIA) 1 cm Bulb Diameter (DIA) (MIN) 0.94 cm Bulb Diameter (DIA) (MAX) 1 cm 23.22 cm Max Base Face to Base Face

(A)

Face to End of Opposing Pin 23.4 cm

(B) (MIN)

Face to End of Opposing Pin 23.5 cm

(B) (MAX)

End of Base Pin to End of 23.67 cm

Opposite Pin End (C)

### **PRODUCT INFORMATION**

**Product Code** 45743

Description F17T8/SP35/ECO


ANSI Code 1001-1 Standard Package Case

Standard Package GTIN 10043168457436

Standard Package Quantity 24 Sales Unit Unit No Of Items Per Sales Unit No Of Items Per Standard 24

Package

UPC 043168457439



# **Lamp Mortality**

