Presented By: **Candela Corporation** Contact Phone: (800) 922-9226 Contact E-mail: sales@candelacorp.com

Customer Name: Project Name: Fixture Type:



Lighting

10416 - F25T8XLSPX50/ECO

GE Ecolux® Starcoat® T8

• Passes TCLP, which can lower disposal costs.









CAUTIONS & WARNINGS


Caution

- · Lamp may shatter and cause injury if broken
- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.

- · Risk of Electric Shock
- Turn power off before inspection, installation or removal.

GRAPHS & CHARTS

Spectral Power Distribution



Lumen Maintenance

GENERAL CHARACTERISTICS

Linear Fluorescent - Straight Lamp Type

Linear

Bulb T8

Medium Bi-Pin (G13) Base Wattage 25 Voltage 100

Rated Life 24000 hrs Rated Life (instant start) @ 20000 h @ 3 h 24000 h @ 12 h Time

Rated Life (rapid start) @ Time 29000.0 @ 12.0 h **Bulb Material** Soda lime 10 K (50 °F) Starting Temperature

LEED-EB MR Credit 84 picograms Hg per mean

lumen hour

Additional Info TCLP compliant

PHOTOMETRIC CHARACTERISTICS

Initial Lumens 2050 Mean Lumens 1950 Nominal Initial Lumens per Watt 82 Color Temperature 5000 K Color Rendering Index (CRI) 86

ELECTRICAL CHARACTERISTICS

Open Circuit Voltage (rapid start)

Open Circuit Voltage (rapid 260 V @ 10 °C

start) Min @ Temperature

Cathode Resistance Ratio - Rh/ 4.25

Rc (MIN)

Cathode Resistance Ratio - Rh/ 6.5

Rc (MAX)

Current Crest Factor 1.7

DIMENSIONS

Maximum Overall Length 35.78 cm (MOL) Minimum Overall Length 35.67 cm Nominal Length 36 cm Bulb Diameter (DIA) 1 cm Bulb Diameter (DIA) (MIN) 0.94 cm Bulb Diameter (DIA) (MAX) 1 cm

Outside Bulb Diameter

Max Base Face to Base Face 35.22 cm

(A)

Face to End of Opposing Pin 35.4 cm

(B) (MIN)

Face to End of Opposing Pin 35.5 cm (B) (MAX) 35.67 cm

End of Base Pin to End of

Opposite Pin End (C)

PRODUCT INFORMATION

Product Code 10416

Description F25T8XLSPX50/ECO


ANSI Code 1002-1 Standard Package Case

Standard Package GTIN 10043168104163

Standard Package Quantity 24 Sales Unit Unit No Of Items Per Sales Unit No Of Items Per Standard 24

Package

UPC 043168104166



Lamp Mortality

