

**Presented By:** Candela Corporation  
**Contact Phone:** (800) 922-9226  
**Contact E-mail:** sales@candelacorp.com




**Customer Name:**  
**Project Name:**  
**Fixture Type:**



GE  
Lighting

### 97609 - F26DBX/841/ECO

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office;  
Restaurant; Warehouse



#### GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Plug-In
Bulb	T4
Base	G24d-3
Wattage	26
Voltage	105
Rated Life	10000 hrs
Starting Temperature	-9 °C (16 °F)
Cathode Resistance	2.7 Ohm
LEED-EB MR Credit	274 picograms Hg per mean lumen hour
Additional Info	TCLP compliant
Primary Application	Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse

#### PHOTOMETRIC CHARACTERISTICS

Initial Lumens	1710
Mean Lumens	1460
Nominal Initial Lumens per Watt	65
Color Temperature	4100 K
Color Rendering Index (CRI)	82

#### ELECTRICAL CHARACTERISTICS

Open Circuit Voltage Across Starter	198 V
Lamp Current	0.325 A
Current Crest Factor	1.7
Supply Current Frequency	60 Hz

#### DIMENSIONS

Maximum Overall Length (MOL)	6.6700 in(169.4 mm)
Nominal Length	6.700 in(170.2 mm)
Base Face to Top of Lamp	5.790 in(147.1 mm)

#### PRODUCT INFORMATION

Product Code	97609
Description	F26DBX/841/ECO
ANSI Code	60901-IEC-0526-2
Standard Package	BUNDLE
Standard Package GTIN	
Standard Package Quantity	50
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	50
UPC	043168976091

#### CAUTIONS & WARNINGS

##### Caution

- Lamp may shatter and cause injury if broken
  - Remove and install by grasping only plastic portion of the lamp.

#### NOTES

- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life