

Presented By: Candela Corporation

Contact Phone: 800-922-9226

Contact E-mail: sales@candelaCorp.com

Customer Name:

Project Name:

Fixture Type:



GE
Lighting

68852 - F32T8/SPX41/ECO2

F32T8/SPX41/ECO2

Product Photo



GENERAL CHARACTERISTICS

Base Description	Medium Bi-Pin
Base Type	Pin/Plug-In
Mercury Content	2.95 mg
Mercury-Picogram per mean lm hr	35.5
Rated Life Instant Start-Hrs	21000 h @ 3 h 30000 h @ 12 h
Rated Life Rapid Start - Hrs	30000 h @ 3 h 36000 h @ 12 h
Starting Temp (MIN) C-degrees	10 °C
Bulb Material	Sodalime glass
Rated Life Hours-nominal	30000 h
Primary Application	Full Wattage
Product Technology	Linear Fluorescent
Base	G13
Bulb Shape	T8

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	2770 lm
Nominal Initial Lumen per Watt	91
Initial Lumens-nominal	2925 lm
Color Rendering Index-CRI	85
Color Temperature	4100 K

PRODUCT INFORMATION

Product Code	68852
Description	F32T8/SPX41/ECO2
Alternative Unit Of Measure	CASE

DIMENSIONS

Diameter	1.0 in
Nominal Length	48.0 in

ELECTRICAL CHARACTERISTICS

Rated power (Watts)	32 W
---------------------	------