

Presented By: Candela Corporation
Contact Phone: (800) 922-9226
Contact E-mail: sales@candelacorp.com


Customer Name:
Project Name:
Fixture Type:



GE
Lighting

75399 - F40/25BX830IS/WM

GE Biax® T5 - Facilities; Hospitality; Office; Restaurant; Retail Display; Warehouse



GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Plug-In
Bulb	T5
Base	4-Pin (2G11)
Wattage	25
Voltage	120/126
Rated Life	20000 hrs
Starting Temperature	10 K (50 °F)
LEED-EB MR Credit	77 picograms Hg per mean lumen hour
Additional Info	TCLP compliant
Primary Application	Facilities;Hospitality;Office;Restaurant;Retail Display;Warehouse

PHOTOMETRIC CHARACTERISTICS

Initial Lumens	2600
Nominal Initial Lumens per Watt	104
Color Temperature	3000 K
Color Rendering Index (CRI)	82

DIMENSIONS

Maximum Overall Length (MOL)	21.5 cm
Nominal Length	21.5 cm

PRODUCT INFORMATION

Product Code	75399
Description	F40/25BX830IS/WM
ANSI Code	60901-IEC-6240-2
Standard Package	Master
Standard Package GTIN	10043168753996
Standard Package Quantity	40
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	40
UPC	043168753999

CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Fluorescent lamp lumens decline during life