



Product Number: 24080

Order Abbreviation: FB40/D30/6

General Description: 40W, T12 Curvalume rapid start fluorescent lamp, 6" leg spacing, Designer rare earth phosphor, 3000K color temperature, 70 CRI

Product Information

Abbrev. With Packaging Info.	FB40D306 12/CS 1/SKU
Actual Length (in)	22.598
Actual Length (mm)	573.99
Average Rated Life (hr)	18000
Base	Medium Bipin
Bulb	T12
Color Rendering Index (CRI)	70
Color Temperature/CCT (K)	3000
Diameter (in)	1.591
Diameter (mm)	40.40
Family Brand Name	Designer
Industry Standards	ANSI C78.901 - 2001
Initial Lumens at 25C	3050
Mean Lumens at 25C	2745
Nominal Length (in)	22.500
Nominal Length (mm)	571.50
Nominal Wattage (W)	40.00



Footnotes

- Average rated life is measured at 3 hours per start on 2-lamp, rapid start magnetic ballasts per IES recommended practice. Lamp life on single-lamp rapid start ballasts may be reduced.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.