


4

3

DWG NO. 1000492 BH 1

1

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED



## NOTES:

1. ALL DIMENSIONS ARE IN MM UNLESS OTHERWISE SPECIFIED.
2. SEAL TEMP SHOULD BE MAINTAINED BELOW 360°C.
3. THE DIMENSIONS AND SPECIFICATIONS OF PRODUCT LISTED IN THIS SHEET ARE SUBJECT TO CHANGE WITHOUT NOTICE FOR IMPROVEMENT.

## CHARACTERISTICS

VOLTAGE	24 V
WATTAGE	150 W
TOTAL LUMEN	3000 Lm
COLOR TEMP.	3400 K
BASE TYPE	86.35
AVERAGE LIFE	50 HR9
FILAMENT TYPE	CBor6
BURN POSITION	BD/Her

NEXT ASSY	USED ON

APPLICATION

ITEM	QTY	DESCRIPTION	CODE IDENT	PART NUMBER	REMARKS	
LIST OF MATERIALS						
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		CONTRACT NO.		<b>USHIO AMERICA, INC.</b> 5440 Carritos Ave. Cypress, CA90830		
DECIMALS .X ± - .XX ± - .XXX ± -		APPROVALS				DATE
ANGLES ± -		DRAWN				DB/20/99
DRILLED HOLES PER AND 103&7 REMOVE BURRS AND SHARP EDGES ALL DIMENSIONS AFTER PLATING		ENGR				D9/20/99
MATERIAL		MFG		TITLE FCS, JC24V-150W/UI HALOGEN LAMP		
COMPOSITE		QUAL				
FINISH		DRGN ACTVY		SIZE	B	
		DRVT ACTVY		DGDE IDENT NO.	FCS	
				DWG NO.	1000492	
				SCALE	NONE	
				WEIGHT		
				SHEET	1 OF 1	

4

3

2

1

CAD