



PHYSICAL DIMENSIONS

3" x 4" Core





WIRING DIAGRAM



CAPACITOR

Dry Typ or Oil Oval



Height: 2.75"

Length: 1.91"

Width: 2.91"



**2 YEAR WARRANTY FROM
DATE OF MANUFACTURE**

MAGNETIC HID BALLAST

Ballast Type	Magnetic Probe Start	Circuit Type	CWA
Lamp	175W Metal Halide M57/M107(150W)	Frequency	60Hz

ELECTRICAL SPECIFICATIONS

		Five Tap				
Input Voltage (V)		120	208	240	277	480
Line Current (A)	Operating	1.9	1.1	0.9	0.8	0.5
	Open Circuit	1.6	0.9	0.8	0.7	0.4
	Starting	1.3	0.7	0.6	0.5	0.3
Recommended Fuse		10	5	5	3	2
Input Voltage At Lamp Dropout		70	115	125	155	265
UL Class H 180°C Temp. Code		C	B	B	B	A
UL Class N 200°C Temp. Code		A	A	A	A	A
Nom. Open Circuit Voltage		302				
Input Power (W)		210				
Power Factor (≥ %)		90				
Regulation (± %)	Line Volts	10				
	Lamp Watts	10				
Min. Starting Temp		-20°F / -30°C				
Ballast Dimensions (inches)	A	2.44				
	B	4.10				
Ballast Net Weight (lbs)		6.9				
Lead Length (inches)		12				
Capacitor	Capacitance (μF)	10				
	Min VAC Rating (V)	400				
Coil Material (Pri./ Sec.)		Cu / Al				

60 HZ. TEST PROCEDURES

Short Circuit Current (A)	Secondary	Min	1.5				
		Max	2.5				
	Input	Min	0.6	0.4	0.3	0.3	0.2
		Max	1.8	1.1	0.9	0.8	0.7
Open Circuit Voltage (V)	Min	250					
	Max	340					
High Potential Test (V)	1 Minute	2000					
	1 Second	2400					

REFERENCE LAMP DATA

	Test Range	ANSI Standard
Starting Current (A)		1.5 ~ 2.5
CCF	1.5	≤ 1.8
OCV (V)	250 ~ 340	
di/dt (A/ms)	1.1	≥ 0.65
Off Time (ms.)	1.8	≤ 2.75
Peak Current (A)	3.4	≤ 3.8
Overshoot (mA)	-12	≤ 45
VSS (V)	269	

OPTIONAL FEATURES

(ADD SUFFIX FOR OPTIONS)

-WB	With welded bracket
-I	With ignitor
-DC	With dry film capacitor
-OC	With oil filled capacitor
-K	With distributor replacement kit (includes bracket, capacitor and ignitor as necessary)