


ELECTRONIC BALLAST

IG226-32ELSK

- Two Lamp
- Multi-Watt
- Small Case Size
- High Heat
- Lightweight
- Energy Saving

**HIGH TEMP
90°C**



Features & Benefits

Wide lamp versatility, suitable for two CFQ26W/G24q, CFTR26W/GX24q, or CFTR32W/GX24q lamps

Class A Sound Rating

End of Lamp Life Protection

More efficient compared to standard magnetic ballasts

Lead wires do not interfere with mounting holes

Contains No PCBs

Eliminates strobing

Thermal potting

Metal enclosure

Rapid Start




RoHS compliant


SPECIFICATIONS

- Operating Voltage: 120 VAC \pm 10%
- Frequency: 50/60Hz
- Protection: Class P Inherent Thermal Protection
- Regulatory Approvals: UL, CUL Listed
- Min. Starting Temp: 0°F (-17.78°C)
- Max. Case Temp: 194°F (90°C)
- Over Current: Fuse
- FCC, 47 CFR, Part 18 Consumer Limits
- Type 1 Outdoor, Normal Power Factor

DIMENSIONS



WIRING DIAGRAM



Weight: 14 oz. Case Quantity: 40pcs Case Weight: 29.5 lbs Standard Lead Length: black/white-12" blue/red/yellow-12"

Line Voltage	Lamp Type	Line Current	Input Power	Power Factor	Crest Factor	Ballast Factor	THD Percent	Min Start Temp
120	CFQ26W/G24q	0.57	44.5	0.513	1.46	0.86	119.6	0°F
120	CFTR26W/GX24q	0.56	44.7	0.513	1.49	0.77	119.9	0°F
120	CFTR32W/GX24q	0.62	48.2	0.521	1.43	0.69	118.9	0°F