



MR-16 JDR

- Only for Use in Approved Halogen Fixtures
- 2 inch Dichroic Coated Reflector
- Line Voltage - 120 Volts
- Operate Base Up
- Intermediate Screw Base - E17
- Medium Screw Base - E26

Watts	Ushio Ordering Code	Ushio Lamp Description	ANSI Code	Dimension		Beam		Color Temp K	Avg Life h	Case Qty
				MOL (A)	Angle	Spread	Max CP cd			
Intermediate Screw Base – E17										
75	1001032	JDR120V-75WL/SP14	FSA	3.0	14°	Spot	5000	3000	2000	10
75	1001030	JDR120V-75WL/NFL24	FSB	3.0	24°	Narrow Flood	1800	3000	2000	10
75	1001033	JDR120V-75WL/FL38	FSD	3.0	38°	Flood	1300	3000	2000	10
100	1001013	JDR120V-100WL/SP14	FSC	3.0	14°	Spot	7100	3000	2000	12
100	1001011	JDR120V-100WL/NFL24	FSE	3.0	24°	Narrow Flood	4200	3000	2000	10
100	1001016	JDR120V-100WL/FL38	FSF	3.0	38°	Flood	2800	3000	2000	10
Krypton Fill Medium Screw Base – E26 (cooler than Halogen)										
20	1001019	JDR120V-20W/FL28/E26/INC		2.8	28°	Flood	—	2800	2000	10
40	1001020	JDR120V-40W/FL28/E26/INC		2.8	28°	Flood	—	2900	2000	10
60	1001021	JDR120V-60W/FL28/E26/INC		2.8	28°	Flood	—	3150	2000	10
Medium Screw Base – E26										
75	1001834	JDR120V-75WL/SP14		3.0	14°	Spot	5000	3000	2000	10
75	1001022	JDR120V-75W/NFL20/FG**		3.0	20°	Narrow Flood	2800	3000	2000	20
75	1001031	JDR120V-75WL/NFL24		3.0	24°	Narrow Flood	2800	3000	2000	10
75	1001836	JDR120V-75WL/FL30		3.0	30°	Flood	2100	3000	2000	10
75	1001029	JDR120V-75W/FL30/FG**		3.0	30°	Flood	2100	3000	2000	20
100	1001014	JDR120V-100WL/NSP10		3.0	10°	Narrow Spot	6300	3000	2000	10
100	1001012	JDR120V-100WL/NFL20		3.0	20°	Narrow Flood	4200	3000	2000	10
100	1001017	JDR120V-100WL/FL30		3.0	30°	Flood	2500	3000	2000	10

** with Front Glass cover

All dimensions shown in inches unless otherwise noted.



E17

E26