

TUNGSTEN HALOGEN/KRYPTON REFLECTOR LAMPS • MR16


MR16 JDR

- Only for Use in Approved Halogen Fixtures
- 2 inch Dichroic Coated Reflector
- Line Voltage - 120 Volts
- Operate Base Up
- Medium Screw Base - E26
- Available with Front Glass Cover (/FG)



Watts (W)	Ordering Code	Lamp Description	MOL (A)	Beam		Color Temp (K)	Avg Life (h)	Case Qty
				Angle	Spread			
MR16 JDR, Krypton Fill Medium Screw Base – E26 (cooler than Halogen)								
60	1001021	JDR120V-60W/FL28/E26/INC	2.8	28°	Flood	—	2000	10
MR16 JDR, Medium Screw Base – E26								
75	1001834	JDR120V-75WL/SP14	3.0	14°	Spot	5000	2000	10
75	1001022	JDR120V-75W/NFL20/FG	3.0	20°	Narrow Flood	2800	2000	20
75	1001031	JDR120V-75WL/NFL24	3.0	24°	Narrow Flood	2800	2000	10
75	1001836	JDR120V-75WL/FL30	3.0	30°	Flood	2100	2000	10
75	1001029	JDR120V-75W/FL30/FG	3.0	30°	Flood	2100	2000	20
100	1001014	JDR120V-100WL/NSP10	3.0	10°	Narrow Spot	6300	2000	10
100	1001012	JDR120V-100WL/NFL20	3.0	20°	Narrow Flood	4200	2000	10
100	1001017	JDR120V-100WL/FL30	3.0	30°	Flood	2500	2000	10

All dimensions shown in inches unless otherwise noted.



E26