



Features

- Advanced dimming with Pro-DIM technology: 0-10V and/or AB dimming
- No Polarity: lamp ends can be reversed
- Same wiring as fluorescent lamp/ballast system
- UL 1598C for safety
- Full glass as fluorescent T5
- No Mercury, No UV
- Suitable for Dry and Damp Locations
- Low Temperature Operation
- Instant On
- 50,000 hours with no limitation on On/Off Cycles
- 5-year Warranty
- Evaluated for use in totally enclosed, recessed luminaires, surface mount wall and ceiling luminaires, outdoor luminaires (open surface mount luminaires with compartment protection from weather)
- For use with Class 2 driver only

CoreTech LED Series

PRODUCT SPECIFICATIONS

Model	Lamp Input Current	System Wattage	Lamp Wattage	Length	CRI	Initial Lumens	Lamp Efficacy (lm/W)	System Efficacy (lm/W)	Beam Angle	CCT	DLC
L24T5/830/11G-XT	250mA	11	8	24"	82	1200	150	109	240	3000K	No
L24T5/835/11G-XT	250mA	11	8	24"	82	1200	150	109	240	3500K	No
L24T5/840/11G-XT	250mA	11	8	24"	82	1200	150	109	240	4000K	No
L24T5/850/11G-XT	250mA	11	8	24"	82	1200	150	109	240	5000K	No
L24T5/830/11G-XT	360mA	12	9	24"	82	1300	145	108	240	3000K	No
L24T5/835/11G-XT	360mA	12	9	24"	82	1300	145	108	240	3500K	No
L24T5/840/11G-XT	360mA	12	9	24"	82	1300	145	108	240	4000K	No
L24T5/850/11G-XT	360mA	12	9	24"	82	1300	145	108	240	5000K	No
L24T5/830/11G-XT	500mA	15	12	24"	82	1700	142	113	240	3000K	No
L24T5/835/11G-XT	500mA	15	12	24"	82	1700	142	113	240	3500K	No
L24T5/840/11G-XT	500mA	15	12	24"	82	1700	142	113	240	4000K	No
L24T5/850/11G-XT	500mA	15	12	24"	82	1700	142	113	240	5000K	No

Wiring diagram





Specification data is based on tests performed in a controlled environment and represents relative performance. Actual performance can vary depending on operating conditions. Application and performance data subject to change without notice. All specifications are nominal unless noted otherwise.

Espen Technology, Inc. | 12257 Florence Avenue | Santa Fe Springs, CA 90670 | Phone: (562) 529-2938 | Fax: (562) 529-2978
Toll Free: (866) 933-7736 | Email: info@espentech.com | www.espentech.com