

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT



California Quality LED Lamps

Product Specifications

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelops you in warmth - lighting that generates beauty with every flip of the switch.

TCP's California Quality High CRI LED line offers exceptional color consistency and rendering while meeting all requirements for Title 24 JA8-2019-E.

Reasons to choose the California Quality LED Lamps from TCP

- Excellent color consistency and CRI enhance colors of focal point while maintaining uniformity throughout lighting installation
- Uses up to 80% less energy than halogen alternatives, providing instant energy savings
- Long lasting - minimizing replacement and maintenance costs
- Smooth, uniform dimming
- PAR style lamps can be used in wet locations
- Shatter resistant - lowering the risk of injury and breakage
- Meets California Title 24 JA8-2019-E
- Damp location rated - PARs wet location rated

Ideal Applications

- Track and Display lights
- Sconces
- General lighting
- Table and Floor Lamps
- Ceiling Fixture and Sconces
- Recessed Downlights
- Protected Outdoor Fixtures

Specifications

| | |
|------------------------|--------------------------------|
| Voltage | 120V |
| Input Line Frequency | 50/60Hz |
| Lamp Life (Rated) | 15,000 / 25,000 / 35,000 hours |
| Minimum Starting Temp | -22°C/-8°F |
| Maximum Operating Temp | 45°C/113°F |
| CRI | ≥ 90 |

| | |
|------------|--|
| Beam Angle | Omnidirectional, 360°, 110°, 40°, 25° |
| Base | E12, E26, GU5.3, GU10, GU24 |
| Warranty | 3 Years (Filaments) 5 Years (A-/BR/R20/MR16/PAR/Downlights) |

Suitable for use in totally enclosed fixtures



TCP®
325 Campus Dr | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day

*Based on 12 hours use per day



Specifications

A Lamps



6W A19

10W GU24-A19

10W A19

13W A19

17W A21

17.5W GU24-A21

17/10/8 W A21 3 Way

BR Lamps



8W BR20

16W BR20

13.5W BR40

7W E20

7W GU10 MR16

6.5W GU2.3 MR16

PAR Lamps



1.5W PAR38

10W PAR30

10W PAR38/4

7W PAR20

7W PAR16

Downlights



4" Downlights

5" & 6" Downlights

9W A19

4.5W E11

4.3W G16

4.3W G25

3W T10

4.2W S119

| ITEM # | DESCRIPTION | WATTS | REPLACEMENT WATTS | LUMENS | BEAM ANGLE | CCT | HOURS | CRI | MOL. (inches) | IDA (inches) | TITLE | 20 | JAB | BASE | CASE | |
|--|-----------------------------|---------|-------------------|--------------|------------|-------|--------|-----|---------------|--------------|-------|-----|-----|------|------|--|
| A Lamps – Dimmable • 25,000 Hours | | | | | | | | | | | | | | | | |
| L40A19D2527KCO | A19 40W 27K DM/CC | 6 | 40 | 475 | OWN | 2700K | 25,000 | 90 | 4.0 | 2.2 | Y | Y | Y | E26 | 12 | |
| L40A19D2530KCO | A19 40W 30K DM/CC | 6 | 40 | 475 | OWN | 3000K | 25,000 | 90 | 4.0 | 2.2 | Y | Y | Y | E26 | 12 | |
| L40A19D2535KCO | A19 40W 35K DM/CC | 6 | 40 | 475 | OWN | 3500K | 25,000 | 90 | 4.0 | 2.2 | Y | Y | Y | E26 | 12 | |
| L40A19D2541KCO | A19 40W 41K DM/CC | 6 | N/A | 525 | OWN | 4100K | 25,000 | 90 | 4.0 | 2.2 | Y | N/A | N/A | E26 | 12 | |
| L40A19D2550KCO | A19 40W 50K DM/CC | 6 | N/A | 525 | OWN | 5000K | 25,000 | 90 | 4.0 | 2.2 | Y | N/A | N/A | E26 | 12 | |
| L11A19GJD2527KCO | LED 10W A19 GU24 DM 27K CC | 10 | 60 | 800 | OWN | 2700K | 25,000 | 90 | 4.8 | 2.4 | Y | N | N | GU24 | 12 | |
| L11A19GJD2530KCO | LED 10W A19 GU24 DM 30K CC | 10 | 60 | 850 | OWN | 3000K | 25,000 | 90 | 4.8 | 2.4 | Y | N | N | GU24 | 12 | |
| L11A19GJD2535KCO | LED 10W A19 GU24 DM 35K CC | 10 | 60 | 850 | OWN | 3500K | 25,000 | 90 | 4.8 | 2.4 | Y | N | N | GU24 | 12 | |
| L11A19GJD2541KCO | LED 10W A19 GU24 DM 41K CC | 10 | 60 | 850 | OWN | 4100K | 25,000 | 90 | 4.8 | 2.4 | Y | N | N | GU24 | 12 | |
| L60A19D2527KCO | A19 60W 27K DM/CC | 10 | 60 | 800 | OWN | 2700K | 25,000 | 90 | 4.3 | 2.4 | Y | Y | Y | E26 | 12 | |
| L60A19D2530KCO | A19 60W 30K DM/CC | 10 | 60 | 800 | OWN | 3000K | 25,000 | 90 | 4.3 | 2.4 | Y | Y | Y | E26 | 12 | |
| L60A19D2535KCO | A19 60W 35K DM/CC | 10 | 60 | 800 | OWN | 3500K | 25,000 | 90 | 4.3 | 2.4 | Y | Y | Y | E26 | 12 | |
| L60A19D2541KCO | A19 60W 41K DM/CC | 10 | N/A | 800 | OWN | 4100K | 25,000 | 90 | 4.3 | 2.4 | Y | N/A | N/A | E26 | 12 | |
| L60A19D2550KCO | A19 60W 50K DM/CC | 10 | N/A | 800 | OWN | 5000K | 25,000 | 90 | 4.3 | 2.4 | Y | N/A | N/A | E26 | 12 | |
| L75A19D2527KCO | A19 75W 27K DM/CC | 13 | 75 | 1100 | OWN | 2700K | 25,000 | 90 | 4.4 | 2.5 | Y | Y | Y | E26 | 12 | |
| L75A19D2530KCO | A19 75W 30K DM/CC | 13 | 75 | 1100 | OWN | 3000K | 25,000 | 90 | 4.4 | 2.5 | Y | Y | Y | E26 | 12 | |
| L75A19D2535KCO | A19 75W 35K DM/CC | 13 | 75 | 1100 | OWN | 3500K | 25,000 | 90 | 4.4 | 2.5 | Y | Y | Y | E26 | 12 | |
| L75A19D2541KCO | A19 75W 41K DM/CC | 13 | N/A | 1100 | OWN | 4100K | 25,000 | 90 | 4.4 | 2.5 | Y | N/A | N/A | E26 | 12 | |
| L75A19D2550KCO | A19 75W 50K DM/CC | 13 | N/A | 1100 | OWN | 5000K | 25,000 | 90 | 4.4 | 2.5 | Y | N/A | N/A | E26 | 12 | |
| L100A21GD2527KCO | A21 100W 27K DM/CC | 16.5 | 100 | 1600 | OWN | 2700K | 25,000 | 90 | 5.2 | 2.5 | Y | Y | Y | GU24 | 12 | |
| L100A21GD2530KCO | A21 100W 30K DM/CC | 16.5 | 100 | 1600 | OWN | 3000K | 25,000 | 90 | 5.2 | 2.5 | Y | Y | Y | GU24 | 12 | |
| L100A21GD2535KCO | A21 100W 35K DM/CC | 16.5 | 100 | 1600 | OWN | 3500K | 25,000 | 90 | 5.2 | 2.5 | Y | Y | Y | GU24 | 12 | |
| L100A21GD2541KCO | A21 100W 41K DM/CC | 16.5 | 100 | 1600 | OWN | 4100K | 25,000 | 90 | 5.2 | 2.5 | Y | Y | Y | GU24 | 12 | |
| L100A21D2527KCO | A21 100W 27K DM/CC | 17 | 100 | 1600 | OWN | 2700K | 25,000 | 90 | 5.2 | 2.8 | Y | Y | Y | E26 | 12 | |
| L100A21D2530KCO | A21 100W 30K DM/CC | 17 | 100 | 1625 | OWN | 3000K | 25,000 | 90 | 5.2 | 2.8 | Y | Y | Y | E26 | 12 | |
| L100A21D2535KCO | A21 100W 35K DM/CC | 17 | 100 | 1625 | OWN | 3500K | 25,000 | 90 | 5.2 | 2.8 | Y | Y | Y | E26 | 12 | |
| L100A21D2541KCO | A21 100W 41K DM/CC | 17 | N/A | 1675 | OWN | 4100K | 25,000 | 90 | 5.2 | 2.8 | Y | N/A | N/A | E26 | 12 | |
| L100A21D2550KCO | A21 100W 50K DM/CC | 17 | N/A | 1675 | OWN | 5000K | 25,000 | 90 | 5.2 | 2.8 | Y | N/A | N/A | E26 | 12 | |
| L100A21BW2527KCO | A21 3 WAY 100/60/40W 27K CC | 17/10/6 | 100/60/40 | 1650/800/450 | OWN | 2700K | 25,000 | 90 | 5.2 | 2.8 | Y | N/A | N/A | E26 | 12 | |
| L100A21BW2530KCO | A21 3 WAY 100/60/40W 30K CC | 17/10/6 | 100/60/40 | 1650/800/450 | OWN | 3000K | 25,000 | 90 | 5.2 | 2.8 | Y | N/A | N/A | E26 | 12 | |
| L100A21BW2541KCO | A21 3 WAY 100/60/40W 41K CC | 17/10/6 | N/A | 1700/800/450 | OWN | 4100K | 25,000 | 90 | 5.2 | 2.8 | Y | N/A | N/A | E26 | 12 | |
| L100A21BW2550KCO | A21 3 WAY 100/60/40W 50K CC | 17/10/6 | N/A | 1700/800/450 | OWN | 5000K | 25,000 | 90 | 5.2 | 2.8 | Y | N/A | N/A | E26 | 12 | |

TCP California Quality LED Lamps

Specifications

| ITEM # | DESCRIPTION | WATTS | REPLACEMENT WATTS | LUMENS | BEAM ANGLE | CCT | HOURS | CR | MOL (inches) | DA (inches) | TITLE 20 | JAB | BASE | CASE QTY | |
|---|--------------------------------|-------|-------------------|--------|------------|-------|--------|----|--------------|-------------|----------|-----|-------|----------|--|
| BR Lamps – Dimmable • 25,000 Hours | | | | | | | | | | | | | | | |
| 165983002527KCC | BR60 65W 27K DIM CO | 8 | 65 | 650 | 110° | 2700K | 25,000 | 90 | 5.4 | 3.8 | Y | Y | E26 | 12 | |
| 165983002530KCC | BR60 65W 30K DIM CO | 8 | 65 | 650 | 110° | 3000K | 25,000 | 90 | 5.4 | 3.8 | Y | Y | E26 | 12 | |
| 165983002541KCC | BR60 65W 41K DIM CO | 8 | N/A | 650 | 110° | 4100K | 25,000 | 90 | 5.4 | 3.8 | Y | N/A | E26 | 12 | |
| 165983002550KCC | BR60 65W 50K DIM CO | 8 | N/A | 700 | 110° | 5000K | 25,000 | 90 | 5.4 | 3.8 | Y | N/A | E26 | 12 | |
| 110083002527KCC | BR60 100W 27K DIM CO | 16 | 100 | 1500 | 110° | 2700K | 25,000 | 90 | 5.4 | 3.8 | Y | Y | E26 | 12 | |
| 110083002530KCC | BR60 100W 30K DIM CO | 16 | 100 | 1550 | 110° | 3000K | 25,000 | 90 | 5.4 | 3.8 | Y | Y | E26 | 12 | |
| 110083002541KCC | BR60 100W 41K DIM CO | 16 | N/A | 1600 | 110° | 4100K | 25,000 | 90 | 5.4 | 3.8 | Y | N/A | E26 | 12 | |
| 110083002550KCC | BR60 100W 50K DIM CO | 16 | N/A | 1600 | 110° | 5000K | 25,000 | 90 | 5.4 | 3.8 | Y | N/A | E26 | 12 | |
| 18594002527KCC | BR40 85W 27K DIM CO | 13.5 | 85 | 1065 | 110° | 2700K | 25,000 | 90 | 6.1 | 5.0 | Y | Y | E26 | 12 | |
| 18594002530KCC | BR40 85W 30K DIM CO | 13.5 | 85 | 1065 | 110° | 3000K | 25,000 | 90 | 6.1 | 5.0 | Y | Y | E26 | 12 | |
| 18594002541KCC | BR40 85W 41K DIM CO | 13.5 | N/A | 1065 | 110° | 4100K | 25,000 | 90 | 6.1 | 5.0 | Y | N/A | E26 | 12 | |
| 18594002550KCC | BR40 85W 50K DIM CO | 13.5 | N/A | 1065 | 110° | 5000K | 25,000 | 90 | 6.1 | 5.0 | Y | N/A | E26 | 12 | |
| R20 Lamps – Dimmable • 25,000 Hours | | | | | | | | | | | | | | | |
| 15092002527KCC | R20 50W 27K DIM CO | 7 | 50 | 525 | 110° | 2700K | 25,000 | 90 | 3.8 | 2.5 | Y | Y | E26 | 12 | |
| 15092002530KCC | R20 50W 30K DIM CO | 7 | 50 | 525 | 110° | 3000K | 25,000 | 90 | 3.8 | 2.5 | Y | Y | E26 | 12 | |
| MR16 Lamps – Dimmable • 25,000 Hours | | | | | | | | | | | | | | | |
| 150916002527KCC | MR16 50W 27K GU10 DIM 40° CO | 7 | 50 | 500 | 40° | 2700K | 25,000 | 90 | 2.3 | 2.0 | Y | N | GU10 | 12 | |
| 150916002530KCC | MR16 50W 30K GU10 DIM 40° CO | 7 | 50 | 500 | 40° | 3000K | 25,000 | 90 | 2.3 | 2.0 | Y | N | GU10 | 12 | |
| 150916002527KFCO | MR16 50W 27K GU5.3 DIM 40° 12V | 6.5 | 50 | 430 | 40° | 2700K | 25,000 | 90 | 2.0 | 2.0 | Y | Y | GU5.3 | 12 | |
| 150916002530KFCO | MR16 50W 30K GU5.3 DIM 40° 12V | 6.5 | 50 | 470 | 40° | 3000K | 25,000 | 90 | 2.0 | 2.0 | Y | Y | GU5.3 | 12 | |

Specifications

| ITEM # | DESCRIPTION | WATTS | REPLACEMENT WATTS | LUMENS | BEAM ANGLE | COLOR | HOURS | CR | MOL (inches) | DA (inches) | TITLE 20 | JAB | BASE | CASE QTY | |
|--|--------------------------|-------|-------------------|--------|------------|-------|--------|----|--------------|-------------|----------|-----|------|----------|--|
| PAR Lamps – Dimmable • 25,000 Hours | | | | | | | | | | | | | | | |
| 190P38002527KFCO | PAR38 90W 27K DIM 40° CO | 13 | 90 | 950 | 40° | 2700K | 25,000 | 90 | 5.3 | 4.8 | Y | Y | E26 | 12 | |
| 190P38002530KFCO | PAR38 90W 30K DIM 40° CO | 13 | 90 | 1000 | 40° | 3000K | 25,000 | 90 | 5.3 | 4.8 | Y | Y | E26 | 12 | |
| 190P38002527KFCO | PAR38 90W 27K DIM 25° CO | 13 | 90 | 950 | 25° | 2700K | 25,000 | 90 | 5.3 | 4.8 | Y | Y | E26 | 12 | |
| 190P38002530KFCO | PAR38 90W 30K DIM 25° CO | 13 | 90 | 1000 | 25° | 3000K | 25,000 | 90 | 5.3 | 4.8 | Y | Y | E26 | 12 | |
| 175930002527KFCO | P50 75W 27K DIM 25° CO | 10 | 75 | 750 | 25° | 2700K | 25,000 | 90 | 4.6 | 3.8 | Y | Y | E26 | 12 | |
| 175930002530KFCO | P50 75W 30K DIM 25° CO | 10 | 75 | 750 | 25° | 3000K | 25,000 | 90 | 4.6 | 3.8 | Y | Y | E26 | 12 | |
| 175930002535KFCO | P50 75W 35K DIM 25° CO | 10 | 75 | 750 | 25° | 3500K | 25,000 | 90 | 4.6 | 3.8 | Y | Y | E26 | 12 | |
| 175930002527KFCO | P50 75W 27K DIM 40° CO | 10 | 75 | 750 | 40° | 2700K | 25,000 | 90 | 4.6 | 3.8 | Y | Y | E26 | 12 | |
| 175930002530KFCO | P50 75W 30K DIM 40° CO | 10 | 75 | 750 | 40° | 3000K | 25,000 | 90 | 4.6 | 3.8 | Y | Y | E26 | 12 | |
| 175930002535KFCO | P50 75W 35K DIM 40° CO | 10 | 75 | 750 | 40° | 3500K | 25,000 | 90 | 4.6 | 3.8 | Y | Y | E26 | 12 | |
| 175930002527KFCO | P50 75W 27K DIM 25° CO | 9.5 | 75 | 750 | 25° | 2700K | 25,000 | 90 | 3.8 | 3.6 | Y | Y | E26 | 12 | |
| 175930002530KFCO | P50 75W 30K DIM 25° CO | 9.5 | 75 | 750 | 25° | 3000K | 25,000 | 90 | 3.8 | 3.6 | Y | Y | E26 | 12 | |
| 175930002535KFCO | P50 75W 35K DIM 25° CO | 9.5 | 75 | 750 | 25° | 3500K | 25,000 | 90 | 3.8 | 3.6 | Y | Y | E26 | 12 | |
| 175930002527KFCO | P50 75W 27K DIM 40° CO | 9.5 | 75 | 750 | 40° | 2700K | 25,000 | 90 | 3.8 | 3.6 | Y | Y | E26 | 12 | |
| 175930002530KFCO | P50 75W 30K DIM 40° CO | 9.5 | 75 | 750 | 40° | 3000K | 25,000 | 90 | 3.8 | 3.6 | Y | Y | E26 | 12 | |
| 150920002527KFCO | P20 50W 27K DIM 25° CO | 7 | 50 | 550 | 25° | 2700K | 25,000 | 90 | 3.5 | 2.5 | Y | Y | E26 | 12 | |
| 150920002530KFCO | P20 50W 30K DIM 25° CO | 7 | 50 | 550 | 25° | 3000K | 25,000 | 90 | 3.5 | 2.5 | Y | Y | E26 | 12 | |
| 150920002527KFCO | P20 50W 27K DIM 40° CO | 7 | 50 | 600 | 40° | 2700K | 25,000 | 90 | 3.5 | 2.5 | Y | Y | E26 | 12 | |
| 150920002530KFCO | P20 50W 30K DIM 40° CO | 7 | 50 | 600 | 40° | 3000K | 25,000 | 90 | 3.5 | 2.5 | Y | Y | E26 | 12 | |
| 150916002527KFCO | P16 50W 27K DIM 40° CO | 7 | 50 | 500 | 40° | 2700K | 25,000 | 90 | 3.5 | 2.0 | Y | Y | E26 | 12 | |
| 150916002530KFCO | P16 50W 30K DIM 40° CO | 7 | 50 | 500 | 40° | 3000K | 25,000 | 90 | 3.5 | 2.0 | Y | Y | E26 | 12 | |



TCP®
325 Campus Dr | Aurora, Ohio 44002 | P: 800-394-1496 | tcp.com



Specifications

| ITEM # | DESCRIPTION | WATTS | REPLACEMENT WATTS | LUMENS | BEAM ANGLE | COLOR | HOURS | CFI | MOL. (inches) | DLA. (inches) | TITLE 20 | JAB | BASE | CASE QTY |
|---|-------------------------------|-------|-------------------|--------|------------|-------|--------|-----|---------------|---------------|----------|-----|------|----------|
| Downlights – Dimmable • 35,000 Hours | | | | | | | | | | | | | | |
| U750K4035Z7CCQ | Downlight 4" 27K DMV CO | 9.5 | 75 | 750 | 110° | 2700K | 35,000 | 90 | 3.0 | 5.0 | Y | Y | E26 | 12 |
| U750K403536KCCQ | Downlight 4" 30K DMV CO | 9.5 | 75 | 750 | 110° | 3000K | 35,000 | 90 | 3.0 | 5.0 | Y | Y | E26 | 12 |
| U750K403541KCCQ | Downlight 4" 41K DMV CO | 9.5 | N/A | 750 | 110° | 4100K | 35,000 | 90 | 3.0 | 5.0 | Y | N/A | E26 | 12 |
| Downlights – Dimmable • 35,000 Hours • PHASING OUT • | | | | | | | | | | | | | | |
| 1850K5003541KCCQ | Downlight 5/6" 41K DMV CO | 10.5 | N/A | 850 | 110° | 4100K | 35,000 | 90 | 3.0 | 7.5 | Y | N/A | E26 | 6 |
| Filament Lamps – Dimmable • 15,000 Hours | | | | | | | | | | | | | | |
| 1FF60A19D1527KCCQ | LED 9W GLASS A19 DMV 27K CO | 9 | 60 | 810 | OWN | 2700K | 15,000 | 90 | 4.3 | 2.4 | Y | N | E26 | 12 |
| 1FF60A19D1530KCCQ | LED 9W GLASS A19 DMV 30K CO | 9 | 60 | 810 | OWN | 3000K | 15,000 | 90 | 4.3 | 2.4 | Y | N | E26 | 12 |
| 1FB11D4027ECCQ | LED FL 4.5W B11 CL E12 27K CO | 4.5 | 40 | 350 | 360° | 2700K | 15,000 | 90 | 3.8 | 1.4 | Y | N | E12 | 12 |
| 1FG1604027ECCQ | LED FL 4.5W G16 RRE12 27K CO | 4.5 | 40 | 360 | 360° | 2700K | 15,000 | 90 | 3.4 | 2.0 | Y | N | E12 | 12 |
| 1FG1604027ECCQ | LED FL 4.5W G16 CL E12 27K CO | 4.5 | 40 | 360 | 360° | 2700K | 15,000 | 90 | 3.4 | 2.0 | Y | N | E12 | 12 |
| 1FG2504027ECCQ | LED FL 4.5W G25 RRE26 27K CO | 4.5 | 40 | 350 | 360° | 2700K | 15,000 | 90 | 4.5 | 3.2 | Y | N | E26 | 12 |
| 1FG2504027ECCQ | LED FL 4.5W G25 CL E26 27K CO | 4.5 | 40 | 350 | 360° | 2700K | 15,000 | 90 | 4.5 | 3.2 | Y | N | E26 | 12 |
| 1FT100304027CCEQ | LED FL 5W T10 CL E26 27K CO | 5 | 40 | 450 | 360° | 2700K | 15,000 | 90 | 5.3 | 1.2 | Y | N | E26 | 12 |
| 1F3119L04027CCEQ | LED FL 4.2W S19 CL E26 27K CO | 4.2 | 40 | 340 | 360° | 2700K | 15,000 | 90 | 5.4 | 2.5 | Y | N | E26 | 12 |

Dimmer Compatibility

| E26 SUGGESTED DIMMER COMPATIBILITY | |
|------------------------------------|--|
| MANUFACTURER | MODEL NUMBER |
| Leviton | R50FR06-10VA R61-106674-PCJ |
| Lutron | CTC-153PHHWH TCCL-153PHWH DWWCH-153PHHWH |

| MR16 SUGGESTED DIMMER COMPATIBILITY | |
|-------------------------------------|---|
| MANUFACTURER | MODEL NUMBER |
| Leviton | SureSlide-6615P Diva D10V-600P Diva D10V-600P |
| Lutron | Skytrak-SLE-V300P Skytrak-SLE-V600P Nova N16K450 Nova N16V400 MAN-600 VERII-V16V-600VA |
| Cooper | DAL06P - All load dimmer SAL06P |

