



# California Quality LED Lamps

## Product Specifications



TCP's California Quality High CRI LED line offers exceptional color consistency and rendering while meeting all requirements for Title 24 JA8-2019-E.

## Reasons to choose the California Quality LED Lamps from TCP

- Excellent color consistency and CRI enhance colors of focal point while maintaining uniformity throughout lighting installation
- Uses up to 80% less energy than halogen alternatives, providing instant energy savings
- Long lasting - minimizing replacement and maintenance costs
- Smooth, uniform dimming
- PAR style lamps can be used in wet locations
- Shatter resistant - lowering the risk of injury and breakage
- Meets California Title 24 JA8-2019-E
- Damp location rated - PARs wet location rated



## Ideal Applications

- Track and Display Lights
- Sconces
- General Lighting
- Table and Floor Lamps
- Ceiling Fixture and Sconces
- Recessed Downlights
- Protected Outdoor Fixtures

## Specifications

Voltage ..... 120V/12V  
Input Line Frequency..... 50/60Hz  
Lamp Life (Rated) ..... 15,000 / 25,000 / 35,000 hours  
Minimum Starting Temp ..... -22°C/-8°F  
Maximum Operating Temp..... 45°C/113°F  
CRI ..... ≥ 90

Beam Angle ..... Omnidirectional, 360°, 110°, 40°, 25°  
Base ..... E12, E26, GU5.3, GU10, GU24  
Warranty..... 3 Years (Filaments)  
..... 5 Years (A/BR/R20/MR16/PAR/Downlights)  
Suitable for use in totally enclosed fixtures





# California Quality LED Lamps

## Specifications

### A Lamps



6W A19



10W GU24 A19



10W A19



13W A19



17W A21



17.5W GU24 A21



17/10/6 W A21 3 Way

### BR Lamps



8W BR30



16W BR30



13.5W BR40

### R20 Lamp



7W R20

### MR16 Lamps



7W GU10 MR16



6.5W GU5.3 MR16

### PAR Lamps



13W PAR38



10W PAR30



10W PAR30SN



7W PAR20



7W PAR16

### Downlights



4" Downlights



5" & 6" Downlights

### Filaments



9W A19



4.5W B11



4.5W G16



4.5W G25



5W T10



4.2W ST19

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com



RoHS  
COMPLIANT

3 YEAR  
WARRANTY  
\*Based on 12 hours  
use per day

5 YEAR  
WARRANTY  
\*Based on 12 hours  
use per day



# California Quality LED Lamps

| ITEM #                                   | DESCRIPTION                 | WATTS   | REPLACEMENT WATTS | LUMENS       | BEAM ANGLE | CCT   | HOURS  | CRI | MOL (inches) | DIA (inches) | TITLE 20 | JA8 | BASE | CASE QTY |
|------------------------------------------|-----------------------------|---------|-------------------|--------------|------------|-------|--------|-----|--------------|--------------|----------|-----|------|----------|
| <b>A Lamps – Dimmable • 25,000 Hours</b> |                             |         |                   |              |            |       |        |     |              |              |          |     |      |          |
| L40A19D2527KCQ                           | A19 40W 27K DIM CQ          | 6       | 40                | 475          | OMNI       | 2700K | 25,000 | 90  | 4.0          | 2.2          | Y        | Y   | E26  | 12       |
| L40A19D2530KCQ                           | A19 40W 30K DIM CQ          | 6       | 40                | 475          | OMNI       | 3000K | 25,000 | 90  | 4.0          | 2.2          | Y        | Y   | E26  | 12       |
| L40A19D2535KCQ                           | A19 40W 35K DIM CQ          | 6       | 40                | 475          | OMNI       | 3500K | 25,000 | 90  | 4.0          | 2.2          | Y        | Y   | E26  | 12       |
| L40A19D2541KCQ                           | A19 40W 41K DIM CQ          | 6       | N/A               | 525          | OMNI       | 4100K | 25,000 | 90  | 4.0          | 2.2          | Y        | N/A | E26  | 12       |
| L40A19D2550KCQ                           | A19 40W 50K DIM CQ          | 6       | N/A               | 525          | OMNI       | 5000K | 25,000 | 90  | 4.0          | 2.2          | Y        | N/A | E26  | 12       |
| L11A19GUD2527KCQ                         | LED 10W A19 GU24 DIM 27K CQ | 10      | 60                | 800          | OMNI       | 2700K | 25,000 | 90  | 4.8          | 2.4          | Y        | N   | GU24 | 12       |
| L11A19GUD2530KCQ                         | LED 10W A19 GU24 DIM 30K CQ | 10      | 60                | 850          | OMNI       | 3000K | 25,000 | 90  | 4.8          | 2.4          | Y        | N   | GU24 | 12       |
| L11A19GUD2535KCQ                         | LED 10W A19 GU24 DIM 35K CQ | 10      | 60                | 850          | OMNI       | 3500K | 25,000 | 90  | 4.8          | 2.4          | Y        | N   | GU24 | 12       |
| L11A19GUD2541KCQ                         | LED 10W A19 GU24 DIM 41K CQ | 10      | 60                | 850          | OMNI       | 4100K | 25,000 | 90  | 4.8          | 2.4          | Y        | N   | GU24 | 12       |
| L60A19D2527KCQ                           | A19 60W 27K DIM CQ          | 10      | 60                | 800          | OMNI       | 2700K | 25,000 | 90  | 4.3          | 2.4          | Y        | Y   | E26  | 12       |
| L60A19D2530KCQ                           | A19 60W 30K DIM CQ          | 10      | 60                | 800          | OMNI       | 3000K | 25,000 | 90  | 4.3          | 2.4          | Y        | Y   | E26  | 12       |
| L60A19D2535KCQ                           | A19 60W 35K DIM CQ          | 10      | 60                | 800          | OMNI       | 3500K | 25,000 | 90  | 4.3          | 2.4          | Y        | Y   | E26  | 12       |
| L60A19D2541KCQ                           | A19 60W 41K DIM CQ          | 10      | N/A               | 800          | OMNI       | 4100K | 25,000 | 90  | 4.3          | 2.4          | Y        | N/A | E26  | 12       |
| L60A19D2550KCQ                           | A19 60W 50K DIM CQ          | 10      | N/A               | 800          | OMNI       | 5000K | 25,000 | 90  | 4.3          | 2.4          | Y        | N/A | E26  | 12       |
| L75A19D2527KCQ                           | A19 75W 27K DIM CQ          | 13      | 75                | 1100         | OMNI       | 2700K | 25,000 | 90  | 4.4          | 2.5          | Y        | Y   | E26  | 12       |
| L75A19D2530KCQ                           | A19 75W 30K DIM ECQ         | 13      | 75                | 1100         | OMNI       | 3000K | 25,000 | 90  | 4.4          | 2.5          | Y        | Y   | E26  | 12       |
| L75A19D2535KCQ                           | A19 75W 35K DIM ECQ         | 13      | 75                | 1100         | OMNI       | 3500K | 25,000 | 90  | 4.4          | 2.5          | Y        | Y   | E26  | 12       |
| L75A19D2541KCQ                           | A19 75W 41K DIM CQ          | 13      | N/A               | 1100         | OMNI       | 4100K | 25,000 | 90  | 4.4          | 2.5          | Y        | N/A | E26  | 12       |
| L75A19D2550KCQ                           | A19 75W 50K DIM CQ          | 13      | N/A               | 1100         | OMNI       | 5000K | 25,000 | 90  | 4.4          | 2.5          | Y        | N/A | E26  | 12       |
| L100A21GUD2527KCQ                        | A21 100W 27K GU24 DIM CQ    | 16.5    | 100               | 1600         | OMNI       | 2700K | 25,000 | 90  | 5.2          | 2.5          | Y        | Y   | GU24 | 12       |
| L100A21GUD2530KCQ                        | A21 100W 30K GU24 DIM CQ    | 16.5    | 100               | 1600         | OMNI       | 3000K | 25,000 | 90  | 5.2          | 2.5          | Y        | Y   | GU24 | 12       |
| L100A21GUD2535KCQ                        | A21 100W 35K GU24 DIM CQ    | 16.5    | 100               | 1600         | OMNI       | 3500K | 25,000 | 90  | 5.2          | 2.5          | Y        | Y   | GU24 | 12       |
| L100A21GUD2541KCQ                        | A21 100W 41K GU24 DIM CQ    | 16.5    | 100               | 1600         | OMNI       | 4100K | 25,000 | 90  | 5.2          | 2.5          | Y        | Y   | GU24 | 12       |
| L100A21D2527KCQ                          | A21 100W 27K DIM CQ         | 17      | 100               | 1600         | OMNI       | 2700K | 25,000 | 90  | 5.2          | 2.8          | Y        | Y   | E26  | 12       |
| L100A21D2530KCQ                          | A21 100W 30K DIM CQ         | 17      | 100               | 1625         | OMNI       | 3000K | 25,000 | 90  | 5.2          | 2.8          | Y        | Y   | E26  | 12       |
| L100A21D2535KCQ                          | A21 100W 35K DIM CQ         | 17      | 100               | 1625         | OMNI       | 3500K | 25,000 | 90  | 5.2          | 2.8          | Y        | Y   | E26  | 12       |
| L100A21D2541KCQ                          | A21 100W 41K DIM CQ         | 17      | N/A               | 1675         | OMNI       | 4100K | 25,000 | 90  | 5.2          | 2.8          | Y        | N/A | E26  | 12       |
| L100A21D2550KCQ                          | A21 100W 50K DIM CQ         | 17      | N/A               | 1675         | OMNI       | 5000K | 25,000 | 90  | 5.2          | 2.8          | Y        | N/A | E26  | 12       |
| L100A213W2527KCQ                         | A21 3 WAY 100/60/40W 27K CQ | 17/10/6 | 100/60/40         | 1650/800/450 | OMNI       | 2700K | 25,000 | 90  | 5.2          | 2.8          | Y        | N/A | E26  | 12       |
| L100A213W2530KCQ                         | A21 3 WAY 100/60/40W 30K CQ | 17/10/6 | 100/60/40         | 1650/800/450 | OMNI       | 3000K | 25,000 | 90  | 5.2          | 2.8          | Y        | N/A | E26  | 12       |
| L100A213W2541KCQ                         | A21 3 WAY 100/60/40W 41K CQ | 17/10/6 | N/A               | 1700/800/450 | OMNI       | 4100K | 25,000 | 90  | 5.2          | 2.8          | Y        | N/A | E26  | 12       |
| L100A213W2550KCQ                         | A21 3 WAY 100/60/40W 50K CQ | 17/10/6 | N/A               | 1700/800/450 | OMNI       | 5000K | 25,000 | 90  | 5.2          | 2.8          | Y        | N/A | E26  | 12       |





# California Quality LED Lamps

## Specifications

| ITEM #                                      | DESCRIPTION                   | WATTS | REPLACEMENT WATTS | LUMENS | BEAM ANGLE | CCT   | HOURS  | CRI | MOL (inches) | DIA (inches) | TITLE 20 | JA8 | BASE  | CASE QTY |
|---------------------------------------------|-------------------------------|-------|-------------------|--------|------------|-------|--------|-----|--------------|--------------|----------|-----|-------|----------|
| <b>BR Lamps – Dimmable • 25,000 Hours</b>   |                               |       |                   |        |            |       |        |     |              |              |          |     |       |          |
| L65BR30D2527KCQ                             | BR30 65W 27K DIM CQ           | 8     | 65                | 650    | 110°       | 2700K | 25,000 | 90  | 5.4          | 3.8          | Y        | Y   | E26   | 12       |
| L65BR30D2530KCQ                             | BR30 65W 30K DIM CQ           | 8     | 65                | 650    | 110°       | 3000K | 25,000 | 90  | 5.4          | 3.8          | Y        | Y   | E26   | 12       |
| L65BR30D2541KCQ                             | BR30 65W 41K DIM CQ           | 8     | N/A               | 650    | 110°       | 4100K | 25,000 | 90  | 5.4          | 3.8          | Y        | N/A | E26   | 12       |
| L65BR30D2550KCQ                             | BR30 65W 50K DIM CQ           | 8     | N/A               | 700    | 110°       | 5000K | 25,000 | 90  | 5.4          | 3.8          | Y        | N/A | E26   | 12       |
| L100BR30D2527KCQ                            | BR30 100W 27K DIM CQ          | 16    | 100               | 1500   | 110°       | 2700K | 25,000 | 90  | 5.4          | 3.8          | Y        | Y   | E26   | 12       |
| L100BR30D2530KCQ                            | BR30 100W 30K DIM CQ          | 16    | 100               | 1550   | 110°       | 3000K | 25,000 | 90  | 5.4          | 3.8          | Y        | Y   | E26   | 12       |
| L100BR30D2541KCQ                            | BR30 100W 41K DIM CQ          | 16    | N/A               | 1600   | 110°       | 4100K | 25,000 | 90  | 5.4          | 3.8          | Y        | N/A | E26   | 12       |
| L100BR30D2550KCQ                            | BR30 100W 50K DIM CQ          | 16    | N/A               | 1600   | 110°       | 5000K | 25,000 | 90  | 5.4          | 3.8          | Y        | N/A | E26   | 12       |
| L85BR40D2527KCQ                             | BR40 85W 27K DIM CQ           | 13.5  | 85                | 1065   | 110°       | 2700K | 25,000 | 90  | 6.1          | 5.0          | Y        | Y   | E26   | 12       |
| L85BR40D2530KCQ                             | BR40 85W 30K DIM CQ           | 13.5  | 85                | 1065   | 110°       | 3000K | 25,000 | 90  | 6.1          | 5.0          | Y        | Y   | E26   | 12       |
| L85BR40D2541KCQ                             | BR40 85W 41K DIM CQ           | 13.5  | N/A               | 1065   | 110°       | 4100K | 25,000 | 90  | 6.1          | 5.0          | Y        | N/A | E26   | 12       |
| L85BR40D2550KCQ                             | BR40 85W 50K DIM CQ           | 13.5  | N/A               | 1065   | 110°       | 5000K | 25,000 | 90  | 6.1          | 5.0          | Y        | N/A | E26   | 12       |
| <b>R20 Lamps – Dimmable • 25,000 Hours</b>  |                               |       |                   |        |            |       |        |     |              |              |          |     |       |          |
| L50R20D2527KCQ                              | R20 50W 27K DIM CQ            | 7     | 50                | 525    | 110°       | 2700K | 25,000 | 90  | 3.8          | 2.5          | Y        | Y   | E26   | 12       |
| L50R20D2530KCQ                              | R20 50W 30K DIM CQ            | 7     | 50                | 525    | 110°       | 3000K | 25,000 | 90  | 3.8          | 2.5          | Y        | Y   | E26   | 12       |
| <b>MR16 Lamps – Dimmable • 25,000 Hours</b> |                               |       |                   |        |            |       |        |     |              |              |          |     |       |          |
| L50MR16GUD2527KFLCQ                         | MR16 50W 27K GU10 DIM 40° CQ  | 7     | 50                | 500    | 40°        | 2700K | 25,000 | 90  | 2.3          | 2.0          | Y        | N   | GU10  | 12       |
| L50MR16GUD2530KFLCQ                         | MR16 50W 30K GU10 DIM 40° CQ  | 7     | 50                | 500    | 40°        | 3000K | 25,000 | 90  | 2.3          | 2.0          | Y        | N   | GU10  | 12       |
| L50MR16D2527KFLCQ*                          | MR16 50W 27K GU5.3 DIM 40° CQ | 6.5   | 50                | 430    | 40°        | 2700K | 25,000 | 90  | 2.3          | 2.0          | Y        | N   | GU5.3 | 12       |
| L50MR16D2530KFLCQ*                          | MR16 50W 27K GU5.3 DIM 40° CQ | 6.5   | 50                | 470    | 40°        | 3000K | 25,000 | 90  | 2.3          | 2.0          | Y        | N   | GU5.3 | 12       |

\*Voltage.....12V





# California Quality LED Lamps

## Specifications

| ITEM #                                     | DESCRIPTION               | WATTS | REPLACEMENT WATTS | LUMENS | BEAM ANGLE | COLOR | HOURS  | CRI | MOL (inches) | DIA (inches) | TITLE 20 | JA8 | BASE | CASE QTY |
|--------------------------------------------|---------------------------|-------|-------------------|--------|------------|-------|--------|-----|--------------|--------------|----------|-----|------|----------|
| <b>PAR Lamps – Dimmable • 25,000 Hours</b> |                           |       |                   |        |            |       |        |     |              |              |          |     |      |          |
| L90P38D2527KFLCQ                           | PAR38 90W 27K DIM 40° CQ  | 13    | 90                | 950    | 40°        | 2700K | 25,000 | 90  | 5.3          | 4.8          | Y        | Y   | E26  | 12       |
| L90P38D2530KFLCQ                           | PAR38 90W 30K DIM 40° CQ  | 13    | 90                | 1000   | 40°        | 3000K | 25,000 | 90  | 5.3          | 4.8          | Y        | Y   | E26  | 12       |
| L90P38D2527KNFLCQ                          | PAR38 90W 27K DIM 25° CQ  | 13    | 90                | 950    | 25°        | 2700K | 25,000 | 90  | 5.3          | 4.8          | Y        | Y   | E26  | 12       |
| L90P38D2530KNFLCQ                          | PAR38 90W 30K DIM 25° CQ  | 13    | 90                | 1000   | 25°        | 3000K | 25,000 | 90  | 5.3          | 4.8          | Y        | Y   | E26  | 12       |
| L75P30D2527KNFLCQ                          | P30 75W 27K DIM 25° CQ    | 10    | 75                | 750    | 25°        | 2700K | 25,000 | 90  | 4.6          | 3.8          | Y        | Y   | E26  | 12       |
| L75P30D2530KNFLCQ                          | P30 75W 30K DIM 25° CQ    | 10    | 75                | 750    | 25°        | 3000K | 25,000 | 90  | 4.6          | 3.8          | Y        | Y   | E26  | 12       |
| L75P30D2535KNFLCQ                          | P30 75W 35K DIM 25° CQ    | 10    | 75                | 750    | 25°        | 3500K | 25,000 | 90  | 4.6          | 3.8          | Y        | Y   | E26  | 12       |
| L75P30D2527KFLCQ                           | P30 75W 27K DIM 40° CQ    | 10    | 75                | 750    | 40°        | 2700K | 25,000 | 90  | 4.6          | 3.8          | Y        | Y   | E26  | 12       |
| L75P30D2530KFLCQ                           | P30 75W 30K DIM 40° CQ    | 10    | 75                | 750    | 40°        | 3000K | 25,000 | 90  | 4.6          | 3.8          | Y        | Y   | E26  | 12       |
| L75P30D2535KFLCQ                           | P30 75W 35K DIM 40° CQ    | 10    | 75                | 750    | 40°        | 3500K | 25,000 | 90  | 4.6          | 3.8          | Y        | Y   | E26  | 12       |
| L75P30SD2527KNFLCQ                         | P30 75W SN 27K DIM 25° CQ | 9.5   | 75                | 750    | 25°        | 2700K | 25,000 | 90  | 3.8          | 3.6          | Y        | Y   | E26  | 12       |
| L75P30SD2530KNFLCQ                         | P30 75W SN 30K DIM 25° CQ | 9.5   | 75                | 750    | 25°        | 3000K | 25,000 | 90  | 3.8          | 3.6          | Y        | Y   | E26  | 12       |
| L75P30SD2527KFLCQ                          | P30 75W SN 27K DIM 40° CQ | 9.5   | 75                | 750    | 40°        | 2700K | 25,000 | 90  | 3.8          | 3.6          | Y        | Y   | E26  | 12       |
| L75P30SD2530KFLCQ                          | P30 75W SN 30K DIM 40° CQ | 9.5   | 75                | 750    | 40°        | 3000K | 25,000 | 90  | 3.8          | 3.6          | Y        | Y   | E26  | 12       |
| L50P20D2527KNFLCQ                          | P20 50W 27K DIM 25° CQ    | 7     | 50                | 550    | 25°        | 2700K | 25,000 | 90  | 3.5          | 2.5          | Y        | Y   | E26  | 12       |
| L50P20D2530KNFLCQ                          | P20 50W 30K DIM 25° CQ    | 7     | 50                | 550    | 25°        | 3000K | 25,000 | 90  | 3.5          | 2.5          | Y        | Y   | E26  | 12       |
| L50P20D2527KFLCQ                           | P20 50W 27K DIM 40° CQ    | 7     | 50                | 600    | 40°        | 2700K | 25,000 | 90  | 3.5          | 2.5          | Y        | Y   | E26  | 12       |
| L50P20D2530KFLCQ                           | P20 50W 30K DIM 40° CQ    | 7     | 50                | 600    | 40°        | 3000K | 25,000 | 90  | 3.5          | 2.5          | Y        | Y   | E26  | 12       |
| L50P16D2527KFLCQ                           | P16 50W 27K DIM 40° CQ    | 7     | 50                | 500    | 40°        | 2700K | 25,000 | 90  | 3.5          | 2.0          | Y        | Y   | E26  | 12       |
| L50P16D2530KFLCQ                           | P16 50W 30K DIM 40° CQ    | 7     | 50                | 500    | 40°        | 3000K | 25,000 | 90  | 3.5          | 2.0          | Y        | Y   | E26  | 12       |





# California Quality LED Lamps

## Specifications

| ITEM #                                                      | DESCRIPTION                     | WATTS | REPLACEMENT WATTS | LUMENS | BEAM ANGLE | COLOR | HOURS  | CRI | MOL (inches) | DIA (inches) | TITLE 20 | JA8 | BASE | CASE QTY |
|-------------------------------------------------------------|---------------------------------|-------|-------------------|--------|------------|-------|--------|-----|--------------|--------------|----------|-----|------|----------|
| <b>Downlights – Dimmable • 35,000 Hours</b>                 |                                 |       |                   |        |            |       |        |     |              |              |          |     |      |          |
| L75DR4D3527KCQ                                              | Downlight 4" 27K DIM CQ         | 9.5   | 75                | 750    | 110°       | 2700K | 35,000 | 90  | 3.0          | 5.0          | Y        | Y   | E26  | 12       |
| L75DR4D3530KCQ                                              | Downlight 4" 30K DIM CQ         | 9.5   | 75                | 750    | 110°       | 3000K | 35,000 | 90  | 3.0          | 5.0          | Y        | Y   | E26  | 12       |
| L75DR4D3541KCQ                                              | Downlight 4" 41K DIM CQ         | 9.5   | N/A               | 750    | 110°       | 4100K | 35,000 | 90  | 3.0          | 5.0          | Y        | N/A | E26  | 12       |
| <b>Downlights – Dimmable • 35,000 Hours • PHASING OUT •</b> |                                 |       |                   |        |            |       |        |     |              |              |          |     |      |          |
| L85DR5D3541KCQ                                              | Downlight 5/6" 41K DIM CQ       | 10.5  | N/A               | 850    | 110°       | 4100K | 35,000 | 90  | 3.0          | 7.5          | Y        | N/A | E26  | 6        |
| <b>Filament Lamps – Dimmable • 15,000 Hours</b>             |                                 |       |                   |        |            |       |        |     |              |              |          |     |      |          |
| LFF60A19D1527KCQ                                            | LED 9W GLASS A19 DIM 27K CQ     | 9     | 60                | 810    | OMNI       | 2700K | 15,000 | 90  | 4.3          | 2.4          | Y        | N   | E26  | 12       |
| LFF60A19D1530KCQ                                            | LED 9W GLASS A19 DIM 30K CQ     | 9     | 60                | 810    | OMNI       | 3000K | 15,000 | 90  | 4.3          | 2.4          | Y        | N   | E26  | 12       |
| FB11D4027ECCQ                                               | LED FIL 4.5W B11 CL E12 27K CQ  | 4.5   | 40                | 350    | 360°       | 2700K | 15,000 | 90  | 3.8          | 1.4          | Y        | N   | E12  | 12       |
| FG16D4027EFCQ                                               | LED FIL 4.5W G16 FR E12 27K CQ  | 4.5   | 40                | 360    | 360°       | 2700K | 15,000 | 90  | 3.4          | 2.0          | Y        | N   | E12  | 12       |
| FG16D4027ECCQ                                               | LED FIL 4.5W G16 CL E12 27K CQ  | 4.5   | 40                | 360    | 360°       | 2700K | 15,000 | 90  | 3.4          | 2.0          | Y        | N   | E12  | 12       |
| FG25D4027FCQ                                                | LED FIL 4.5W G25 FR E26 27K CQ  | 4.5   | 40                | 350    | 360°       | 2700K | 15,000 | 90  | 4.5          | 3.2          | Y        | N   | E26  | 12       |
| FG25D4027CCQ                                                | LED FIL 4.5W G25 CL E26 27K CQ  | 4.5   | 40                | 350    | 360°       | 2700K | 15,000 | 90  | 4.5          | 3.2          | Y        | N   | E26  | 12       |
| FT1005D4027CCQ                                              | LED FIL 5W T10 CL E26 27K CQ    | 5     | 40                | 450    | 360°       | 2700K | 15,000 | 90  | 5.3          | 1.2          | Y        | N   | E26  | 12       |
| FST19D4027CCQ                                               | LED FIL 4.2W ST19 CL E26 27K CQ | 4.2   | 40                | 340    | 360°       | 2700K | 15,000 | 90  | 5.4          | 2.5          | Y        | N   | E26  | 12       |





## Dimmer Compatibility

| E26 SUGGESTED DIMMER COMPATIBILITY |                |
|------------------------------------|----------------|
| MANUFACTURER                       | MODEL NUMBER   |
| Leviton                            | R50-IPLO6-10M  |
|                                    | R61-06674-POI  |
| Lutron                             | CTCL-153PDH-WH |
|                                    | TGCL-153PH-WH  |
|                                    | DVVCL-153PH-WH |

| MR16 SUGGESTED DIMMER COMPATIBILITY |                          |
|-------------------------------------|--------------------------|
| MANUFACTURER                        | MODEL NUMBER             |
| Leviton                             | Sureslide 6615P          |
| Lutron                              | Diva DVLV-600P           |
|                                     | Divs DVELV-300P          |
|                                     | Skylark SLEV-300P        |
|                                     | Skylark SLV-600P         |
|                                     | Nova NELV-450            |
|                                     | Nova NTELV-600           |
|                                     | MALV-600                 |
|                                     | VERTI VTELV-600M         |
| Cooper                              | DAL06P - All load dimmer |
|                                     | SAL06P                   |



# TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit [tcpi.com](http://tcpi.com)

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516