

Features & Benefits

- Internal Driver
- Smooth, Consistent Light
- UL for Safety
- No UV, No Mercury
- Long Life
- High CRI
- Instant on, no delay or warm up time
- Convenient and quick installation
- Utilizes R17d sockets
- Compatible with controls and sensors
- Works in cold temperature applications
- Suitable for damp and dry locations
- Glass tube for superior optical performance
- -20° F to 130° F ambient operating temperature
- 5 Year Warranty



Commercial Grade **LED T8 Lamp**
Double End Input



Flex™
Internal Driver **LED Lamp**

Specification Data

Model No.	Length	Base type	Lamp Wattage	Input Voltage	CCT	Initial Lumens	CRI	Beam Angle	LPW	Power Factor	THD	Life (h)	DLC
L72T8HO/830/18G-ID DE	72	R17d	18	120-277	3000K	2700	82	325	150	0.9	<20%	50000	No
L72T8HO/835/18G-ID DE	72	R17d	18	120-277	3500K	2700	82	325	150	0.9	<20%	50000	No
L72T8HO/840/18G-ID DE	72	R17d	18	120-277	4000K	2700	82	325	150	0.9	<20%	50000	No
L72T8HO/850/18G-ID DE	72	R17d	18	120-277	5000K	2700	82	325	150	0.9	<20%	50000	No

Ordering Information

EXAMPLE: **L48T8/840/14G-ID DE**

L

Manufacturer's Code

48

Normal Length
48=48"

T8

Lamp Shape
T8=T8

8

CRI
8=>80

40

CCT
50 =5000K
40 =4000K
35 =3500K

14 G

Wattage
14G=14W

-


ID

Internal Driver

DE

Double End Input

Wiring diagram



Espen Technology, Inc. | 12257 Florence Avenue | Santa Fe Springs, CA 90670 | Phone: (562) 529-2938 | Fax: (562) 529-2978
Toll-free: (866) 933-7736 | Email: info@espentech.com | www.espentech.com