



Elite Series LED 7W P20 Floodlights



TCP's award winning PAR lamps combine traditional beauty with top-notch technology. With the wide variety of options available, you can be sure to find PAR lamps to meet your needs.

Reasons to choose the Elite Series LED 7W P20 from TCP

- Provides designer-grade light quality with the same look as halogen
- Perfect for sensitive display lighting such as art galleries
- Enhances colors of focal point while maintaining uniformity throughout the lighting installation
- Track and downlight installations are not strained by excess weight
- Suitable for wet locations—when exposed to water use only with device base up
- Seamlessly blends into lighting applications

Ideal Applications

- Retail
- Display lights
- Track lighting
- Outdoor settings

Specifications

Voltage	120V	CRI	80
Input Line Frequency	50/60Hz	Beam Angle	40°, 25°, 15°
Lamp Life (Rated)	25,000	Base	E26
Minimum Starting Temp	(-30°C)/-22°F	Warranty	5 Years
Maximum Operating Temp	(45°C)/113°F	Suitable for use in totally enclosed fixtures	

Specifications



PAR20****KSP
15° Spot Flood



PAR20****KNFL
25° Narrow Flood



PAR20****KFL
40° Flood

ITEM #	DESCRIPTION	ENERGY STAR	WATTS	LUMENS	LPW	REPLACEMENT WATTS	CCT	CRI	BEAM ANGLE
7W P20 Lamps – Dimmable • 25,000 Hours									
L7P20D2524KFL	LED 7W P20 DIM 24KFL		7W	550	78.6	50W	2400K	80	40°
L7P20D2524KNFL	LED 7W P20 DIM 24KNFL		7W	550	78.6	50W	2400K	80	25°
L7P20D2527KFL	LED 7W P20 DIM 27KFL	★	7W	600	85.7	50W	2700K	80	40°
L7P20D2527KFLB	LED 7W P20 DIM 27KFL BLK	★	7W	600	85.7	50W	2700K	80	40°
L7P20D2527KNFL	LED 7W P20 DIM 27KNFL	★	7W	600	85.7	50W	2700K	80	25°
L7P20D2527KNFLB	LED 7W P20 DIM 27KNFL BLK	★	7W	600	85.7	50W	2700K	80	25°
L7P20D2527KSP	LED 7W P20 DIM 27SP	★	7W	600	85.7	50W	2700K	80	15°
L7P20D2530KFL	LED 7W P20 DIM 30KFL	★	7W	625	89.3	50W	3000K	80	40°
L7P20D2530KFLB	LED 7W P20 DIM 30KFL BLK	★	7W	625	89.3	50W	3000K	80	40°
L7P20D2530KNFL	LED 7W P20 DIM 30KNFL	★	7W	625	89.3	50W	3000K	80	25°
L7P20D2530KNFLB	LED 7W P20 DIM 30KNFL BLK	★	7W	625	89.3	50W	3000K	80	25°
L7P20D2530KSP	LED 7W P20 DIM 30KSP	★	7W	625	89.3	50W	3000K	80	15°
L7P20D2535KFL	LED 7W P20 DIM 35KFL		7W	675	96.4	50W	3500K	80	40°
L7P20D2535KNFL	LED 7W P20 DIM 35KNFL		7W	675	96.4	50W	3500K	80	25°
L7P20D2541KFL	LED 7W P20 DIM 41KFL	★	7W	675	96.4	50W	4100K	80	40°
L7P20D2541KFLB	LED 7W P20 DIM 41KFL BLK	★	7W	675	96.4	50W	4100K	80	40°
L7P20D2541KNFL	LED 7W P20 DIM 41KNFL	★	7W	675	96.4	50W	4100K	80	25°
L7P20D2541KNFLB	LED 7W P20 DIM 41KNFL BLK	★	7W	675	96.4	50W	4100K	80	25°
L7P20D2541KSP	LED 7W P20 DIM 41KSP	★	7W	675	96.4	50W	4100K	80	15°
L7P20D2550KFL	LED 7W P20 DIM 50KFL	★	7W	700	100.0	50W	5000K	80	40°
L7P20D2550KFLB	LED 7W P20 DIM 50KFL BLK	★	7W	700	100.0	50W	5000K	80	40°
L7P20D2550KNFL	LED 7W P20 DIM 50KNFL	★	7W	700	100.0	50W	5000K	80	25°
L7P20D2550KSP	LED 7W P20 DIM 50KSP	★	7W	700	100.0	50W	5000K	80	15°

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcpi.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516