

LED PAR Lamps

ITEM #	DESCRIPTION	VOLTAGE	WATTS	WATT EQUIV.	LUMENS	LPW	CBCP	BEAM ANGLE	CCT	CRI	CASE QTY.
10W Elite PAR30 Short Neck – Dimmable • E26 Base • 25,000 Rated Life (continued)											
LED12P30SD30KFL	10W PAR30 SHORT NECK - 30K 40°	120V	10	75	850	85	1858	40	3000K	80	12
LED12P30SD30KFLB	10W PAR30 SHORT NECK - 30K 40° BLK	120V	10	75	850	85	1858	40	3000K	80	12
LED12P30SD30KNFL	10W PAR30 SHORT NECK - 30K 25°	120V	10	75	850	85	4968	25	3000K	80	12
LED12P30SD30KNFLB	10W PAR30 SHORT NECK - 30K 25° BLK	120V	10	75	850	85	4968	25	3000K	80	12
LED12P30SD30KSP	10W PAR30 SHORT NECK - 30K 15°	120V	10	75	850	85	8380	15	3000K	80	12
LED12P30SD30KSPB	10W PAR30 SHORT NECK - 30K 15° BLK	120V	10	75	850	85	8380	15	3000K	80	12
LED12P30SD35KFL	10W PAR30 SHORT NECK - 35K 40°	120V	10	75	850	85	2232	40	3500K	80	12
LED12P30SD35KFLB	10W PAR30 SHORT NECK - 35K 40° BLK	120V	10	75	850	85	2232	40	3500K	80	12
LED12P30SD35KNFL	10W PAR30 SHORT NECK - 35K 25°	120V	10	75	850	85	4402	25	3500K	80	12
LED12P30SD35KNFLB	10W PAR30 SHORT NECK - 35K 25° BLK	120V	10	75	850	85	4402	25	3500K	80	12
LED12P30SD35KSP	10W PAR30 SHORT NECK - 35K 15°	120V	10	75	850	85	8380	15	3500K	80	12
LED12P30SD41KFL	10W PAR30 SHORT NECK - 41K 40°	120V	10	75	850	85	2247	40	4100K	80	12
LED12P30SD41KFLB	10W PAR30 SHORT NECK - 41K 40° BLK	120V	10	75	850	85	2247	40	4100K	80	12
LED12P30SD41KNFL	10W PAR30 SHORT NECK - 41K 25°	120V	10	75	850	85	4895	25	4100K	80	12
LED12P30SD41KNFLB	10W PAR30 SHORT NECK - 41K 25° BLK	120V	10	75	850	85	4895	25	4100K	80	12
LED12P30SD41KSP	10W PAR30 SHORT NECK - 41K 15°	120V	10	75	850	85	8710	15	4100K	80	12
LED12P30SD50KFL	10W PAR30 SHORT NECK - 50K 40°	120V	10	75	850	85	2454	40	5000K	80	12
LED12P30SD50KNFL	10W PAR30 SHORT NECK - 50K 25°	120V	10	75	850	85	5260	25	5000K	80	12
LED12P30SD50KSP	10W PAR30 SHORT NECK - 50K 15°	120V	10	75	850	85	9292	15	5000K	80	12

ITEM #	DESCRIPTION	VOLTAGE	WATTS	WATT EQUIV.	LUMENS	LPW	CBCP	BEAM ANGLE	CCT	CRI	CASE QTY.
7W Elite PAR20 – Dimmable • E26 Base • 25,000 Rated Life											
L7P20D2524KFL	7W PAR20 - 24K 40°	120V	7	50	550	78.6	1058	40	2400K	80	12
L7P20D2524KNFL	7W PAR20 - 24K 25°	120V	7	50	550	78.6	1894	25	2400K	80	12
L7P20D2527KFL	7W PAR20 - 27K 40°	120V	7	50	600	85.7	1208	40	2700K	80	12
L7P20D2527KFLB	7W PAR20 - 27K 40° - BLACK	120V	7	50	600	85.7	1208	40	2700K	80	12
L7P20D2527KNFL	7W PAR20 - 27K 25°	120V	7	50	600	85.7	2030	25	2700K	80	12
L7P20D2527KSP	7W PAR20 - 27K 15°	120V	7	50	600	85.7	4898	15	2700K	80	12
L7P20D2530KFL	7W PAR20 - 30K 40°	120V	7	50	625	89.3	1187	40	3000K	80	12
L7P20D2530KFLB	7W PAR20 - 30K 40° - BLACK	120V	7	50	625	89.3	1187	40	3000K	80	12
L7P20D2530KNFL	7W PAR20 - 30K 25°	120V	7	50	625	89.3	2050	25	3000K	80	12
L7P20D2530KNFLB	7W PAR20 - 30K 25° - BLACK	120V	7	50	625	89.3	2050	25	3000K	80	12
L7P20D2530KSP	7W PAR20 - 30K 15°	120V	7	50	625	89.3	5391	15	3000K	80	12
L7P20D2535KFL	7W PAR20 - 35K 40°	120V	7	50	675	96.4	1187	40	3500K	80	12
L7P20D2535KNFL	7W PAR20 - 35K 25°	120V	7	50	675	96.4	2050	25	3500K	80	12
L7P20D2541KFL	7W PAR20 - 41K 40°	120V	7	50	675	96.4	1383	40	4100K	80	12
L7P20D2541KFLB	7W PAR20 - 41K 40° - BLACK	120V	7	50	675	96.4	1383	40	4100K	80	12
L7P20D2541KNFL	7W PAR20 - 41K 25°	120V	7	50	675	96.4	2174	25	4100K	80	12
L7P20D2541KNFLB	7W PAR20 - 41K 25° - BLACK	120V	7	50	675	96.4	2174	25	4100K	80	12
L7P20D2541KSP	7W PAR20 - 41K 15°	120V	7	50	675	96.4	5411	15	4100K	80	12
L7P20D2550KFL	7W PAR20 - 50K 40°	120V	7	50	700	100	1330	40	5000K	80	12
L7P20D2550KFLB	7W PAR20 - 50K 40° - BLACK	120V	7	50	700	100	1330	40	5000K	80	12
L7P20D2550KNFL	7W PAR20 - 50K 25°	120V	7	50	700	100	2172	25	5000K	80	12
L7P20D2550KSP	7W PAR20 - 50K 15°	120V	7	50	700	100	5599	15	5000K	80	12

For the most up-to-date specs and warranty information, please visit www.tcpi.com

Black housing options are often available. Add "B" to the end of the item number.



RoHS
COMPLIANT

5 YEAR
WARRANTY
*Based on 12 hours use per day

I13