



Starlight LED Lamps

Product Specifications



Shine as bright as a star with our new LED Starlight series. The sleek, modern shape can be used in a wide variety of applications—from pendants to sockets and everywhere in between.

Reasons to choose the Starlight LED Lamp from TCP

- Sleek, low profile design provides a unique shape for limitless applications
- Smooth warm dimming creates the perfect atmosphere
- 110° beam angle
- Up to 85% more efficient than incandescent/halogen replacements
- Long 30,000 hours life minimizes replacement and maintenance costs
- UL approved for damp locations means the lamp can be used outdoors when protected from the elements
- Pendant and socket extender accessories available
- Socket extender allows for installation in an existing recessed can

Ideal Applications

- Commercial
- Industrial
- Retail
- Residential

Specifications

Color Temperatures 3000K; 4000K; 5000K;
..... 3000K to 1800K
Input Line Voltage 120V
Input Line Frequency 50/60HZ

Lamp Life (Rated) 30,000 hours
Minimum Starting Temp -22F/-30C
Maximum Operating Temp 45°C
CRI 80

Specifications



SL13



SL16



SL19



SL22

ITEM #	DESCRIPTION	VOLTAGE	LED WATTS	WATTAGE EQUIVALENT	LUMENS	LPW	CRI	COLOR TEMP	BEAM ANGLE	MOL (inches)	DIA (inches)	BASE
LED SL13 Starlight 65W Equivalent – 9W LED • 30,000 hours												
L9SL13D3030K	LED STARLIGHT DIM 9W 30K	120V	9	65	950	105.56	80	3000K	110°	3.8	5.2	E26
L9SL13D3040K	LED STARLIGHT DIM 9W 40K	120V	9	65	1000	111.11	80	4000K	110°	3.8	5.2	E26
L9SL13D3050K	LED STARLIGHT DIM 9W 50K	120V	9	65	1000	111.11	80	5000K	110°	3.8	5.2	E26
LED SL16 Starlight 100W Equivalent – 15W LED • 30,000 hours												
L15SL16D3030K	LED STARLIGHT DIM 15W 30K	120V	15	100	1625	108.33	80	3000K	110°	3.8	6.3	E26
L15SL16D3040K	LED STARLIGHT DIM 15W 40K	120V	15	100	1700	113.33	80	4000K	110°	3.8	6.3	E26
L15SL16D3050K	LED STARLIGHT DIM 15W 50K	120V	15	100	1750	116.67	80	5000K	110°	3.8	6.3	E26
L15SL16D30A	LED ALLUSION 15W WARM-DIMMING	120V	13	100	1200	116.67	80	3000K to 2000K	110°	3.8	6.3	E26
LED SL19 Starlight 140W Equivalent – 19W LED • 30,000 hours												
L19SL19D3030K	LED STARLIGHT DIM 19W 30K	120V	19	140	2100	110.53	80	3000K	110°	4.5	7.75	E26
L19SL19D3040K	LED STARLIGHT DIM 19W 40K	120V	19	140	2250	118.42	80	4000K	110°	4.5	7.75	E26
L19SL19D3050K	LED STARLIGHT DIM 19W 50K	120V	19	140	2250	118.42	80	5000K	110°	4.5	7.75	E26
LED SL22 Starlight 160W Equivalent – 22W LED • 30,000 hours												
L22SL22D3030K	LED STARLIGHT DIM 22W 30K	120V	22	160	2350	106.82	80	3000K	110°	4.8	8.9	E26
L22SL22D3040K	LED STARLIGHT DIM 22W 40K	120V	22	160	2450	111.36	80	4000K	110°	4.8	8.9	E26
L22SL22D3050K	LED STARLIGHT DIM 22W 50K	120V	22	160	2450	111.36	80	5000K	110°	4.8	8.9	E26
LED SL122 Starlight 200W Equivalent – 25W LED • 30,000 hours												
L25SL22HD3030K	LED STARLIGHT DIM 25W 30K HL	120V	25	200	3100	124.00	80	3000K	110°	4.8	8.9	E26

Specifications

All 30K Starlights are available in Black, Red, Green, and Blue except L25SL22HD3030K & L15SL16D30A.

Just add the following to the end of the part number:

Add "B" for Black

Add "RED" for Red

Add "GRN" for Green

Add "BLU" for Blue

*Colors in 40K and 50K versions available via special order



Matching Pendant Mounts are also available:

- 6' adjustable length mounts directly to junction box

555PMWHT Pendant Mount White

555PMB Pendant Mount Black

555PMRED Pendant Mount Red

555PMGRN Pendant Mount Green

555PMBLU Pendant Mount Blue

SLEXTEND Starlight Extender



Dimmer Compatibility

SUGGESTED DIMMER COMPATIBILITY	
MANUFACTURER	MODEL NUMBER
Leviton	R50-IPLO6-10M
	R61-06674-POI
Lutron	CTCL-153PDH-WH
	TGCL-153PH-WH
	DVVCL-153PH-WH

Note: E26 compatible dimmer

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcpi.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516