



GE
Lighting

43125 - Integrated U6 LED Plastic Tubes

LED13ET8/U6/835

- ☞ Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall.
- ☞ LED tubes are ideal for those seeking high energy savings with minimal installation time.
- ☞ Each LED tube is outfitted with an internal GE driver.
- ☞ GE integrated LED tubes run on electronic T8 instant-start or programmed start ballasts.
- ☞ Shatter resistant
- ☞ No UV
- ☞ Easy disposal, non-hazardous waste
- ☞ UL Listed

Product Photo



CAUTIONS & WARNINGS

Caution

Risk of Electric Shock

Suitable for damp locations

Not intended for use with emergency exit fixtures or emergency exit lights

GENERAL CHARACTERISTICS

Dimmable	Yes
Product Technology	LED
Rated Life (Hours)	50000 h
Dimmable / Non-Dimmable	Yes
LED Tube Type	Plastic
Lamp Count	1
Life in Years	45.7 yr
Requested Structure	Carton
Estimated Energy Cost per Year	1.57
Base	G13
Bulb Shape	T8-U6

PHOTOMETRIC CHARACTERISTICS

Initial Lumens-nominal	1850 lm
Color Rendering Index-CRI	80
Color Temperature	3500 K

PRODUCT INFORMATION

Product Code	43125
Description	LED13ET8/U6/835
Alternative Unit Of Measure	CASE
Standard Package Quantity	12
Ean UPC	043168431255
Standard Package GTIN	10043168431252
No Of Items Per Sales Unit	
No Of Items Per Standard Package	12
Sales Unit	Case
UCC	
Alternative Unit Of Measure	EACH
Standard Package Quantity	12
Ean UPC	043168431255
Standard Package GTIN	00043168431255
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
Sales Unit	Each
UCC	

DIMENSIONS

Bulb Max Overall Length-MOL	22.5 in
-----------------------------	---------

ELECTRICAL CHARACTERISTICS

Rated power (Watts)	13 W
---------------------	------