

# Refit solutions from GE



## Type C LED Tubes – T5 Glass

### DESCRIPTION

Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall. LED tubes are ideal for those seeking high energy savings with minimal installation time. Each LED tube is operated by a GE Lightech™ driver. See reverse for LED tubes and Lightech driver product details.

### FEATURES

- T5 glass tube
- 1800-4500 lumen options available
- > 270 degree beam spread
- > 120 total system lumens per watt (LPW)
- 3000K, 3500K, 4000K, 5000K and 6500K color temperature
- 50,000-hour rated life
- 5 year warranty
- UL and CUL-approved technologies
  - in compliance with UL 1598 certification

### BENEFITS

- Fast and Easy LED upgrade
- Low energy LFL replacement
- 66% longer life than LFL (50,000 vs. 30,000 hours)
- Better quality of light –instant on
- Fully illuminates fixture - 270° light distribution
- Easy disposal, non-hazardous waste

ecomagination<sup>SM</sup>

To learn more about saving money and energy, go to: [gelighting.com/ThinkLED](http://gelighting.com/ThinkLED)

When you Think LED lighting, Think GE.



imagination at work

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

## Product Specifications

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (in)	Lumens Initial	Initial Color Temp	CRI	*Rated Life L70 (Hrs)	DLC	UL	#Location Rating	Additional Information
<b>Remote LED Glass T5 2ft Tubes (Operates on Remote Driver)</b>															
	G5	13	76150	LED15T5/G/2/830	20	22	1800	3000K	80+	50,000	-	Yes	Damp	Requires Driver	
	G5	13	76164	LED15T5/G/2/835	20	22	1850	3500K	80+	50,000	-	Yes	Damp	Requires Driver	
	G5	13	76129	LED15T5/G/2/840	20	22	1900	4000K	80+	50,000	-	Yes	Damp	Requires Driver	
	G5	13	76167	LED15T5/G/2/850	20	22	1900	5000K	80+	50,000	-	Yes	Damp	Requires Driver	
	G5	13	76192	LED15T5/G/2/865	20	22	1900	6500K	80+	50,000	-	Yes	Damp	Requires Driver	
<b>Remote LED Glass T5 4ft HO Tubes (Operates on Remote Driver)</b>															
	G5	31	91973	LED36T5/G/4/830	20	46	4100	3000K	80+	50,000	-	Yes	Damp	Requires Driver	
	G5	31	91976	LED36T5/G/4/835	20	46	4200	3500K	80+	50,000	-	Yes	Damp	Requires Driver	
	G5	31	91977	LED36T5/G/4/840	20	46	4400	4000K	80+	50,000	-	Yes	Damp	Requires Driver	
	G5	31	91997	LED36T5/G/4/850	20	46	4500	5000K	80+	50,000	-	Yes	Damp	Requires Driver	
	G5	31	92006	LED36T5/G/4/865	20	46	4400	6500K	80+	50,000	-	Yes	Damp	Requires Driver	

### Lightech Drivers - Non Dimming

GE Product Code	Description	# of Lamps
38970	LED15T8/DR/UN/2L	2

### Lightech Drivers - Dimming

GE Product Code	Description	# of Lamps
38975	LED15T8/DR/4DL	4
38974	LED15T8/DR/D2L	2
92013	LED36T/DR/4DL	4
63126	LED36T8/DR/D2L	2

### General Characteristics - Non Dimming

GE Product Code	38970
Output Current (A)	0.44*2
Input Watt Range (W)	30
Input Voltage (V)	120-277V
Input Frequency (Hz)	50/60Hz
Efficiency (%)	> .9%
Output Type	DC
Output Volt Range	27-33V
Dimmability	None
Ambient Temp Min	-4°F
Ambient Temp Max	104°F
Case Temperature	158°F

### General Characteristics - Dimming

GE Product Code	38974	63126	38975	92013
Output Current (A)	0.44*2	1.06*2	0.44*4	1.06*4
Input Watt Range (W)	30	72	60	144
Input Voltage (V)		120-277V		
Input Frequency (Hz)		50/60Hz		
Efficiency (%)		> .9%		
Output Type		DC		
Output Volt Range		27-33V		
Dimmability		0-10V		
Ambient Temp Min		-4°F		
Ambient Temp Max		104°F		
Case Temperature		158°F		

### Dimensions - Non Dimming

GE Product Code	38970
Weight	1.01
Casing Length (in)	9.5
Casing Width (in)	1.3
Casing Height (in)	1.25
Lead Exit Length (in)	26
Input Wire Length (in)	36
Output Wire Length (in)	38

### Dimensions - Dimming

GE Product Code	38974	63126	38975	92013
Weight	1.01	1.08	1.08	2.15
Casing Length (in)	9.5	9.5	9.5	16.75
Casing Width (in)	1.3	1.7	1.7	2.0
Casing Height (in)	1.25	1.25	1.25	1.25
Lead Exit Length (in)	26	26	26	26
Input Wire Length (in)	36	36	36	36
Output Wire Length (in)	42	42	42	42

ecomagination<sup>SM</sup>



Product is compliant with material restriction requirements of RoHS



www.gelighting.com

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2016 GE.

LEDL037 (Rev. 10/11/16)