

Refit Solutions from GE



Application illustration only, subject lamps not used in photo.

Type C LED Tubes - Glass - Improved Lumens

Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall. LED tubes are ideal for those seeking high energy savings with minimal installation time. Each LED tube is operated by a GE Lightech™ driver. See reverse for LED tubes and Lightech driver product details.

FEATURES

- 2'-4' glass tubes
- 1,050 -2,800 lumen options available
- > 270° beam spread
- > 105 total system lumens per watt (LPW)
- 3000K, 3500K, 4000K, 5000K and 6500K color temperature
- 50,000-hour rated life
- Open or enclosed fixtures
- 5 year warranty
- UL and CUL- approved technologies
 - in compliance with UL 1598 certification
- 2' and 4' DLC Listed

BENEFITS

- Fast and Easy LED upgrade
- Low energy LFL replacement
- 66% longer life than LFL (50,000 vs. 30,000 hours)
- Better quality of light
 - instant on
- Fully illuminates fixture
 - >320° light distribution
- Easy disposal, non-hazardous waste

To learn more about saving money and energy, go to: <http://products.currentbyge.com>.

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

Product Specifications

GE Product Code	Description	Bulb Shape	Base	Watts	Case Quantity	Length (in)	Initial Lumens	Color Temp (K°)	CRI	*Rated Life L70 (Hrs)	DLC
2ft LED Tube											
38933	LED9T8/G/2/830	T8	Med Bi-Pin (G13)	8	20	24"	1000	3000	80+	50,000	Yes
38935	LED9T8/G/2/835	T8	Med Bi-Pin (G13)	8	20	24"	1000	3500	80+	50,000	Yes
38936	LED9T8/G/2/840	T8	Med Bi-Pin (G13)	8	20	24"	1100	4000	80+	50,000	Yes
38939	LED9T8/G/2/850	T8	Med Bi-Pin (G13)	8	20	24"	1100	5000	80+	50,000	Yes
38943	LED9T8/G/2/865	T8	Med Bi-Pin (G13)	8	20	24"	1000	6500	80+	50,000	-
3ft LED Tube											
99687	LED15T8/G/3/830	T8	Med Bi-Pin (G13)	13	20	36"	1800	3000	80+	50,000	-
99688	LED15T8/G/3/835	T8	Med Bi-Pin (G13)	13	20	36"	1850	3500	80+	50,000	-
99689	LED15T8/G/3/840	T8	Med Bi-Pin (G13)	13	20	36"	1900	4000	80+	50,000	-
99691	LED15T8/G/3/850	T8	Med Bi-Pin (G13)	13	20	36"	1900	5000	80+	50,000	-
38257	LED18T8/G/3/830	T8	Med Bi-Pin (G13)	16	20	36"	1800	3000	80+	50,000	-
38258	LED18T8/G/3/835	T8	Med Bi-Pin (G13)	16	20	36"	1800	3500	80+	50,000	-
38260	LED18T8/G/3/840	T8	Med Bi-Pin (G13)	16	20	36"	1900	4000	80+	50,000	-
38261	LED18T8/G/3/850	T8	Med Bi-Pin (G13)	16	20	36"	1900	5000	80+	50,000	-
4ft LED Tube											
76194	LED12T8/G/4/830	T8	Med Bi-Pin (G13)	10	20	48"	1550	3000	80+	50,000	Yes
76264	LED12T8/G/4/835	T8	Med Bi-Pin (G13)	10	20	48"	1600	3500	80+	50,000	Yes
76265	LED12T8/G/4/840	T8	Med Bi-Pin (G13)	10	20	48"	1650	4000	80+	50,000	Yes
76271	LED12T8/G/4/850	T8	Med Bi-Pin (G13)	10	20	48"	1650	5000	80+	50,000	Yes
76278	LED12T8/G/4/865	T8	Med Bi-Pin (G13)	10	20	48"	1600	6500	80+	50,000	-
38944	LED15T8/G/4/830	T8	Med Bi-Pin (G13)	13	20	48"	1850	3000	80+	50,000	Yes
38945	LED15T8/G/4/835	T8	Med Bi-Pin (G13)	13	20	48"	1900	3500	80+	50,000	Yes
38950	LED15T8/G/4/840	T8	Med Bi-Pin (G13)	13	20	48"	1950	4000	80+	50,000	Yes
38951	LED15T8/G/4/850	T8	Med Bi-Pin (G13)	13	20	48"	2050	5000	80+	50,000	Yes
38952	LED15T8/G/4/865	T8	Med Bi-Pin (G13)	13	20	48"	1950	6500	80+	50,000	-
62428	LED21T8/G/4/835	T8	Med Bi-Pin (G13)	18	20	48"	2600	3500	80+	50,000	Yes
62485	LED21T8/G/4/840	T8	Med Bi-Pin (G13)	18	20	48"	2700	4000	80+	50,000	Yes
62487	LED21T8/G/4/850	T8	Med Bi-Pin (G13)	18	20	48"	2800	5000	80+	50,000	Yes

Lighttech Drivers - Non Dimming

GE Product Code	Description	# of Lamps
93100	LED9T8/DR/UN/2L	2
76289	LED12T8/DR/2L	2
38970	LED15T8/DR/UN/2L	2
82347	LED18T8/DR/UN/2L	2
94384	LED21T8/DR/1L	1
94385	LED21T8/DR/2L	2

General Characteristics - Non Dimming

GE Product Code	76289	38970	82347	94384	94385
Output Current (A)	0.21*2	0.44*2	0.53*2	0.62	0.62*2
Input Watt (Max)	24	30	36	21	42
Input Voltage (V)	120-277V				
Input Frequency (Hz)	50/60Hz				
Efficiency (%)	> .9%				
Output Type	DC				
Output Volt Range	27-33V				
Dimmability	None				
Ambient Temp Min	-4°F				
Ambient Temp Max	113°F				
Case Temperature	158°F				

Dimensions - Non Dimming

GE Product Code	82437	76289	38970	94384	94385
Weight	1.01	1.01	1.01	1.01	1.01
Casing Length (in)	9.5				
Casing Width (in)	1.3				
Casing Height (in)	1				
Lead Exit Length (in)	26				
Input Wire Length (in)	36				
Output Wire Length (in)	38				

Lighttech Drivers - Dimming

GE Product Code	Description	# of Lamps
76290	LED12T8/DR/D2L	2
76318	LED12T8/DR/4DL	4
38974	LED15T8/DR/D2L	2
38975	LED15T8/DR/4DL	4
88141	LED18T8/DR/D2L	2
88139	LED18T8/DR/4DL	4
60041	LED21T8/DR/D/2L	2
34016	LED21T8/DR/VLC/2L	2
62030	LED21T8/DR/D/4L	4

General Characteristics - Dimming

GE Product Code	88141	76290	38974	60041	34016	38975	62030	76318	88139
Output Current (A)	0.53*2	0.21*2	0.44*2	0.62*2	0.62*2	0.44*4	0.62*4	0.21*4	0.53*4
Input Watt (Max)	36	24	30	42	42	60	84	48	72
Input Voltage (V)	120-277V								
Input Frequency (Hz)	50/60Hz								
Efficiency (%)	> .9%								
Output Type	DC								
Output Volt Range	27-33V								
Dimmability	0-10V								
Ambient Temp Min	-4°F								
Ambient Temp Max	113°F								
Case Temperature	158°F								

Dimensions - Dimming

GE Product Code	76290	38974	34016	60041	38975	62030	76318
Weight	1.01			1.08			
Casing Length (in)	9.5			9.5			
Casing Width (in)	1.3			1.7			
Casing Height (in)	1			1			
Lead Exit Length (in)	26			26			
Input Wire Length (in)	36			36			
Output Wire Length (in)	38			42			

ecomaginationSM

current
powered by GE

<http://products.currentbyge.com>

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2017 GE.

LEDL017 (Rev 08/23/17)



Product is compliant with material restriction requirements of RoHS

