

Refit Solutions from GE



Application illustration only, subject lamps not used in photo.



Type C LED Tubes - Assembled in USA- 4' and 8' Glass

Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall. LED tubes are ideal for those seeking high energy savings with minimal installation time. Each LED tube is operated by a GE Lightech™ driver. See reverse for LED tubes and Lightech driver product details.

FEATURES

- 4' and 8' glass tubes
- 1,950-4,400 lumen option available
- >120 total system lumens per watt (LPW)
- 3000K, 3500K, 4000K and 5000K color temperatures
- 50,000-hour rated life
- UL & CUL Classified
 - in compliance with UL 1598 certification
- Open or Enclosed Fixtures
- Damp rating
- 5 year warranty

BENEFITS

- Fast and easy LED upgrade
- Low energy LFL replacement
- 66% longer life than LFL (50,000 vs. 30,000 hours)
- Better quality of light – instant on
- Fully illuminates fixture
 - 270° light distribution
- Easy disposal, non-hazardous waste
- State-of-Art USA Assembly
 - Perfect for special projects

To learn more about saving money and energy, go to: gelighting.com/ThinkLED

When you Think LED lighting, Think GE.

ecomagination™

current
powered by GE

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.



Product Specifications - Type C 4 and 8 Foot LED Glass Tubes

Refit LED Tubes

| GE Product Code | Description | Bulb Shape | Base | Watts | Case Quantity | Length (in) | Initial Lumens | Color Temp (K) | CRI | *Rated Life L70 (Hrs) |
|----------------------|------------------|------------|------------------|-------|---------------|-------------|----------------|----------------|-----|-----------------------|
| 4ft LED Tubes | | | | | | | | | | |
| 99696 | LED15T8/G4/830US | T8 | G13 | 13 | 20 | 48" | 1950 | 3000 | 80+ | 50,000 |
| 99697 | LED15T8/G4/835US | T8 | G13 | 13 | 20 | 48" | 2050 | 3500 | 80+ | 50,000 |
| 99698 | LED15T8/G4/840US | T8 | G13 | 13 | 20 | 48" | 2100 | 4000 | 80+ | 50,000 |
| 99699 | LED15T8/G4/850US | T8 | G13 | 13 | 20 | 48" | 2100 | 5000 | 80+ | 50,000 |
| 91475 | LED21T8/G4/830US | T8 | G13 | 18 | 20 | 48" | 2600 | 3000 | 80+ | 50,000 |
| 91496 | LED21T8/G4/835US | T8 | G13 | 18 | 20 | 48" | 2600 | 3500 | 80+ | 50,000 |
| 91497 | LED21T8/G4/840US | T8 | G13 | 18 | 20 | 48" | 2600 | 4000 | 80+ | 50,000 |
| 91498 | LED21T8/G4/850US | T8 | G13 | 18 | 20 | 48" | 2600 | 5000 | 80+ | 50,000 |
| 8ft LED Tubes | | | | | | | | | | |
| 62326 | LED36T8/G/8/830 | T8 | Single Pin (Fa8) | 30 | 20 | 96" | 4200 | 3000 | 80+ | 50,000 |
| 62327 | LED36T8/G/8/835 | T8 | Single Pin (Fa8) | 30 | 20 | 96" | 4400 | 3500 | 80+ | 50,000 |
| 62329 | LED36T8/G/8/840 | T8 | Single Pin (Fa8) | 30 | 20 | 96" | 4400 | 4000 | 80+ | 50,000 |
| 62349 | LED36T8/G/8/850 | T8 | Single Pin (Fa8) | 30 | 20 | 96" | 4400 | 5000 | 80+ | 50,000 |

Lightech Drivers™ - Non-Dimming

| GE Product Code | Description | # of Lamps |
|-----------------|------------------|------------|
| 38970 | LED15T8/DR/UN/2L | 2 |
| 94384 | LED21T8/DR/1L | 1 |
| 94385 | LED21T8/DR/2L | 2 |

Lightech Drivers - Dimming

| GE Product Code | Description | # of Lamps |
|-----------------|-------------------|------------|
| 38974 | LED15T8/DR/D2L | 2 |
| 38975 | LED15T8/DR/4DL | 4 |
| 60041 | LED21T8/DR/D/2L | 2 |
| 34016 | LED21T8/DR/VLC/2L | 2 |
| 62030 | LED21T8/DR/D/4L | 4 |
| 63126 | LED36T8/DR/D2L | 2 |

General Characteristics - Non Dimming

| GE Product Code | 38970 | 94384 | 94385 |
|----------------------|--------|----------|--------|
| Output Current (A) | 0.44*2 | 0.62 | 0.62*2 |
| Input Wattage (Max) | 30 | 21 | 42 |
| Input Voltage (V) | | 120-277V | |
| Input Frequency (Hz) | | 50/60Hz | |
| Efficiency (%) | | > .9% | |
| Output Type | | DC | |
| Output Voltage Range | | 27-33V | |
| Dimmability | | None | |
| Ambient Temp Min | | -4°F | |
| Ambient Temp Max | | 104°F | |
| Case Temperature | | 158°F | |

General Characteristics - Dimming

| GE Product Code | 38974 | 38975 | 60041 | 34016 | 62030 | 63126 |
|----------------------|--------|--------|----------|--------|--------|-------------|
| Output Current (A) | 0.44*2 | 0.44*4 | 0.62*2 | 0.62*2 | 0.62*4 | 0.54*2 |
| Input Wattage (Max) | 30 | 60 | 42 | 42 | 84 | 72 (36 x 2) |
| Input Voltage (V) | | | 120-277V | | | 120-277V |
| Input Frequency (Hz) | | | 50/60Hz | | | 50/60Hz |
| Efficiency (%) | | | > .9% | | | > .9% |
| Output Type | | | DC | | | DC |
| Output Voltage Range | | | 27-33V | | | 26-34V |
| Dimmability | | | 0-10V | | | 0-10V |
| Ambient Temp Min | | | -4°F | | | -4°F |
| Ambient Temp Max | | | 104°F | | | 113°F |
| Case Temperature | | | 158°F | | | 158°F |

Dimensions - Non Dimming

| GE Product Code | 38970 | 94384 | 94385 |
|-------------------------|-------|-------|-------|
| Weight | 1.01 | 1.01 | 1.08 |
| Casing Length (in) | | 9.5 | |
| Casing Width (in) | | 1.3 | |
| Casing Height (in) | | 1 | |
| Lead Exit Length (in) | | 26 | |
| Input Wire Length (in) | | 36 | |
| Output Wire Length (in) | | 38 | |

Dimensions - Dimming

| GE Product Code | 38974 | 38975 | 60041 | 34016 | 62030 | 63126 |
|-------------------------|-------|-------|-------|-------|-------|-------|
| Weight | | | 1.01 | | 1.08 | 1.01 |
| Casing Length (in) | | | 9.5 | | 9.5 | 9.5 |
| Casing Width (in) | | | 1.3 | | 1.7 | 1.3 |
| Casing Height (in) | | | 1 | | 1 | 1 |
| Lead Exit Length (in) | | | 26 | | 26 | 26 |
| Input Wire Length (in) | | | 36 | | 36 | 36 |
| Output Wire Length (in) | | | 38 | | 42 | 38 |



Product is compliant with material restriction requirements of RoHS



www.gelighting.com

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2016 GE.

LEDL035 (Rev 04/19/17)

