



Awaken

Inspired LED technology

CURRENT LED REPLACEMENT LAMPS AND TUBES



GE current
a Daintree company

LED REPLACEMENT TUBES

Ballast Bypass Glass Tubes XL - Double Ended - Type B/T8

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Power Factor	DLC*	#Location UL	Additional Information	
Ballast Bypass - 4 ft LED XL Glass Tubes																	
T8	G13	9.5	93132548	LED9BDT8/G4/830XL	120-277	20	48	1550	3000K	80		70,000	>.9	-	Yes	Damp	Double-Ended Power
	G13	9.5	93132549	LED9BDT8/G4/835XL	120-277	20	48	1600	3500K	80		70,000	>.9	Yes	Yes	Damp	Double-Ended Power
	G13	9.5	93132550	LED9BDT8/G4/840XL	120-277	20	48	1650	4000K	80		70,000	>.9	Yes	Yes	Damp	Double-Ended Power
	G13	9.5	93132551	LED9BDT8/G4/850XL	120-277	20	48	1650	5000K	80		70,000	>.9	Yes	Yes	Damp	Double-Ended Power
	G13	13	93132552	LED13BDT8/G4/830XL	120-277	20	48	1950	3000K	80		70,000	>.9	Yes	Yes	Damp	Double-Ended Power
	G13	13	93132553	LED13BDT8/G4/835XL	120-277	20	48	2000	3500K	80		70,000	>.9	Yes	Yes	Damp	Double-Ended Power
	G13	13	93132554	LED13BDT8/G4/840XL	120-277	20	48	2050	4000K	80		70,000	>.9	Yes	Yes	Damp	Double-Ended Power
	G13	13	93132555	LED13BDT8/G4/850XL	120-277	20	48	2050	5000K	80		70,000	>.9	Yes	Yes	Damp	Double-Ended Power
	G13	16	93132586	LED16BDT8/G4/830XL	120-277	20	48	2450	3000K	80		70,000	>.9	Yes	Yes	Damp	Double-Ended Power
	G13	16	93132587	LED16BDT8/G4/835XL	120-277	20	48	2500	3500K	80		70,000	>.9	Yes	Yes	Damp	Double-Ended Power
	G13	16	93132588	LED16BDT8/G4/840XL	120-277	20	48	2550	4000K	80		70,000	>.9	Yes	Yes	Damp	Double-Ended Power
	G13	16	93132589	LED16BDT8/G4/850XL	120-277	20	48	2550	5000K	80		70,000	>.9	Yes	Yes	Damp	Double-Ended Power

Ballast Bypass Glass Tubes - Double Ended - Type B

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Power Factor	DLC*	#Location UL	Additional Information	
Ballast Bypass - 8 ft LED Glass Tubes																	
T8	Fa8	34	93122170	LED34BDT8/G/8/830	120-277	20	96	4000	3000K	80		50,000	>.9	Yes	Yes	Damp	Double-Ended Power
	Fa8	34	93122171	LED34BDT8/G/8/835	120-277	20	96	4000	3500K	80		50,000	>.9	Yes	Yes	Damp	Double-Ended Power
	Fa8	34	93122172	LED34BDT8/G/8/840	120-277	20	96	4400	4000K	80		50,000	>.9	Yes	Yes	Damp	Double-Ended Power
	Fa8	34	93122174	LED34BDT8/G/8/850	120-277	20	96	4400	5000K	80		50,000	>.9	Yes	Yes	Damp	Double-Ended Power
Ballast Bypass - 4 ft LED Glass Tubes																	
G13	16	93123476	LED16BDT8/G4/830	120-277	20	48	2100	3000K	80			50,000	>.9	Yes	Yes	Damp	Double-Ended Power
G13	16	93125618	LED16BDT8/G4/835	120-277	20	48	2150	3500K	80			50,000	>.9	Yes	Yes	Damp	Double-Ended Power
G13	16	93125620	LED16BDT8/G4/840	120-277	20	48	2200	4000K	80			50,000	>.9	Yes	Yes	Damp	Double-Ended Power
G13	16	93125622	LED16BDT8/G4/850	120-277	20	48	2200	5000K	80			50,000	>.9	Yes	Yes	Damp	Double-Ended Power
G13	14	39493	LED14BDT8/G4/830	120-277	20	48	1700	3000K	80			50,000	>.9	Yes	Yes	Damp	Double-Ended Power
G13	14	39494	LED14BDT8/G4/835	120-277	20	48	1750	3500K	80			50,000	>.9	Yes	Yes	Damp	Double-Ended Power
G13	14	39498	LED14BDT8/G4/840	120-277	20	48	1800	4000K	80			50,000	>.9	Yes	Yes	Damp	Double-Ended Power
G13	14	39519	LED14BDT8/G4/850	120-277	20	48	1850	5000K	80			50,000	>.9	Yes	Yes	Damp	Double-Ended Power
G13	11	93117212	LED11BDT8/G4/830	120-277	20	48	1600	3000K	80			50,000	>.9	-	Yes	Damp	Double-Ended Power
G13	11	93117213	LED11BDT8/G4/835	120-277	20	48	1650	3500K	80			50,000	>.9	Yes	Yes	Damp	Double-Ended Power
G13	11	93117214	LED11BDT8/G4/840	120-277	20	48	1650	4000K	80			50,000	>.9	Yes	Yes	Damp	Double-Ended Power
G13	11	93117215	LED11BDT8/G4/850	120-277	20	48	1700	5000K	80			50,000	>.9	Yes	Yes	Damp	Double-Ended Power
Ballast Bypass - 3 ft LED Glass Tubes																	
G13	12	39525	LED12BDT8/G3/830	120-277	20	36	1450	3000K	80			50,000	>.9	Yes	Yes	Damp	Double-Ended Power
G13	12	39547	LED12BDT8/G3/835	120-277	20	36	1500	3500K	80			50,000	>.9	Yes	Yes	Damp	Double-Ended Power
G13	12	39554	LED12BDT8/G3/840	120-277	20	36	1550	4000K	80			50,000	>.9	Yes	Yes	Damp	Double-Ended Power
G13	12	39557	LED12BDT8/G3/850	120-277	20	36	1550	5000K	80			50,000	>.9	Yes	Yes	Damp	Double-Ended Power
Ballast Bypass - 2 ft LED Glass Tubes																	
G13	9	39558	LED9BDT8/G2/830	120-277	20	24	1100	3000K	80			50,000	>.9	Yes	Yes	Damp	Double-Ended Power
G13	9	39560	LED9BDT8/G2/835	120-277	20	24	1150	3500K	80			50,000	>.9	Yes	Yes	Damp	Double-Ended Power
G13	9	39561	LED9BDT8/G2/840	120-277	20	24	1200	4000K	80			50,000	>.9	Yes	Yes	Damp	Double-Ended Power
G13	9	39563	LED9BDT8/G2/850	120-277	20	24	1200	5000K	80			50,000	>.9	Yes	Yes	Damp	Double-Ended Power
Ballast Bypass - 4 ft LED Tube - PET Plastic Coated Glass																	
G13	14	93123123	LED14BDT8/G4/830CT	120-277	20	48	1650	3000K	80			50,000	>.9	Yes	Yes	Damp	Shatter containment, NSF
G13	14	93123124	LED14BDT8/G4/835CT	120-277	20	48	1750	3500K	80			50,000	>.9	Yes	Yes	Damp	Shatter containment, NSF
G13	14	93123316	LED14BDT8/G4/840CT	120-277	20	48	1750	4000K	80			50,000	>.9	Yes	Yes	Damp	Shatter containment, NSF
G13	14	93123317	LED14BDT8/G4/850CT	120-277	20	48	1800	5000K	80			50,000	>.9	Yes	Yes	Damp	Shatter containment, NSF
G13	11	93129539	LED11BDT8/G4/830CT	120-277	20	48	1550	3000K	80			50,000	>.9	-	Yes	Damp	Shatter containment, NSF
G13	11	93129660	LED11BDT8/G4/835CT	120-277	20	48	1600	3500K	80			50,000	>.9	Yes	Yes	Damp	Shatter containment, NSF
G13	11	93129666	LED11BDT8/G4/840CT	120-277	20	48	1650	4000K	80			50,000	>.9	Yes	Yes	Damp	Shatter containment, NSF
G13	11	93129717	LED11BDT8/G4/850CT	120-277	20	48	1700	5000K	80			50,000	>.9	Yes	Yes	Damp	Shatter containment, NSF

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at

www.gecurrent.com