



LED Lamps - HID



Ballast Bypass - Ordinary Locations

LED replacement for HID lamps leverage the low energy and long life of LED. The existing fixture is wired to bypass the ballast, which reduces energy use and eliminates the need to check ballast compatibility. Additional maintenance savings are realized by removing costs associated with purchasing and installing ballasts.

PERFORMANCE HIGHLIGHTS:

Ballast Bypass - Ordinary Locations	
Light Output:	3,400 - 106,000 Lumens
CRI:	70
CCT:	Selectable: 3000K/4000K/5000K; 1800K/2200K/2700K Standard: 3000K, 3500K, 4000K, 5000K
Input Voltage:	120-277V; 120-347V; 208-277; 277-480V
Efficiency:	Up to 208 LPW
Wattage:	21W-520W
Life:	50,000
Temperature Rating:	-40°C to +50°C
Location Rating:	Damp
Fixtures:	Open or Enclosed

FEATURES:

- 3.3X longer life than metal halide (50,000 vs 15,000 hours)
- Uses 60-75% less energy, providing similar light output
- In-line misapplication fuse kit included
- Tether kit included with ED18, ED23.5, ED28, ED37 & BT56
- Horizontal support kit included with ED37 & BT56
- Matches ANSI length & diameter of HID lamp shape
- These lamps are energy efficient, contain no lead or mercury and are compliant with material restriction requirements of RoHS

BENEFITS:

- **Energy + Cost Savings:** an LED lamp saves in energy costs over the rated life of the lamp vs. a standard HID lamp. See energy savings chart below.
- Ballast bypass (Type B) wiring eliminates costs and hassle associated with replacing ballasts

LIMITED WARRANTY

5 years

LEARN MORE:

To learn more about saving money and energy, go to www.LED.com.

Energy Savings switching from HID to Type B LED Lamps

Lamp Replacement Wattage	HID System Wattage	LED System Wattage	System Energy Savings (W)	System Energy Cost Savings Over Life of Lamp*
1500	1602	520	1082	\$5,951
1000	1075	450	625	\$3,437
1000	1075	270	805	\$4,427
750	825	200	625	\$2,553
400	460	150	310	\$1,705
250	290	115	175	\$962
175	210	80	130	\$715
100	120	50	70	\$385

*Based on energy rates at 0.11 per kWh over the life of the lamp

LED Lamps for Hazardous Locations are also available - See Spec Sheet LEDL089 & White Paper LEDL126 for more information.




Ballast Bypass for Ordinary Locations

CUSTOMER NAME	
PROJECT NAME	
DATE	NOTES

GE LED Lamps for HID Replacement utilize a proprietary design with active cooling, which allows for high output from a compact size. The length and diameter match HID ANSI profiles. These lamps feature omnidirectional light output, with similar distribution to traditional HID lamps. This enables GE LED Lamps to fit in a variety of fixtures while providing equivalent light levels to HID. All of the GE LED Lamps in this category are Type B, which means the fixture is re-wired to bypass the ballast.

Lamp Drawings (not drawn to scale)





Ballast Bypass for Ordinary Locations

CUSTOMER NAME	
PROJECT NAME	
DATE	NOTES

NEMA LED HID Wattage Equivalency

In February of 2021, the National Electrical Manufacturers Association (NEMA) published NEMA LL 10-2020 *Replacing HID Lamps with LED Lamps: Light Output Equivalency Claims*. Current uses this Standard for LED products replacing HID lamps, meeting or exceeding the minimum LED light output for equivalency claims. The LED wattage equivalency varies based on the type of HID lamp being replaced - Metal Halide (MH) or High Pressure Sodium (HPS).

Metal Halide Lamp Wattage (W)	Metal Halide Initial Light Output (lm)	Minimum LED Lamp Initial Light Output (lm)	Current LED Ordinary Location Retrofit Lamps	Current LED Ordinary Location Selectable Retrofit Lamps	Current LED Hazardous Location Retrofit Lamps
50	3,200	2,000	LED21ED17	LED/LC/ED17	LED21ED17/HAZ
70	5,200	3,000	LED21ED17	LED/LC/ED17	LED21ED17/HAZ
100	8,100	5,000	LED35ED17; LED45ED17	LED/LC/ED17	LED35ED17/HAZ; LED45ED17/HAZ
150	12,000	7,500	LED50ED23.5	LED/LC/ED23.5	
175	11,000	7,000	LED45ED17; LED50ED23.5	LED/LC/ED17; LED/LC/ED23.5	
250	19,100	12,000	LED80ED23.5	LED/LC/ED23.5	LED80ED23.5/HAZ
320	25,600	16,500	LED115ED28	LED/LC/ED28	
350	28,400	18,000	LED115ED28	LED/LC/ED28	
360	29,400	19,000	LED150ED28; LED120ED18	LED/LC/ED28	LED150ED28/HAZ
400	33,100	21,500	LED150ED28; LED180ED18; LED200ED37	LED/LC/ED28; LED/LC/ED37	LED150ED28/HAZ
750	72,300	46,500	LED360ED37	LED/LC/ED37	
1,000	100,280	65,000	LED450BT56; LED470BT56	LED/LC/ED37	
1,500	153,000	99,450	LED520BT56		

HPS Lamp Wattage (W)	HPS Initial Light Output (lm)	Minimum LED Lamp Initial Light Output (lm)	Current LED Ordinary Location Retrofit Lamps	Current LED Ordinary Location Selectable Retrofit Lamps	Current LED Hazardous Location Retrofit Lamps
50	4,500	2,500	LED21ED17	LED/LC/ED17	LED21ED17/HAZ
70	6,300	4,000	LED35ED17	LED/LC/ED17	LED35ED17/HAZ
100	9,500	6,000	LED45ED17; LED50ED23.5	LED/LC/ED17; LED/LC/ED23.5	LED45ED17/HAZ
150	13,000	8,500	LED80ED23.5	LED/LC/ED23.5	LED80ED23.5/HAZ
200	19,500	12,500		LED/LC/ED23.5	
250	26,000	17,000	LED115ED28; LED120ED18	LED/LC/ED28	
310	33,200	21,500	LED150ED28	LED/LC/ED28	LED150ED28/HAZ
400	44,000	29,000	LED180ED18; LED200ED37; LED270BT56	LED/LC/ED37	
600	66,000	42,500	LED360ED37	LED/LC/ED37	
750	82,500	53,500	LED450BT56	LED/LC/ED37	
1,000	110,000	73,000	LED470BT56; LED520BT56		



Ballast Bypass for Ordinary Locations

CUSTOMER NAME	_____
PROJECT NAME	_____
DATE	NOTES

Go to www.LED.com to learn more about Current's family of Selectable LED Lamps.



Selectable LED Lamps

Current offers unmatched flexibility with Selectable LED HID Replacement Lamps. Select wattage and color temperature at the flick of a switch.

- Reduce & simplify inventory** - one lamp can replace many, reducing inventory dollars & storage space
- Optimize solutions & save** - adjust light output to the correct level & color for each application & reduce energy consumption
- Simplify projects & BOMs** - streamline product lists & take the guesswork out of which lamps are needed where




Lumen**Choice**®



Select wattage (lumens) using built-in switch.



Spectra**Choice**™



Select color temperature using built-in switch.



Even more versatility

Each E26 base lamp comes with a mogul base adapter. Lamps may be used in E26 or E39/EX39 sockets.

LED HID Accessories

Order Code	Description	Carton Qty ²	
93151372	LED/E26/EX39/ADAPTER	60	E26/EX39 Socket Adapter
93313551	LED-HID-TETHER-KIT	20	1 Tether Kit
93313553	LED-HID-4A-FUSE-KIT	20	1 Fuse (4A), 1 Fuse Holder
93313555	LED-HID-8A-FUSE-KIT	20	1 Fuse (8A), 1 Fuse Holder



Ballast Bypass for Ordinary Locations

CUSTOMER NAME _____
 PROJECT NAME _____
 DATE _____ NOTES _____

Selectable LumenChoice® + SpectraChoice™ HID Replacement - Type B

Bulb Shape	Base Type	Order Code	Description	Volts	Carton Qty ²	MOL (in)	MOD (in)	Selectable Watts*	Selectable Lumens (Initial)*	Selectable Color Temp. (Initial)*	Wattage Replacement ⁷	CRI	Rated Life L70 (Hrs) ¹	DLC ^{3,4}	Location Rating ^{5,6}
LED Replacement Lamp for HID - Ballast Bypass (Type B)															
ED17	E26/EX39	93303384	LED/LC/ED17/7SC	120-277	3	5.4	2.6	21	3,400	3000K	50W HPS / 70W MH	>70	50,000	-	Damp
								35*	5,500*	4000K*	70W HPS / 100W MH				
								45	7,000	5000K	100W HPS / 175W MH				
	E26/EX39	93314526	LED/LC/ED17/7SC/120-347	120-347	3	5.4	2.6	21	3,400	3000K	50W HPS / 70W MH	>70	50,000	-	Damp
								35*	5,500*	4000K*	70W HPS / 100W MH				
								45	7,000	5000K	100W HPS / 175W MH				
ED23.5	E26/EX39	93312104	LED/LC/ED23.5M/7SC	120-277	3	7.8	3.7	50	8,200	3000K	100W HPS / 150W MH	>70	50,000	-	Damp
								65	10,500	4000K	150W HPS / 250W MH				
								80*	12,500*	5000K*	150W HPS / 250W MH				
	EX39	93312106	LED/LC/ED23.5/7SC	120-277	3	7.8	3.7	50	8,200	3000K	100W HPS / 150W MH	>70	50,000	S-4V5N0G	Damp
								65	10,500	4000K	150W HPS / 150W MH				
								80*	12,500*	5000K*	150W HPS / 250W MH				
	EX39	93314766	LED/LC/ED23.5/7SC/277-480	277-480	3	7.8	3.7	50	8,200	3000K	100W HPS / 150W MH	>70	50,000	S-Y2WDPN / S-S2HLFY	Damp
								65	10,500	4000K	150W HPS / 150W MH				
								80*	12,500*	5000K*	150W HPS / 250W MH				
ED28	EX39	93312102	LED/LC/ED28/7SC	120-277	3	8.3	4.1	90	14,000	3000K	200W HPS / 250W MH	>70	50,000	S-MB9GRL / S-NMTK94	Damp
								115	18,000	4000K	250W HPS / 350W MH				
								150*	23,500*	5000K*	310W HPS / 400W MH				
	EX39	93314772	LED/LC/ED28/7SC/277-480	277-480	3	8.3	4.1	90	14,000	3000K	200W HPS / 250W MH	>70	50,000	S-WWN1WP / S-3WC1C9	Damp
								115	18,000	4000K	250W HPS / 350W MH				
								150*	23,500*	5000K*	310W HPS / 400W MH				

Selectable LumenChoice® HID Replacement - Type B

Bulb Shape	Base Type	Order Code	Description	Volts	Carton Qty ²	MOL (in)	MOD (in)	Selectable Watts*	Selectable Lumens (Initial)*	Selectable Color Temp. (Initial)*	Wattage Replacement ⁷	CRI	Rated Life L70 (Hrs) ¹	DLC ^{3,4}	Location Rating ^{5,6}
LED Replacement Lamp for HID - Ballast Bypass (Type B)															
ED37	EX39	93321818	LED/LC/ED37/740/208-277	208-277	3	11.3	5.6	200	35,000	4000K	400W HPS / 400W MH	>70	50,000	S-TQ7WXV	Damp
								325	53,500		750W HPS / 750W MH				
								450*	68,000*		750W HPS / 1000W MH				
	EX39	93311586	LED/LC/ED37/740	277-480	3	11.3	5.6	200	35,000	4000K	400W HPS / 400W MH	>70	50,000	S-ZZMLJT	Damp
								325	53,500		750W HPS / 750W MH				
								450*	68,000*		750W HPS / 1000W MH				
	EX39	93321820	LED/LC/ED37/750/208-277	208-277	3	11.3	5.6	200	35,000	5000K	400W HPS / 400W MH	>70	50,000	S-T4ZBKH	Damp
								325	53,500		750W HPS / 750W MH				
								450*	68,000*		750W HPS / 1000W MH				
	EX39	93311587	LED/LC/ED37/750	277-480	3	11.3	5.6	200	35,000	5000K	400W HPS / 400W MH	>70	50,000	S-25L41Q	Damp
								325	53,500		750W HPS / 750W MH				
								450*	68,000*		750W HPS / 1000W MH				

Warm Selectable LumenChoice® + SpectraChoice™ HID Replacement - Type B

Bulb Shape	Base Type	Order Code	Description	Volts	Carton Qty ²	MOL (in)	MOD (in)	Selectable Watts*	Selectable Lumens (Initial)*	Selectable Color Temp. (Initial)*	Wattage Replacement ⁷	CRI	Rated Life L70 (Hrs) ¹	DLC ³	Location Rating ^{5,6}
LED Replacement Lamp for HID - Ballast Bypass (Type B)															
ED17	E26/EX39	93315986	LED/LC/ED17/7WSC/120-347	120-347	3	5.4	2.6		2,450	1800K	35W HPS / 50W MH	>70	50,000	-	Damp
									3,000	2200K	35W HPS / 50W MH				
									3,300	2700K	50W HPS / 50W MH				
									3,950	1800K	35W HPS / 50W MH				
									4,900*	2200K*	50W HPS / 70W MH				
									5,350	2700K	70W HPS / 70W MH				
									4,900	1800K	50W HPS / 70W MH				
									45	6,200	2200K				
								6,650	2700K	70W HPS / 100W MH					

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen output (L70)

² Minimum order quantity = 1

³ E26 based products are not eligible for DLC. Not all product variations on this page are DLC qualified. Visit qpl.designlights.org/solid-state-lighting to confirm qualification.

⁴ Do not use with phase-cut dimmers. Dimming functions only with external Variac control devices.

⁵ UL 1993 Environmental Requirements for LED LAMPS

Damp Location - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to electrical equipment, including partially protected locations

⁶ Not suitable for air-tight explosive or hazardous fixtures.

⁷ Wattage Replacement levels correspond with wattage levels. Wattage Replacements based on NEMA Standards Publication LL 10-2020 *Replacing HID Lamps with LED Lamps: Light Output Equivalency Claims*.

* Default wattage and color temperature settings noted by "*" in tables above.



LED Lamps - HID

Ballast Bypass for Ordinary Locations

CUSTOMER NAME _____
 PROJECT NAME _____
 DATE _____ NOTES _____

LED HID - Type B

Bulb Shape	Base Type	Order Code	Description	Volts	Carton Qty ²	MOL (in)	MOD (in)	Watts	Lumens (Initial)	Color Temp. (Initial)	Wattage Replacement ⁷	CRI	Rated Life L70 (Hrs) ¹	DLC ^{3,4}	Location Rating ^{5,6}	
LED Replacement Lamps for HID - Ballast Bypass (Type B)																
ED17	E26	27729	LED21ED17/740	120-277	3	5.4	2.6	21	3,400	4000K	50W HPS / 70W MH	>70	50,000	-	Damp	
	E26	27732	LED21ED17/750	120-277	3	5.4	2.6	21	3,400	5000K	50W HPS / 70W MH	>70	50,000	-	Damp	
	E26	93112114	LED35ED17/730	120-277	3	5.4	2.6	35	5,000	3000K	70W HPS / 100W MH	>70	50,000	-	Damp	
	E26	27602	LED35ED17/740	120-277	3	5.4	2.6	35	5,000	4000K	70W HPS / 100W MH	>70	50,000	-	Damp	
	E26	27724	LED35ED17/750	120-277	3	5.4	2.6	35	5,000	5000K	70W HPS / 100W MH	>70	50,000	-	Damp	
	E26	93116975	LED45ED17/835	120-277	3	5.4	2.6	45	6,000	3500K	100W HPS / 100W MH	>70	50,000	-	Damp	
	E26	93148082	LED45ED17/740	120-277	3	5.4	2.6	45	7,000	4000K	100W HPS / 175W MH	>70	50,000	-	Damp	
	E26	93148081	LED45ED17/750	120-277	3	5.4	2.6	45	7,000	5000K	100W HPS / 175W MH	>70	50,000	-	Damp	
	ED23.5	E26	22768	LED80ED23.5M/740	120-277	3	7.8	3.7	80	12,000	4000K	150W HPS / 250W MH	>70	50,000	-	Damp
		E26	93125008	LED80ED23.5M/750	120-277	3	7.8	3.7	80	12,000	5000K	150W HPS / 250W MH	>70	50,000	-	Damp
EX39		22679	LED50ED23.5/740	120-277	3	7.8	3.7	50	7,500	4000K	100W HPS / 150W MH	>70	50,000	P2LJ433Z	Damp	
EX39		22739	LED50ED23.5/750	120-277	3	7.8	3.7	50	7,500	5000K	100W HPS / 150W MH	>70	50,000	P9E7B4MB	Damp	
EX39		93154637	LED50ED23.5/740/277/480	277-480	3	7.8	3.7	50	7,500	4000K	100W HPS / 150W MH	>70	50,000	S-QSEC3A	Damp	
EX39		93154639	LED50ED23.5/750/277/480	277-480	3	7.8	3.7	50	7,500	5000K	100W HPS / 150W MH	>70	50,000	S-TGNWE4	Damp	
EX39		22635	LED80ED23.5/740	120-277	3	7.8	3.7	80	12,000	4000K	150W HPS / 250W MH	>70	50,000	PHJ4LA1W	Damp	
EX39		22676	LED80ED23.5/750	120-277	3	7.8	3.7	80	12,000	5000K	150W HPS / 250W MH	>70	50,000	PYL1MPL2	Damp	
EX39		93154642	LED80ED23.5/740/277/480	277-480	3	7.8	3.7	80	12,000	4000K	150W HPS / 250W MH	>70	50,000	S-TUGPZM	Damp	
EX39		93154640	LED80ED23.5/750/277/480	277-480	3	7.8	3.7	80	12,000	5000K	150W HPS / 250W MH	>70	50,000	S-IFJ4CK	Damp	
ED28	EX39	93112197	LED115ED28/730	120-277	3	8.3	4.1	115	18,000	3000K	250W HPS / 350W MH	>70	50,000	PE646DNU / S-PJV8RX	Damp	
	EX39	22622	LED115ED28/740	120-277	3	8.3	4.1	115	18,000	4000K	250W HPS / 350W MH	>70	50,000	PONSAR2J / S-7Y6F60	Damp	
	EX39	22623	LED115ED28/750	120-277	3	8.3	4.1	115	18,000	5000K	250W HPS / 350W MH	>70	50,000	PZFIPZUL / S-VVTYR7	Damp	
	EX39	93139853	LED115ED28/740/277/480	277-480	3	8.3	4.1	115	18,000	4000K	250W HPS / 350W MH	>70	50,000	PZ3P5P7U/PEQF29S7	Damp	
	EX39	93139854	LED115ED28/750/277/480	277-480	3	8.3	4.1	115	18,000	5000K	250W HPS / 350W MH	>70	50,000	PY31MNAU/PCV74KSL	Damp	
	EX39	93112198	LED150ED28/730	120-277	3	8.3	4.1	150	23,500	3000K	310W HPS / 400W MH	>70	50,000	PAVD2D0E	Damp	
	EX39	22611	LED150ED28/740	120-277	3	8.3	4.1	150	23,500	4000K	310W HPS / 400W MH	>70	50,000	P5Y3N60	Damp	
	EX39	22613	LED150ED28/750	120-277	3	8.3	4.1	150	23,500	5000K	310W HPS / 400W MH	>70	50,000	PIEL9LHG	Damp	
	EX39	93139849	LED150ED28/740/277/480	277-480	3	8.3	4.1	150	23,500	4000K	310W HPS / 400W MH	>70	50,000	PUQUH5LU/PYCNNIK7	Damp	
	ED18	EX39	93320018	LED120ED18/730/277-480	277-480	3	9.7	3.0	120	20,000	3000K	250W HPS / 360W MH	>70	50,000	S-47FGTZ	Damp
EX39		93320024	LED120ED18/740/277-480	277-480	3	9.7	3.0	120	20,000	4000K	250W HPS / 360W MH	>70	50,000	S-INR1YH	Damp	
EX39		93320030	LED120ED18/750/277-480	277-480	3	9.7	3.0	120	20,000	5000K	250W HPS / 360W MH	>70	50,000	S-MQGM9J	Damp	
EX39		93312096	LED180ED18/730	120-277	3	9.7	3.0	180	30,000	3000K	400W HPS / 400W MH	>70	50,000	S-F26H3J	Damp	
EX39		93312098	LED180ED18/740	120-277	3	9.7	3.0	180	30,000	4000K	400W HPS / 400W MH	>70	50,000	S-WN2HR8	Damp	
EX39		93312100	LED180ED18/750	120-277	3	9.7	3.0	180	30,000	5000K	400W HPS / 400W MH	>70	50,000	S-BG0B87	Damp	
EX39		93320000	LED180ED18/730/277-480	277-480	3	9.7	3.0	180	30,000	3000K	400W HPS / 400W MH	>70	50,000	S-LCDXR9	Damp	
EX39		93320006	LED180ED18/740/277-480	277-480	3	9.7	3.0	180	30,000	4000K	400W HPS / 400W MH	>70	50,000	S-9792TD	Damp	
EX39		93320012	LED180ED18/750/277-480	277-480	3	9.7	3.0	180	30,000	5000K	400W HPS / 400W MH	>70	50,000	S-HYQC7Z	Damp	
BT56		EX39	93153080	LED270BT56/740/120/277	120-277	3	12.3	5.6	270	40,000	4000K	400W HPS / 400W MH	>70	50,000	PG8499V4	Damp
	EX39	93153121	LED270BT56/750/120/277	120-277	3	12.3	5.6	270	40,000	5000K	400W HPS / 400W MH	>70	50,000	PIZKSQ30	Damp	
	EX39	93095547	LED270BT56/740	277-480	3	12.3	5.6	270	40,000	4000K	400W HPS / 400W MH	>70	50,000	PW00LOQL	Damp	
	EX39	93095553	LED270BT56/750	277-480	3	12.3	5.6	270	40,000	5000K	400W HPS / 400W MH	>70	50,000	PUZP8RVI	Damp	
ED37	EX39	93122144	LED360ED37/740	277-480	3	10.6	5.6	360	53,000	4000K	600W HPS / 750W MH	>70	50,000	P7WQQT4S	Damp	
	EX39	93122166	LED360ED37/750	277-480	3	10.6	5.6	360	53,000	5000K	600W HPS / 750W MH	>70	50,000	PK5HC9UY	Damp	
BT56	EX39	93153122	LED450BT56/740/208/277	208-277	3	12.3	5.6	450	65,000	4000K	750W HPS / 1000W MH	>70	50,000	POIL8M4C	Damp	
	EX39	93153123	LED450BT56/750/208/277	208-277	3	12.3	5.6	450	65,000	5000K	750W HPS / 1000W MH	>70	50,000	PD4K2UXF	Damp	
	EX39	93096445	LED450BT56/740	277-480	3	12.3	5.6	450	65,000	4000K	750W HPS / 1000W MH	>70	50,000	PLNCOZ5Z	Damp	
	EX39	93096547	LED450BT56/750	277-480	3	12.3	5.6	450	65,000	5000K	750W HPS / 1000W MH	>70	50,000	PH8F9ZNF	Damp	
	EX39	93303389	LED470BT56/740	277-480	3	12.8	5.6	470	85,000	4000K	1000W HPS / 1000W MH	>70	50,000	S-E56HRP	Damp	
	EX39	93303388	LED470BT56/750	277-480	3	12.8	5.6	470	85,000	5000K	1000W HPS / 1000W MH	>70	50,000	S-64APZW	Damp	
	EX39	93320138	LED520BT56/740/208-277	208-277	3	12.8	5.6	520	106,000	4000K	1000W HPS / 1500W MH	>70	50,000	S-8J5CHR	Damp	
	EX39	93320144	LED520BT56/750/208-277	208-277	3	12.8	5.6	520	106,000	5000K	1000W HPS / 1500W MH	>70	50,000	S-7CHFSW	Damp	

Additional Information for LED Replacement Lamps for HID: Open and Closed Rated - Ballast bypass required
 These products are covered by U.S. Patents 10788163 and 10508776. These products may also be covered by other U.S. patents or pending applications.

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen output (L70)
² Minimum order quantity = 1
³ E26 based products are not eligible for DLC. Not all product variations on this page are DLC qualified. Visit qpl.designlights.org/solid-state-lighting to confirm qualification.
⁴ Do not use with phase-cut dimmers. Dimming functions only with external Variac control devices.
⁵ UL 1993 Environmental Requirements for LED LAMPS
 Damp Location - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to electrical equipment, including partially protected locations
⁶ Not suitable for air-tight explosive or hazardous fixtures.
⁷ Wattage Replacement levels correspond with wattage levels. Wattage Replacements based on NEMA Standards Publication LL 10-2020 *Replacing HID Lamps with LED Lamps: Light Output Equivalency Claims*.