



LED Lamps - Plug-in



Type B 2-Pin Plug-in Lamps

Type B Plug-in lamps provide an easy solution to leverage the low energy and long life of LED. The existing fixture is wired to bypass the ballast, which further reduces energy use and eliminates the need to check ballast compatibility. Type B Plug-ins also present a long-term replacement lamp option when compact fluorescents and CFL ballasts become unavailable.

PERFORMANCE HIGHLIGHTS:

Type B 2-Pin Plug-in Lamps	
Light Output Range:	500 - 1,850 Lumens
CRI:	80
CCT:	Various, Selectable on some models
Input Voltage:	120-277; 120-347 on some models
Efficiency:	Up to 105 LPW
Wattage:	5W - 18W
Life:	Up to 50,000 hours L70
Temperature Rating:	-20°C to 40°C
Location Rating:	Damp

FEATURES:

- Operate from 120-277 or 120-347VAC input voltage
- Fit in existing CFL sockets
- Selectable color temperature available on some models
- Directional light output can provide improved fixture efficiency
- Last up to 4x longer than CFL
- These lamps are energy efficient, contain no lead or mercury and are compliant with material restriction requirements of RoHS


BENEFITS:

Energy + Cost Savings

- For example, using only 10.5 watts of energy, save over \$90 in energy costs over the rated life of the lamp versus a standard 26-watt compact fluorescent lamp operated on a ballast based on \$0.11 per kWh
- Eliminate the need for ballasts and provide long-term lamp replacement options
- G24 2-pin lamps work in 2-pin G24d and 4-pin G24q sockets
- Selectable color temperature allows flexibility to match color with fewer SKUs

LIMITED WARRANTY

5 years



Available on some models:
Select color temperature using built-in switch.

LEARN MORE:

To learn more about saving money and energy, go to www.LED.com.



Selectable **LED Lamps**

Do more with less.



- *Reduce Inventory*
- *Simplify Projects*
- *Optimize Solutions*








Type B 2-Pin Plug-in Lamps

CUSTOMER NAME _____
 PROJECT NAME _____
 DATE _____ NOTES _____

Ballast Bypass SpectraChoice™ 2-Pin Plug-in Lamps - Type B

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Carton Qty ²	MOL (in)	MOD (in)	Lumens (Initial) ⁵	Selectable Color Temp.*	CRI	Wattage Replacement	Rated Life L70 (Hrs) ¹	DLC ⁴	Location Rating ³	Additional Information
Horizontal 2-pin - Fits in G24d and G24q sockets - Ballast Bypass																
	G24	10.5	93300087	LED11BG24-H/8SC/120-347-4PK	120-347	24	6.4	1.9	1000	2700	80	13/18/26	50,000	N/A	Damp, Enclosed	Ballast Bypass, 4 pack
									1100	3000						
									1100	3500						
									1100	4000						
	G24	18	93312525	LED18BG24-H/8SC/120-347	120-347	12	6.8	2.3	1850	2700	80	32/42	50,000	N/A	Damp, Enclosed	Ballast Bypass
									1850	3000						
									1850	3500						
									1850	4000						
Vertical 2-pin - Fits in G24d and G24q sockets - Ballast Bypass																
	G24	10.5	93300088	LED11BG24-V/8SC/120-347-4PK	120-347	24	5.9	3.1	1000	2700	80	13/18/26	50,000	N/A	Damp, Enclosed	Ballast Bypass, 4 pack
									1100	3000						
									1100	3500						
									1100	4000						
	G24	18	93312489	LED18BG24-V/8SC/120-347	120-347	12	6.5	3.6	1850	2700	80	32/42	50,000	N/A	Damp, Enclosed	Ballast Bypass
									1850	3000						
									1850	3500						
									1850	4000						

Ballast Bypass Fixed Color Temperature 2-Pin Plug-in Lamps - Type B

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Carton Qty ²	MOL (in)	MOD (in)	Lumens (Initial)	Color Temp. (Initial)	CRI	Wattage Replacement	Rated Life L70 (Hrs) ¹	DLC ⁴	Location Rating ³	Additional Information
Type B 2-pin - G23 replacement - Ballast Bypass																
	G23	5	93312465	LED5BG23/827	120-277	24	5.4		500	2700K	80	7/9	50,000	N/A	Damp, Enclosed	Ballast Bypass
	G23	5	93312471	LED5BG23/830	120-277	24	5.4		500	3000K	80	7/9	50,000	N/A	Damp, Enclosed	Ballast Bypass
	G23	5	93312477	LED5BG23/835	120-277	24	5.4		500	3500K	80	7/9	50,000	N/A	Damp, Enclosed	Ballast Bypass
	G23	5	93312483	LED5BG23/840	120-277	24	5.4		500	4000K	80	7/9	50,000	N/A	Damp, Enclosed	Ballast Bypass
Type B 2-pin - GX23 replacement - Ballast Bypass																
	GX23	5	93312495	LED5BGX23/827	120-277	24	6.8		500	2700K	80	13	50,000	N/A	Damp, Enclosed	Ballast Bypass
	GX23	5	93312501	LED5BGX23/830	120-277	24	6.8		500	3000K	80	13	50,000	N/A	Damp, Enclosed	Ballast Bypass
	GX23	5	93312507	LED5BGX23/835	120-277	24	6.8		500	3500K	80	13	50,000	N/A	Damp, Enclosed	Ballast Bypass
	GX23	5	93312513	LED5BGX23/840	120-277	24	6.8		500	4000K	80	13	50,000	N/A	Damp, Enclosed	Ballast Bypass
	GX23	5	93312519	LED5BGX23/850	120-277	24	6.8		500	5000K	80	13	50,000	N/A	Damp, Enclosed	Ballast Bypass
Type B 2-pin - GX23-2 replacement - Ballast Bypass																
	GX23-2	7.5	93312531	LED8BGX23-2-O/827	120-277	24	4.7	1.5	800	2700K	80	13	20,000	N/A	Damp, Enclosed	Ballast Bypass
	GX23-2	7.5	93312537	LED8BGX23-2-O/830	120-277	24	4.7	1.5	800	3000K	80	13	20,000	N/A	Damp, Enclosed	Ballast Bypass
	GX23-2	7.5	93312543	LED8BGX23-2-O/835	120-277	24	4.7	1.5	800	3500K	80	13	20,000	N/A	Damp, Enclosed	Ballast Bypass
	GX23-2	7.5	93312549	LED8BGX23-2-O/840	120-277	24	4.7	1.5	800	4000K	80	13	20,000	N/A	Damp, Enclosed	Ballast Bypass
Type B 2-pin - Fits in G24d and G24q sockets - Ballast Bypass																
	G24	7.5	93300068	LED8BG24-O/827-4PK	120-277	24	4.4	1.5	800	2700K	80	13	20,000	N/A	Damp, Enclosed	Ballast Bypass, 4 pack
	G24	7.5	93300069	LED8BG24-O/830-4PK	120-277	24	4.4	1.5	850	3000K	80	13	20,000	N/A	Damp, Enclosed	Ballast Bypass, 4 pack
	G24	7.5	93300080	LED8BG24-O/835-4PK	120-277	24	4.4	1.5	850	3500K	80	13	20,000	N/A	Damp, Enclosed	Ballast Bypass, 4 pack
	G24	7.5	93300081	LED8BG24-O/840-4PK	120-277	24	4.4	1.5	850	4000K	80	13	20,000	N/A	Damp, Enclosed	Ballast Bypass, 4 pack
Type B 2-pin - Fits in G24d and G24q sockets - Ballast Bypass																
	G24	10	93300082	LED10BG24-O/827-4PK	120-277	24	5.4	1.8	1100	2700K	80	18	50,000	N/A	Damp, Enclosed	Ballast Bypass, 4 pack
	G24	10	93300083	LED10BG24-O/830-4PK	120-277	24	5.4	1.8	1200	3000K	80	18	50,000	N/A	Damp, Enclosed	Ballast Bypass, 4 pack
	G24	10	93300084	LED10BG24-O/835-4PK	120-277	24	5.4	1.8	1200	3500K	80	18	50,000	N/A	Damp, Enclosed	Ballast Bypass, 4 pack
	G24	10	93300086	LED10BG24-O/840-4PK	120-277	24	5.4	1.8	1200	4000K	80	18	50,000	N/A	Damp, Enclosed	Ballast Bypass, 4 pack

Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen output (L70)

² Minimum order quantity from Current - Carton Qty; Smaller unit of sale pack inside carton

³ UL 1993 Environmental Requirements for LED LAMPS

Damp Location - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to electrical equipment, including partially protected locations

⁴ DLC does not have a category for two-pin plug-in lamps.

⁵ Lumen levels correspond with color temperature.

* Default color temperature setting is 4000K.