



# LED Lamps - Plug-in



## SpectraChoice™ Type A 4-pin Plug-in

SpectraChoice™ Type A Plug-in lamps with Selectable CCT provide an easy solution to leverage the low energy and long life of LED. Simply plug the LED lamp into the existing fixture, no tools or re-wiring required.



SpectraChoice™


### PERFORMANCE HIGHLIGHTS:

#### SpectraChoice™ Type A 4-pin Plug-in Lamp

<b>Light Output Range:</b>	1000-1100, 1850 Lumens
<b>CRI:</b>	80
<b>Selectable CCT:</b>	2700K, 3000K, 3500K & 4000K
<b>Efficiency:</b>	Up to 122 LPW
<b>Wattage:</b>	9W, 18.5W
<b>Life:</b>	50,000 hours L70
<b>Temperature Rating:</b>	-20°C to 40°C
<b>Location Rating:</b>	Damp

### LIMITED WARRANTY

5 years



Select color temperature using built-in switch.

### FEATURES:

- Select color temperature with built-in switch, no tool required
- Fits in 4-pin G24q sockets
- Operates from electronic ballasts
- Directional light output for improved fixture efficiency
- Lasts 2.5x longer than CFL
- These lamps are energy efficient, contain no lead or mercury and are compliant with material restriction requirements of RoHS

### BENEFITS:

- For example, using only 9 watts of energy, save over \$90 in energy costs over the rated life of the lamp versus a standard 26-watt compact fluorescent lamp based on \$0.11 per kWh
- One lamp can replace many, greatly reducing inventory
- Use one lamp for applications requiring different CCTs, simplifying project management by streamlining BOMs
- Match color temperature across space with flip of a switch

### LEARN MORE:

To learn more about saving money and energy, go to [www.LED.com](http://www.LED.com).



Selectable LED Lamps

### Do more with less.

- Reduce Inventory
- Simplify Projects
- Optimize Solutions



## SpectraChoice™ Type A 4-pin Plug-in

CUSTOMER NAME \_\_\_\_\_  
 PROJECT NAME \_\_\_\_\_  
 DATE \_\_\_\_\_ NOTES \_\_\_\_\_

### Selectable SpectraChoice™ Type A - 4-pin Plug-In Lamps

Bulb Shape	Base Type	Lamp Watts	Order Code	Description	Carton Qty <sup>2</sup>	MOL (In)	Lumens (Initial) <sup>5</sup>	Color Temp* (Initial)	CRI	Wattage Replacement	Rated Life L70 (Hrs) <sup>1</sup>	DLC <sup>4</sup>	Location Rating <sup>3</sup>	Additional Information <sup>^</sup>
<b>Vertical Type A 4-pin</b>														
Plug-In	G24q/GX24q	9	93300089	LED9G24q-V/8SC-4PK	24	5.9	1000 1100 1100 1100	2700K 3000K 3500K 4000K*	80	13/18/26	50,000	-	Damp	SpectraChoice™ Selectable Color Temperature (4000K Default), Requires Electronic Ballast, Fully Enclosed, 4 pack
Plug-In	GX24q	18.5	93314806	LED19GX24q-V/8SC	12	6.5	1850 1850 1850 1850	2700K 3000K 3500K 4000K*	80	32/42	50,000	-	Damp	SpectraChoice™ Selectable Color Temperature (4000K Default), Requires Electronic Ballast
<b>Horizontal Type A 4-pin</b>														
Plug-In	GX24q	18.5	93314804	LED19GX24q-H/8SC	12	6.8	1850 1850 1850 1850	2700K 3000K 3500K 4000K*	80	32/42	50,000	-	Damp	SpectraChoice™ Selectable Color Temperature (4000K Default), Requires Electronic Ballast

<sup>1</sup> The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen output (L70)

<sup>2</sup> Minimum order quantity = Carton Qty

<sup>3</sup> UL 1993 Environmental Requirements for LED LAMPS

<sup>4</sup> Damp Location - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to electrical equipment, including partially protected locations

<sup>5</sup> Not all product variations on this page are DLC qualified. Visit [qpl.designlights.org/solid-state-lighting](http://qpl.designlights.org/solid-state-lighting) to confirm qualification.

<sup>6</sup> Lumen levels correspond with color temperature for selectable lamps

\* Default color temperature setting is 4000K for selectable lamps

<sup>^</sup> Check ballast compatibility at [LED.com/LED4pin-compatibility](http://LED.com/LED4pin-compatibility)

