



Color :  True White

UPC Code : 078477901014

Country Of Origin : China

Available Colors :


White

OSC10-MWW

Occupancy Sensor, Multi-Technology (PIR/US), Ceiling Mount, 1000SF, True White

Occupancy Sensor lighting control, Ceiling Mounted, Multi-technology, 24VDC, 35mA power consumption, 1000 sq ft, 360 degree (major motion: PIR: 40' diameter; U/S: 46'Lx23'W, minor motion: U/S: 34'Lx17'W), red LED=PIR, green LED=U/S, auto adapting, walk-through, time delay 30s-30m, test mode (6s time delay for 15m with auto exit), connect gray wire for photocell ambient light hold-off. 360 degree harmonic wheel (rotatable), mounting height 8'-10', cUL/NOM listed, CEC Title 24 compliant Color: true-white.

Occupancy Sensor, Ceiling Mounted, Multi-technology, 24VDC, 25mA power consumption, 500 sq ft, 180 degree (major motion: PIR:20' radius; U/S: 23'Lx23'W, minor motion: U/S: 17'Lx17'W), red LED=PIR, green LED=U/S, auto adapting, walk-through, time delay 30s-30m, test mode (6s time delay for 15m with auto exit), connect gray wire for photocell ambient light hold-off, 360 degree harmonic wheel (rotatable), mounting height 8'-10', cUL/NOM listed, CEC Title 24 compliant. Color: true-white.

Technical Information

Product Features

Application : Cafeterias, Classrooms, Computer rooms, Conference rooms, Day care centers, Filing rooms, Workspaces, Open warehouses, Offices with cubicles, Open areas, Restrooms, Stairwells, Storage rooms, Executive, open and private offices

Color : True White

Grade : Commercial

Mounting : Ceiling Mount

Mounting Height (Ft.) : 8-12 FT

Product Line : OSC10

Sensor Technology : Multi-Technology: Passive Infrared (PIR)/Ultrasonic (US)

Sensor Type : Occupancy

Time Delay : 30s-30m

Performance Specifications

Coverage (Sq.Ft.) : 1000

Pattern : 360°

Title 24 Compliant : Yes

Electrical Specifications

Frequency : 40kHz

Power Consumption : 35mA

Voltage : 24 VDC

Standards and Certifications

Listings : cUL/US Certified, can be used to comply with Title 24, Part 6 occupancy sensing requirements

Mechanical Specifications

Mounting Type : Ceiling Mount

Size : Width 4.20" (106.68mm), Depth 1.57" (39.90mm)

Environmental Specifications

Operating Temperature : 0°C to 40°C

Relative Humidity : 0% to 95% non-condensing

Type

Product Type : Occupancy Sensor

Warranty

Warranty : 5-Year Limited

Features and Benefits

- Self-adjusting: internal microprocessor continually analyzes, evaluates and adjusts the sensitivity and time delay. Performance is kept at a maximum and user complaints are eliminated.
- Fast, simple installation: easy ceiling mount, three wire connection (low voltage) and twist-lock sensor attachment for 360° rotation and flexibility
- Maximum reliability, low cost: digital circuitry uses a minimum of components
- Small motion sensitivity: the ultrasonic technology provides excellent small motion sensitivity
- Wide coverage: units from 500 to 2000 sq. ft.

- Rugged, high-impact, injection molded plastic device, custom true white color to meet true white applications
- Applications: cafeterias, conference rooms, day care centers, workspaces, offices with cubicles

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

