

Date: _____ Location: _____

Product: _____ Project: _____

Quantity: _____ Catalog #: _____

LED Cooler Light Family Series

CONSTRUCTION:

Aluminum and PC body. Frosted lens.

OPTICAL SYSTEM:

° beam angle.

WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

ELECTRICAL:

Available as 120-277V.

-28°C to °50C, -20°F to 122°F

INSTALLATION & MOUNTING:

Surface mounting clips with Y-type connecting cord.

CONTROLS & DIMMING:

Non-dimming.

FEATURES

- IP44 rated
- Easy installation and maintenance
- Non-corrosive environments
- Easy to link
- 50,000 hours lifetime

SUITABLE APPLICATIONS

- Food Plants
- Dairy Plants
- Pharmaceutical Plants
- Supermarkets
- Hospitals
- Various Freezers
- Cold Storage



DLC Product ID:

- LOC-4FTCT-18W50K – S-K19HDN
- LOC-5FTCT-23W50K - S-HYNNC5
- LOC-6FTCT-27W50K – S-L3703H




MOUNTING OPTION:



Y-Type connecting cord

OPTIONAL ACCESSORIES:



3-foot Power Input Cord
LOC-CT-3FTINPUT-WP

LENGTH	Vertical Hole Distance	Traverse Hole Distance	Linkable Quantity
4-foot	43.5" (1105mm)	2.25" (57mm)	18 pieces
5-foot	55.31" (1405mm)	2.25" (57mm)	15 pieces
6-foot	65.75" (1670mm)	2.25" (57mm)	12 pieces