

Features & Benefits

- Internal Driver
- Smooth, Consistent Light
- UL for Safety
- No UV, No Mercury
- Long Life
- High CRI
- Instant on, no delay or warm up time
- Convenient and quick installation
- Utilizes 2G11 sockets
- Compatible with controls and sensors
- Works in cold temperature applications
- 5 Year Warranty



Flex™

Internal Driver LED FT Lamp
Commercial Grade LED FT Lamp

Specification Data

Model No.	Replace	Lamp Wattage	Input Voltage	CCT	Initial Lumens	CRI	Lamp Efficacy	THD (%)	Life (hours)
LT40W/835-ID	FT40W	18	120-277	3500	2160	83	120	<20	50000
LT40W/840-ID	FT40W	18	120-277	4000	2160	83	120	<20	50000
LT40W/850-ID	FT40W	18	120-277	5000	2160	83	120	<20	50000
LT40W/830-ID	FT40W	18	120-277	3000	2160	83	120	<20	50000

Wiring diagram



LT series	Overall Length	Base face to top
LT40	54.00 cm/21.26 in	49.30 cm/19.41 in
LT36	42.10 cm/16.58 in	37.40 cm/14.72 in
LT24	32.60 cm/12.84 in	27.80 cm/10.95 in
LT18	23.10 cm/9.10 in	18.30 cm/7.20 in