



Product Number: 67504

Order Abbreviation: LU70/MED

General Description: 70W medium based general lighting high pressure sodium lamp, clear, universal burn

Product Information

Abbrev. With Packaging Info.	LU70MED 20/CS 1/SKU
ANSI Code	S62
ANSI Code 2	S62
Approx. Lumens (initial - horizontal)	6300
Approx. Lumens (initial - vertical)	6300
Approx. Lumens (mean - horizontal)	5350
Approx. Lumens (mean - vertical)	5350
Arc Length (in)	1.09
Arc Length (mm)	27.6
Average Rated Life - Horizontal (hr)	24000
Average Rated Life - (hr)	24000
Avg Rated Life (hrs)	24000
Base	E26 Medium
Bulb	E17
Color Rendering Index (CRI)	22
Color Temperature/CCT (K)	1900
Diameter (in)	2.126
Diameter (mm)	54.00
Family Brand Name	Lumalux®
Fixture Requirement	O
Hot Restrike Time (min)	1 MIN
Lamp Finish	Clear
Light Center Length - LCL (in)	3.42
Light Center Length - LCL (mm)	87
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	725
Maximum Bulb Temperature - Celsius	385
Maximum Overall Length - MOL (in)	5.43
Maximum Overall Length - MOL (mm)	138
Nominal Voltage (V)	52.00
Nominal Wattage (W)	70.00
Operating Position	Universal