



Product Number: 64969

Order Abbreviation: MC70T6/U/G12/830

General Description: METALARC POWERBALL 70W ceramic metal halide tubular T6, clear, universal operation, G12 base, 3000K CCT, 87 CRI, pulse start, enclosed rated, 15 ,000 hour rated life

Product Information

Product Information	
Abbrev. With Packaging Info.	MC70T6UG12830 12/CS 1/SKU
ANSI Code	C139/E
ANSI Code 2	C139/E
Approx. Lumens (initial - horizontal)	7400
Approx. Lumens (initial - vertical)	7000
Approx. Lumens (mean - horizontal)	5600
Approx. Lumens (mean - vertical)	5600
Arc Length (in)	0.29
Arc Length (mm)	7.4
Base	G12
Bulb	T6
Color Rendering Index (CRI)	89
Color Temperature/CCT (K)	3000
Diameter (in)	0.748
Diameter (mm)	19.00
Family Brand Name	POWERBALL® CERAMIC METALARC® TUBULAR SINGLE-ENDED
Fixture Requirement	E
Hot Restrike Time (min)	2-15
Light Center Length - LCL (in)	2.2
Light Center Length - LCL (mm)	56
Maximum Base Temperature - Fahrenheit	536
Maximum Bulb Temperature - Fahrenheit	932
Maximum Overall Length - MOL (in)	3.94
Maximum Overall Length - MOL (mm)	100
Nominal Voltage (V)	95.00
Nominal Wattage (W)	70.00
Operating Position	Universal
Warm-up Time (min)	2-4

Footnotes

- Approved electronic ballast is required, view approved ballast list in Product documents, graphs and images.