



Product Number: 64739

Order Abbreviation: MCP70/U/MED/830 PB

General Description: 70 watt ceramic arc tube, high CRI, color consistent, medium base, open fixture rated, E17, clear metal halide lamp

Product Information

Abbrev. With Packaging Info.	MCP70UMED830 PB 12/CS 1/SKU
ANSI Code	C139/O:C98/O
ANSI Code 2	C98/O, C139/O
Approx. Lumens (initial - horizontal)	5900
Approx. Lumens (initial - vertical)	5900
Approx. Lumens (mean - horizontal)	4365
Approx. Lumens (mean - vertical)	4365
Arc Length (in)	0.26
Arc Length (mm)	6.7
Average Rated Life - Horizontal (hr)	20000
Average Rated Life - (hr)	20000
Avg Rated Life (hrs)	20000
Base	E26 Medium
Bulb	E17
Color Rendering Index (CRI)	88
Color Temperature/CCT (K)	3000
Diameter (in)	2.126
Diameter (mm)	54.00
Family Brand Name	Metalarc® Ceramic
Fixture Requirement	O
Hot Restrike Time (min)	4-6
Lamp Finish	Clear
Light Center Length - LCL (in)	3.39
Light Center Length - LCL (mm)	86
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	5.43
Maximum Overall Length - MOL (mm)	138
Nominal Voltage (V)	97.00
Nominal Wattage (W)	70.00
Operating Position	Universal
Warm-up Time (min)	2-4



Footnotes

- Consult your OSRAM SYLVANIA Lighting Representative for compatible electronic operating systems.
- Use with 4000V pulse rated sockets only.
- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaries. See lamp warning.
- Lamps may be operated on ANSI M98 Compliant Ballast.
- UV-Stop quartz