

# HIGH INTENSITY DISCHARGE

Standard Metal Halide ■■■

| Product Information |      |      |       |                    |       |           | Physical Information |                    |           |          | Photometric Characteristics |                  |                 |                |      |     |              |
|---------------------|------|------|-------|--------------------|-------|-----------|----------------------|--------------------|-----------|----------|-----------------------------|------------------|-----------------|----------------|------|-----|--------------|
| Watts               | Bulb | Base | Item# | Description        | ANSI  | Case Qty. | Finish               | Operating Position | MOL (in)  | LCL (in) | Initial Lumens (lm)         | Mean Lumens (lm) | Avg. Life (Hrs) | Color Temp (K) | CRI  | UPC |              |
| 175                 | ED17 | E26  | 1008  | MH175/ED17/U/4K    | M57/E | -         | 12                   | Clear              | Universal | 5.43     | 3.39                        | 14000            | 9100            | 10000          | 4200 | 65  | 844366010088 |
| 175                 | ED17 | E26  | 1009  | MH175/ED17/C/U/4K  | M57/E | -         | 12                   | Coated             | Universal | 5.43     | 3.39                        | 13300            | 8600            | 10000          | 3800 | 70  | 844366010095 |
| 175                 | ED28 | E39  | 1014  | MH175/ED28/U/4K    | M57/E | -         | 12                   | Clear              | Universal | 8.31     | 5.00                        | 14000            | 9100            | 10000          | 4200 | 65  | 844366010149 |
| 175                 | ED28 | E39  | 1015  | MH175/ED28/C/U/4K  | M57/E | -         | 12                   | Coated             | Universal | 8.31     | 5.00                        | 13600            | 8800            | 10000          | 3800 | 70  | 844366010156 |
| 175                 | T15  | E39  | 1016  | MH175/T15/HOR/4K   | M57/E | -         | 24                   | Clear              | HOR ±15°  | 8.31     | 5.00                        | 14000            | 9100            | 10000          | 4200 | 65  | 844366010163 |
| 250                 | ED28 | E39  | 1017  | MH250/ED28/U/4K    | M58/E | -         | 12                   | Clear              | Universal | 8.31     | 5.00                        | 22000            | 17000           | 10000          | 4200 | 65  | 844366010170 |
| 250                 | ED28 | E39  | 1018  | MH250/ED28/C/U/4K  | M58/E | -         | 12                   | Coated             | Universal | 8.31     | 5.00                        | 21500            | 17000           | 10000          | 3800 | 70  | 844366010187 |
| 250                 | T15  | E39  | 1019  | MH250/T15/HOR/4K   | M58/E | -         | 24                   | Clear              | HOR ±15°  | 8.31     | 5.00                        | 20000            | 14100           | 10000          | 4200 | 65  | 844366010194 |
| 250                 | ET18 | E39  | 1020  | MH250/ET18/HOR/4K  | M58/E | -         | 24                   | Clear              | HOR ±15°  | 9.72     | 5.75                        | 20000            | 13500           | 10000          | 4200 | 65  | 844366010200 |
| 360                 | ED28 | E39  | 1150  | MS360/ED28/ES/U/4K | M59/E | M165/E    | 12                   | Clear              | Universal | 8.31     | 5.00                        | 36000            | 23500           | 20000          | 4200 | 65  | 844366011504 |
| 360                 | ED37 | E39  | 1021  | MS360/ED37/ES/U/4K | M59/E | M165/E    | 12                   | Clear              | Universal | 11.50    | 7.01                        | 36000            | 23500           | 20000          | 4200 | 65  | 844366010217 |
| 400                 | ED28 | E39  | 1022  | MH400/ED28/U/4K    | M59/E | -         | 12                   | Clear              | Universal | 8.31     | 5.00                        | 36000            | 23500           | 20000          | 4200 | 65  | 844366010224 |
| 400                 | ED28 | E39  | 1023  | MH400/ED28/C/U/4K  | M59/E | -         | 12                   | Coated             | Universal | 8.31     | 5.00                        | 34000            | 22000           | 20000          | 3800 | 70  | 844366010231 |
| 400                 | ED37 | E39  | 1024  | MH400/ED37/U/4K    | M59/E | -         | 12                   | Clear              | Universal | 11.50    | 7.01                        | 36000            | 23500           | 20000          | 4200 | 65  | 844366010248 |
| 400                 | ED37 | E39  | 1025  | MH400/ED37/C/U/4K  | M59/E | -         | 12                   | Coated             | Universal | 11.50    | 7.01                        | 34000            | 22000           | 20000          | 3800 | 70  | 844366010255 |
| 400                 | BT37 | E39  | 2414  | MS400/BT37/HOR/4K  | M59/E | -         | 12                   | Clear              | HOR ±15°  | 11.50    | 7.01                        | 36000            | 23500           | 20000          | 4200 | 65  | 844366024146 |
| 400                 | T15  | E39  | 1026  | MH400/T15/HOR/4K   | M59/E | -         | 24                   | Clear              | HOR ±15°  | 9.76     | 5.75                        | 36000            | 23500           | 15000          | 4200 | 65  | 844366010262 |
| 400                 | ET18 | E39  | 1027  | MH400/ET18/HOR/4K  | M59/E | -         | 12                   | Clear              | HOR ±15°  | 9.72     | 5.75                        | 33000            | 21500           | 15000          | 4200 | 65  | 844366010279 |
| 1000                | BT37 | E39  | 1028  | MH1000/BT37/U/4K   | M47/E | -         | 12                   | Clear              | Universal | 11.50    | 7.01                        | 110000           | 93500           | 15000          | 4200 | 65  | 844366010286 |
| 1000                | BT56 | E39  | 1029  | MH1000/BT56/U/4K   | M47/E | -         | 6                    | Coated             | Universal | 15.43    | 7.13                        | 110000           | 93500           | 15000          | 4200 | 65  | 844366010293 |
| 1000                | BT56 | E39  | 1076  | MH1000/BT56/C/U/4K | M47/E | -         | 6                    | Clear              | Universal | 15.43    | 7.13                        | 107000           | 8000            | 15000          | 3800 | 70  | 844366010767 |
| 1500                | BT56 | E39  | 1030  | MH1500/BT56/HBU/4K | M48/E | -         | 6                    | Clear              | HOR-BU    | 15.43    | 7.13                        | 167000           | 140000          | 3000           | 4200 | 65  | 844366010309 |

HID

HALOGEN

CFL

FL

BALLAST

GERMICIDAL