

HIGH INTENSITY DISCHARGE

Standard Metal Halide ■■■

| Product Information | | | | | | | Physical Information | | | | Photometric Characteristics | | | | | | |
|---------------------|------|------|-------|--------------------|-------|-----------|----------------------|--------------------|-----------|----------|-----------------------------|------------------|-----------------|----------------|------|-----|--------------|
| Watts | Bulb | Base | Item# | Description | ANSI | Case Qty. | Finish | Operating Position | MOL (in) | LCL (in) | Initial Lumens (lm) | Mean Lumens (lm) | Avg. Life (Hrs) | Color Temp (K) | CRI | UPC | |
| 175 | ED17 | E26 | 1008 | MH175/ED17/U/4K | M57/E | - | 12 | Clear | Universal | 5.43 | 3.39 | 14000 | 9100 | 10000 | 4200 | 65 | 844366010088 |
| 175 | ED17 | E26 | 1009 | MH175/ED17/C/U/4K | M57/E | - | 12 | Coated | Universal | 5.43 | 3.39 | 13300 | 8600 | 10000 | 3800 | 70 | 844366010095 |
| 175 | ED28 | E39 | 1014 | MH175/ED28/U/4K | M57/E | - | 12 | Clear | Universal | 8.31 | 5.00 | 14000 | 9100 | 10000 | 4200 | 65 | 844366010149 |
| 175 | ED28 | E39 | 1015 | MH175/ED28/C/U/4K | M57/E | - | 12 | Coated | Universal | 8.31 | 5.00 | 13600 | 8800 | 10000 | 3800 | 70 | 844366010156 |
| 175 | T15 | E39 | 1016 | MH175/T15/HOR/4K | M57/E | - | 24 | Clear | HOR ±15° | 8.31 | 5.00 | 14000 | 9100 | 10000 | 4200 | 65 | 844366010163 |
| 250 | ED28 | E39 | 1017 | MH250/ED28/U/4K | M58/E | - | 12 | Clear | Universal | 8.31 | 5.00 | 22000 | 17000 | 10000 | 4200 | 65 | 844366010170 |
| 250 | ED28 | E39 | 1018 | MH250/ED28/C/U/4K | M58/E | - | 12 | Coated | Universal | 8.31 | 5.00 | 21500 | 17000 | 10000 | 3800 | 70 | 844366010187 |
| 250 | T15 | E39 | 1019 | MH250/T15/HOR/4K | M58/E | - | 24 | Clear | HOR ±15° | 8.31 | 5.00 | 20000 | 14100 | 10000 | 4200 | 65 | 844366010194 |
| 250 | ET18 | E39 | 1020 | MH250/ET18/HOR/4K | M58/E | - | 24 | Clear | HOR ±15° | 9.72 | 5.75 | 20000 | 13500 | 10000 | 4200 | 65 | 844366010200 |
| 360 | ED28 | E39 | 1150 | MS360/ED28/ES/U/4K | M59/E | M165/E | 12 | Clear | Universal | 8.31 | 5.00 | 36000 | 23500 | 20000 | 4200 | 65 | 844366011504 |
| 360 | ED37 | E39 | 1021 | MS360/ED37/ES/U/4K | M59/E | M165/E | 12 | Clear | Universal | 11.50 | 7.01 | 36000 | 23500 | 20000 | 4200 | 65 | 844366010217 |
| 400 | ED28 | E39 | 1022 | MH400/ED28/U/4K | M59/E | - | 12 | Clear | Universal | 8.31 | 5.00 | 36000 | 23500 | 20000 | 4200 | 65 | 844366010224 |
| 400 | ED28 | E39 | 1023 | MH400/ED28/C/U/4K | M59/E | - | 12 | Coated | Universal | 8.31 | 5.00 | 34000 | 22000 | 20000 | 3800 | 70 | 844366010231 |
| 400 | ED37 | E39 | 1024 | MH400/ED37/U/4K | M59/E | - | 12 | Clear | Universal | 11.50 | 7.01 | 36000 | 23500 | 20000 | 4200 | 65 | 844366010248 |
| 400 | ED37 | E39 | 1025 | MH400/ED37/C/U/4K | M59/E | - | 12 | Coated | Universal | 11.50 | 7.01 | 34000 | 22000 | 20000 | 3800 | 70 | 844366010255 |
| 400 | BT37 | E39 | 2414 | MS400/BT37/HOR/4K | M59/E | - | 12 | Clear | HOR ±15° | 11.50 | 7.01 | 36000 | 23500 | 20000 | 4200 | 65 | 844366024146 |
| 400 | T15 | E39 | 1026 | MH400/T15/HOR/4K | M59/E | - | 24 | Clear | HOR ±15° | 9.76 | 5.75 | 36000 | 23500 | 15000 | 4200 | 65 | 844366010262 |
| 400 | ET18 | E39 | 1027 | MH400/ET18/HOR/4K | M59/E | - | 12 | Clear | HOR ±15° | 9.72 | 5.75 | 33000 | 21500 | 15000 | 4200 | 65 | 844366010279 |
| 1000 | BT37 | E39 | 1028 | MH1000/BT37/U/4K | M47/E | - | 12 | Clear | Universal | 11.50 | 7.01 | 110000 | 93500 | 15000 | 4200 | 65 | 844366010286 |
| 1000 | BT56 | E39 | 1029 | MH1000/BT56/U/4K | M47/E | - | 6 | Coated | Universal | 15.43 | 7.13 | 110000 | 93500 | 15000 | 4200 | 65 | 844366010293 |
| 1000 | BT56 | E39 | 1076 | MH1000/BT56/C/U/4K | M47/E | - | 6 | Clear | Universal | 15.43 | 7.13 | 107000 | 8000 | 15000 | 3800 | 70 | 844366010767 |
| 1500 | BT56 | E39 | 1030 | MH1500/BT56/HBU/4K | M48/E | - | 6 | Clear | HOR-BU | 15.43 | 7.13 | 167000 | 140000 | 3000 | 4200 | 65 | 844366010309 |

HID

HALOGEN

CFL

FL

BALLAST

GERMICIDAL